



## TIDALWAVE MD-SERIES PUMPS



MD1500



- Magnetic Induction pumps provide years of service under the demanding conditions of smaller ponds, waterfalls and fountains
- Atlantic MD-Series pumps feature better flows at higher heads, a longer warranty and are easier to service
- Male threads on both inlet and outlet are less restrictive for higher flow
- Volute can be oriented in 4 ways for maximum versatility in placement
- A quarter-turn accesses replaceable impeller assembly for easy periodic cleaning to keep pump running for years
- Large, stable base for anchoring pump may be removed in tight applications
- Removable pre-filter and oversized ceramic shaft reduce internal wear and extend service life
- Included outlet fittings are tapered to fit a wide array of tubing types and sizes
- MD1000 through MD1500 include 1/2" adapters for use with Triton Check Valve and Fountain Plumbing Kits

MODEL	ITEM	LIST	VOLTS	WATTS	INLET	OUTLET	CORD	DIMENSIONS	OUTLET FITTING	WARRANTY
MD250	73822	\$98.99	115	15	1" MIPT	3/4" MIPT	20'	4 1/2"L x 3 1/2"W x 5"H	3/4" - 1" Step	5-year Limited
MD350	73823	\$104.99	115	25	1" MIPT	3/4" MIPT	20'	4 1/2"L x 3 1/2"W x 5"H	3/4" - 1" Step	5-year Limited
MD550	73824	\$116.99	115	40	1" MIPT	3/4" MIPT	20'	4 1/2"L x 3 1/2"W x 5"H	3/4" - 1" Step	5-year Limited
MD750	73825	\$130.99	115	50	1" MIPT	3/4" MIPT	20'	4 1/2"L x 3 1/2"W x 5"H	3/4" - 1" Step	5-year Limited
MD1000	73819	\$190.99	115	90	1 1/2" MIPT	1" MIPT	20'	5 1/2"L x 4 1/4"W x 5 1/2"H	1" - 1 1/2" Step	5-year Limited
MD1250	73820	\$233.99	115	120	1 1/2" MIPT	1" MIPT	20'	5 1/2"L x 4 1/4"W x 5 1/2"H	1" - 1 1/2" Step	5-year Limited
MD1500	73821	\$264.99	115	165	1 1/2" MIPT	1" MIPT	20'	6"L x 4 3/4"W x 6"H	1" - 1 1/2" Step	5-year Limited

MODEL	MAX FLOW (GPH)	5'	10'	15'	20'
MD250	300	65			
MD350	370	145			
MD550	650	385			
MD750	790	465			
MD1000	1080	785	275		
MD1250	1330	1040	580		
MD1500	1560	1255	780		

Recommended Operating Range Best Efficiency Range Do Not Operate Range



## NEPTUN



- Asynchronous fountain pumps are ideal for larger fountains, bubblers and nozzles
- OASE Neptun Pumps offer extraordinary construction and a stable platform for your most exacting fountain applications
- Stainless steel intake screen with large surface area resists clogging for dependable low maintenance performance
- Frost proof down to -4°F for extreme durability
- Integrated thermal protection and grounding plate for unparalleled safety
- Adjustable flow control and rotatable intake for use in shallow water applications
- Inline capable for remote placement outside of water reservoir
- Compact design with removable wide stable base for versatility in multiple applications
- Use OASE Nozzle Extension to extend nozzle height from 11" - 22"
- Includes 1 1/2" x 1" / 1 1/4" / 1 1/2" metric step, 1" x 3/4" / 1" / 1 1/4" metric step, 1" slip x FIPT, 1 1/2" slip x FIPT, 1" FIPT coupling fittings

ITEM	LIST	DESCRIPTION	VOLTS	AMPS	WATTS	CORD	DIMENSIONS	HOSE SIZE	WARRANTY
57394	\$377.99	Neptun 1600	120	0.8	100	20'	19"L x 8 1/2"W x 8"H	3/4", 1", 1 1/4" 1 1/2"	5-year
57096	\$514.99	Neptun 2600	120	1.9	220	20'	21"L x 9 3/4"W x 8 3/4"H	3/4", 1", 1 1/4" 1 1/2"	5-year

ITEM	MAX FLOW (GPH)	5'	10'	15'	20'	25'	30'
57394	1560	1000	540				
57096	2630	2100	1600	950	125		

Recommended Operating Range Best Efficiency Range Do Not Operate Range