



BELAIR WALL 2.0

FREESTANDING AND
RETAINING WALL

CHISELED STONE APPEARANCE
FOR SOPHISTICATED LANDSCAPES

FEATURES & BENEFITS

- Freestanding & gravity walls* can be built up to 3 feet high, including buried course
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer
- Rear-lip on retaining wall block makes installation fast and accurate
- Freestanding Walls: 4-foot minimum radius using all 3 units
- Retaining Walls: 1'79.5" Setback/ System batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 8 feet

SHAPES & SIZES**

SRW	FSW
 6 x 6 x 8	 6 x 6 x 5
 6 x 10 x 8	 6 x 10 x 5
 6 x 16 x 8	 6 x 16 x 5

COLUMN/CORNER	
	6 x 16 x 8

TRAPEZOID DOUBLE-SIDED CAP	
	3 x 7 7/8 x 13 3/4

CAP END 3-SIDED	
	3 x 8 x 13 3/4

WALL END 3-SIDED	
	6 x 8 x 11

U START BASE BLOCK*	
	3 1/2 x 18 1/2 x 12

*Gravity wall heights are based on project specific conditions and may be lower than this value.
Check with your local Belgard Representative for product availability and color options.



For more info, visit BelgardCommercial.com

Oldcastle APG - A CRH Company
400 Perimeter Center Terrace, Suite 1000
Atlanta, GA 30346
1-844-495-8210



© 2022 Oldcastle APG, A CRH Company. All Rights Reserved.
BEL20-202 Rev: 4/1 & 2/2022