




AQUALINE™


4½ X 9
PERMEABLE PAVER

LOW MAINTENANCE AND PROVEN DURABILITY THAT ALLOWS FOR FLEXIBLE DESIGN OPTIONS

PALLET LAYOUT



Staked Bond Pallet Layout



90° Herringbone Pallet Layout

FEATURES & BENEFITS

- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Interlocking spacer bars for increased structural performance
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Chamfer Width: 3 mm
- Spacer Bar Width: 10 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 10%


SHAPES & SIZES

PAVER




4½ x 9 x 3/4"

LAYING PATTERNS



RUNNING BOND



HERRINGBONE

Mechanical Installation Available 

Contact your local Belgard® representative for details and mechanical availability.

Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

Check with your local Belgard Representative for product availability and color options.

 BELGARD COMMERCIAL

For more info, visit BelgardCommercial.com

Oldcastle APG - A CRH Company
400 Perimeter Center Terrace, Suite 1000
Atlanta, GA 30346
Ph: 1-844-495-8210



© 2024 Oldcastle APG, A CRH Company. All Rights Reserved.
BEL-20-202 Rev: 10/21/2024