

C/S GRANULAR™

30-50 MESH GRANULAR BENTONITE

CETCO® CRUMBLES # 8

8-20 MESH GRANULAR BENTONITE



DESCRIPTION

C/S GRANULAR and CETCO CRUMBLES are granular bentonite products composed of polymer-free, dried bentonite in various mesh sizes. CETCO CRUMBLES are coarser in size than C/S GRANULAR. C/S GRANULAR and CETCO CRUMBLES are certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals -Health Effects.

RECOMMENDED USE

May be used as casing seal, hole abandonment material, and for sealing earthen structures.

CHARACTERISTICS

- Less than 10% moisture
- Provide a positive seal
- Re-hydrates
- Will not shrink or crack



MIXING AND APPLICATION

Grouting Material	One bag CETCO Crumbles to 24 gallons (91 liters) water or 24 gallons water and 8 ounces (0.25 liters) ACCU-VIS
Dry Shallow Abandonment	Pour required amount directly down borehole; hydrate with freshwater
Earthen Structure Seal	Normal treatment is 3-5 pounds per ft ² (48-80 kg per m ²) depending on soil type

BULK DENSITY

65 lbs/ft³ (1.04 kg/L)

PACKAGING

50 lb (22.7 kg) bag, 48 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

© 2014 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: OCTOBER 2013

TDS_CS_GRANULAR_CETCO_CRUMBLES_AM_EN_201310_v1

