



SDR-26 PRESSURE PIPE 160 PSI PVC1120 ASTM D2241 	SIZE	O.D.	MIN. WALL	WEIGHT PER 100'	SOCKET DEPTH INCHES	FEET PER PALLET	PALLETS PER T.L.	BELLED PART NO.
	1¼"	1.660	.064	20.93	2.750	4000	32	45243
	1½	1.900	.073	27.31	3.000	3600	28	45280
	2	2.375	.091	42.51	3.000	2800	24	45345
	2½	2.875	.110	62.13	3.500	2240	20	45410
	3	3.500	.135	92.81	4.000	1500	20	45470
	4	4.500	.173	156.97	5.000	580	28	47075
	6	6.625	.255	342.71	6.500	400	20	47120
	8	8.625	.332	581.78	7.000	280	16	47735
	10	10.750	.413	904.15	7.500	160	16	47145
	12	12.750	.490	1274.47	8.000	120	12	47155
16	16.000	.616	2026.31	10.000	120	12	47175	

NOTE: 8" SDR-26 IS DUAL MARKED FOR SCH-40 PIPE.

SDR-21 PRESSURE PIPE 200 PSI PVC1120 ASTM D2241 	*½"	.840	.062	9.81	2.000	8400	44	46105
	¾	1.050	.060	12.11	2.125	6600	40	46157
	1	1.315	.063	16.17	2.375	5400	32	46207
	1¼	1.660	.079	25.59	2.750	4000	32	46243
	1½	1.900	.090	33.32	3.000	3600	28	46285
	2	2.375	.113	52.32	3.000	2800	24	46345
	2½	2.875	.137	76.53	3.500	2240	20	46410
	3	3.500	.167	113.71	4.000	1500	20	46470
	4	4.500	.214	192.22	5.000	580	28	47275
	6	6.625	.316	420.11	6.500	400	20	47320
	8	8.625	.410	710.96	7.500	280	16	47335
	10	10.750	.511	1106.58	8.000	160	16	47355
	12	12.750	.606	1560.36	10.000	120	12	47375

*SDR 13.5 - 315 PSI. NOT RECOMMENDED FOR THREADING.

STANDARD LENGTH 20' EXCEPT 4", 6", 8", 10", 12", & 16" WHICH ARE 20' LAYING LENGTH.