



PVC-DS PIPE - ASTM D-2729

FORM NO. 562 SPECIFICATIONS

DECEMBER, 2010

WHEN ORDERING ORDER BY PART NUMBER
 ADDITIONAL 10% CHARGE IF NOT ORDERED IN PALLET QUANTITIES.

PVC-DS ASTM D-2729 SOLID & PERFORATED	SIZE	O.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	PART NO. SOLID	PART NO. PERF.
	3	3.250	.070	45.45	1000	32	52805	52880
	4	4.215	.075	63.57	900	24	52815	52910
	4*	4.215	.075	63.57	900	24		52935
	6	6.275	.100	126.43	350	24	52155	52260

FURNISHED IN 10' LENGTHS BELLED END.

CRESLINE PVC-DS PIPE CONFORMS TO ASTM D-2729 SPECIFICATIONS.

PERFORATED WITH 2 ROWS OF 5/8" HOLES ON 5" CENTERS 120° APART. MEETS MICHIGAN STANDARD.

*PERFORATED WITH 3 ROWS OF 5/8" HOLES ON 5" CENTERS 120° APART. MEETS INDIANA CODE.

PVC SOLVENT CEMENT LISTED ON FORM NO. 466.

PRICES ARE LISTED ON CRESLINE MASTER LIST PRICE SHEET FORM NO. MLP-2.



CRESLINE PLASTIC PIPE CO., INC.

600 Cross Pointe Blvd.
 264 Silver Spring Rd.
 2100 South 35th St.
 3801 East Hwy. 31

Evansville, IN 47715
 Mechanicsburg, PA 17050
 Council Bluffs, IA 51501
 Corsicana, TX 75109

812-428-9350
 717-766-2566
 712-322-2294
 903-872-8475

www.cresline.com

Fax 812-428-9353
 Fax 717-697-2371
 Fax 712-322-6673
 Fax 903-872-7732