



<b>SDR-26</b>  <b>PRESSURE PIPE</b>  <b>160 PSI</b>  <b>PVC1120</b>  <b>ASTM D2241</b>  	SIZE	O.D.	MIN. WALL	WEIGHT PER 100'	SOCKET DEPTH INCHES	FEET PER PALLET	PALLETS PER T.L.	BELLED PART NO.
	1¼"	1.660	.064	20.93	2.750	4000	32	45243
	1½	1.900	.073	27.31	3.000	3600	28	45280
	2	2.375	.091	42.51	3.000	2800	24	45345
	2½	2.875	.110	62.13	3.500	2240	20	45410
	3	3.500	.135	92.81	4.000	1500	20	45470
	4	4.500	.173	156.97	5.000	580	28	47075
	6	6.625	.255	342.71	6.500	400	20	47120
	8	8.625	.332	581.78	7.000	280	16	47735
	10	10.750	.413	904.15	7.500	160	16	47145
	12	12.750	.490	1274.47	8.000	120	12	47155
16	16.000	.616	2026.31	10.000	120	12	47175	

NOTE: 8" SDR-26 IS DUAL MARKED FOR SCH-40 PIPE.

<b>SDR-21</b>  <b>PRESSURE PIPE</b>  <b>200 PSI</b>  <b>PVC1120</b>  <b>ASTM D2241</b>  	*½"	.840	.062	9.81	2.000	8400	44	46105
	¾	1.050	.060	12.11	2.125	6600	40	46157
	1	1.315	.063	16.17	2.375	5400	32	46207
	1¼	1.660	.079	25.59	2.750	4000	32	46243
	1½	1.900	.090	33.32	3.000	3600	28	46285
	2	2.375	.113	52.32	3.000	2800	24	46345
	2½	2.875	.137	76.53	3.500	2240	20	46410
	3	3.500	.167	113.71	4.000	1500	20	46470
	4	4.500	.214	192.22	5.000	580	28	47275
	6	6.625	.316	420.11	6.500	400	20	47320
	8	8.625	.410	710.96	7.500	280	16	47335
	10	10.750	.511	1106.58	8.000	160	16	47355
	12	12.750	.606	1560.36	10.000	120	12	47375

\*SDR 13.5 - 315 PSI. NOT RECOMMENDED FOR THREADING.

STANDARD LENGTH 20' EXCEPT 4", 6", 8", 10", 12", & 16" WHICH ARE 20' LAYING LENGTH.

**PRESSURE RATINGS  
FOR CRESLINE - PVC PIPES  
AT 73.4° F**

SIZE	½	¾	1	1¼	1½	2	2½	3	4	6	8	10	12	16
SDR-26	--	--	--	160	160	160	160	160	160	160	160	160	160	160
SDR-21	315	200	200	200	200	200	200	200	200	200	200	200	200	--

**CONVERSION CHART FOR PRESSURE RATINGS  
AT VARIOUS TEMPERATURES FOR CRESLINE - PVC PIPE**

TEMPERATURE °F	73.4°	80°	90°	100°	110°	120°	130°	140°
CONVERSION FACTOR	1.00	.88	.75	.62	.50	.40	.30	.22

PRESSURE RATING IS THE ESTIMATED MAXIMUM PRESSURE THAT WATER AS THE MEDIUM IN THE PIPE CAN EXERT CONTINUOUSLY WITH A HIGH DEGREE OF CERTAINTY THAT FAILURE OF THE PIPE WILL NOT OCCUR.

**DO NOT USE PLASTIC PIPE AND FITTINGS FOR COMPRESSED AIR.**

**PALLET QUANTITY PVC PRESSURE PIPE**

PIPE SIZE	FEET PER PALLET	WT. PER PALLET	
		SDR-26	SDR-21
½	8400	--	824
¾	6600	--	799
1	5400	--	873
1¼	4000	837	1024
1½	3600	983	1200
2	2800	1191	1465
2½	2240	1392	1714
3	1500	1392	1706
4	580	910	1115
6	400	1371	1681
8	280	1629	1991
10	160	1447	1771
12	120	1529	1872
16	120	2432	--

**PVC SDR-26 & SDR-21 CAN BE USED ON  
JET OR SUBMERSIBLE PUMPS OF 1HP OR LESS**

MAXIMUM DEPTH SETTING TO WATER LEVEL IN FT @ 73.4° F			
CRESLINE PVC PRESSURE PIPE	MAX. TANK SHUT-OFF PRESSURE		
	40 PSI	50 PSI	60 PSI
ANY SIZE PVC SDR-26	275'	255'	230'
ANY SIZE PVC SDR-21	365'	345'	320'



**CRESLINE PLASTIC PIPE CO., INC.**

600 Cross Pointe Blvd.  
264 Silver Spring Rd.  
2100 South 35th St.  
3801 East Hwy. 31

Evansville, IN 47715  
Mechanicsburg, PA 17050  
Council Bluffs, IA 51501  
Corsicana, TX 75109

812-428-9350  
717-766-2566  
712-322-2294  
903-872-8475

[www.cresline.com](http://www.cresline.com)

Fax 812-428-9353  
Fax 717-697-2371  
Fax 712-322-6673  
Fax 903-872-7732