


SEPTEMBER, 2020

CWPVC-10

ADDITIONAL 10% CHARGE IF NOT ORDERED IN PALLET QUANTITIES.

PVC SCH 40 RIGID ELECTRICAL CONDUIT 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	BELL END LGTH.	PART NO.
	1/2"	.840	.622	.109	16.12	3000	10'	58015
	3/4	1.050	.824	.113	21.50	4400	10'	58025
	1	1.315	1.049	.133	31.89	3600	10'	58035
						7200	20'	58030
	1 1/4	1.660	1.380	.140	43.24	2000	10'	58047
						4000	20'	58042
	1 1/2	1.900	1.610	.145	51.65	2250	10'	58055
						4500	20'	58050
	2	2.375	2.067	.154	69.85	1400	10'	58065
2800						20'	58060	
2 1/2	2.875	2.469	.203	110.80	930	10'	58075	
					1860	20'	58070	
3	3.500	3.068	.216	145.13	880	10'	58085	
					1760	20'	58080	
4	4.500	4.026	.237	206.63	570	10'	58095	
					1140	20'	58090	

PVC SCH 40 ELECTRICAL CONDUIT IS PRODUCED IN 10' & 20' LENGTHS WITH BELL END.

PVC SCH 40 ELECTRICAL CONDUIT IS GRAY IN COLOR.

PVC SCH 40 ELECTRICAL CONDUIT CONFORMS TO: UL 651 INCLUDING 90° C RATING
NEMA TC 2
SUNLIGHT RESISTANT

% OF TRUCKLOAD PER PALLET		
SIZE	%/TL	%/TL
	10' LGTH.	20' LGTH.
1/2	0.9	--
3/4	2.1	--
1	1.7	3.4
1 1/4	2.3	4.6
1 1/2	2.5	5.0
2	2.1	4.2
2 1/2	2.3	4.6
3	2.9	5.8
4	3.0	6.0

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD • EVANSVILLE, IN 47715 • TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD • PHOENIX, AZ 85009 • TELEPHONE (602) 269-5161

www.cresline.com