



LEMA 1600HE DC Solenoid Actuator & Adapters

Product Features

The LEMA 1600HE solenoid actuator is designed to be used in conjunction with the LEIT system including LEIT 4000, LEIT X and LEIT XRC ambient light powered controllers. It is an encapsulated, watertight, two-way magnetic solenoid actuator that requires minimal power to operate with the LEIT 4000, X and XRC series controllers. Once the original solenoid is removed, the LEMA 1600HE solenoid actuator can be installed with one of our seven adapters, allowing conversion of most brand name valves

Features

- DESIGNED TO WORK WITH LEIT 4000, LEIT X AND XRC CONTROLLERS ONLY
- POTTED TECHNIQUE FOR SEALED, WATERPROOF CONSTRUCTION
- CAPTURED PLUNGER AND SPRING FOR RELIABLE OPERATION
- USES TWO 18 GAUGE COLOR-CODED 18" WIRES
- MADE OF DURABLE PLASTIC

Specifications

- SOLENOID ACTUATOR THREAD: 11/16"-12 UN
- PRESSURE RANGE: 10-150 PSI (.7-10.5 BAR)
- CONTROL ORIFICE: .065 (1.7 MM)
- WEIGHT: 5.3 OZ. (150 G)
- WEIGHT WITH ADAPTER: 5.6 OZ. (160 GRAMS)
- DIMENSION TOP: 1.375" (3.5 CM) L X 1.880" (4.8 CM) W
- DIMENSION BOTTOM: 1.180 (3.0 CM)
- OVERALL LENGTH: 3.1 (7.9 CM)
- OVERALL LENGTH WITH ADAPTER: 3.45 (8.76 CM)
- LEAD WIRES: 18" (45 CM) UL 1015, AWG 16, 300V - RED AND WHITE WIRES
- TEMPERATURE RANGE: 32°F TO 150°F (3°C TO 65°C)