

FERROUS SULFATE

(Iron Sulfate Heptahydrate)

F.W. = 278 CAS# 7782-63-0

GUARANTEED ANALYSIS

Sulfur (S).....	11.0%
Iron (Fe).....	20.0%
(Derived from Ferrous Sulfate)	

COMPLIES WITH AWWA STANDARD

FeSO ₄ ·7H ₂ O	99.00%
pH (1% Solution).....	4.00
Moisture (Free H ₂ O)	0% to 1%
Bulk Density	55 lbs/cu. ft.
Main Particle Size	-20 to + 100 MESH

CAUTION:

**HARMFUL IF INHALED
CAUSES IRRITATION OF EYES, SKIN AND
RESPIRATORY TRACT
HARMFUL IF SWALLOWED**

Avoid breathing dust.

Do not get in eyes, on skin, or on clothing.

Wear eye protection and protective clothing.

Wash thoroughly after handling.

Avoid fumes from welding.

**INGESTION IN LARGE DOSES CAUSES
INTESTINAL DISORDERS.
CONCENTRATED PRODUCT CAN CAUSE
RUST STAINS.
SEE MSDS FOR FURTHER INFORMATION.**

FIRST AID:

In case of contact: Immediately flush eyes and skin with plenty of water for at least 15 minutes. For eyes, get medical attention.

If inhaled: Remove to fresh air.

If swallowed: Induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person.

FOR FIRE:

Will not burn. Treat as for surrounding media. Wear self-contained breathing apparatus and full personal protective equipment.

FOR SPILL:

Sweep up with minimum of dust.
Place on dry, labeled container.

NET 50 LB (22.68 kg)