

Symbol of Quality

GROW MORE



World Headquarters

1311-9

MATERIAL SAFETY DATA SHEET

M.S.D.S.

I -- PRODUCT IDENTIFICATION

TRADE NAME (as labeled) : SILO-TEC (0-0-3)

MANUFACTURER'S NAME : GROW MORE, INC.
15600 New Century Drive
Gardena, CA 90248
Tel: (310) 515-1700
Fax (310) 515-4937

DATE PREPARED/REVISED : July 17, 2003

NAME OF PREPARER : H. Langheim

II -- HAZARDOUS INGREDIENTS

Chemical Name	CAS No. & %	Exposure Limits in Air (give units)		
		ACGH TLV	OSHA PEL	OTHER (specify)
NO KNOWN HAZARDOUS COMPONENTS				

III- PHYSICAL PROPERTIES

VAPOR DENSITY (AIR = 1) : N/A

SPECIFIC GRAVITY : 1.08

SOLUBILITY IN WATER : Completely

VAPOR PRESSURE, mmHg AT 20°C : N/A

APPEARANCE AND ODOR : Clear liquid; pungent odor

MELTING POINT OR RANGE, °F : Not Established

BOILING POINT OR RANGE, °F : N/A

EVAPORATION RATE (BUTYLACETATE = 1) : N/A

GROW MORE

MSDS For Silo-Tec

Page -2-

IV - FIRE AND EXPLOSION

FLASH POINT, °F (Give Method) : Non Flammable
 AUTO IGNITION TEMPERATURE, °F : N/A
 FLAMMABLE LIMITS IN AIR, (Vol. %) : N/A Lower (LRL) : N/A
 Upper (UEL) : N/A

FIRE EXTINGUISHING MATERIALS

___ water spray ___ carbon dioxide other
 ___ foam ___ dry chemical

SPECIAL FIREFIGHTING PROCEDURE: NONE

UNUSUAL FIRE & EXPLOSION HAZARDS: NONE

V - HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE:

INHALED : Vapors could cause slight irritation of mucus membrane
 CONTACT WITH EYES : May cause redness and slight irritation
 ABSORBED THROUGH SKIN : Possible irritation. Will not be absorbed through skin.
 SWALLOWED : Possible abdominal pain and nausea

FIRST AID (EMERGENCY) PROCEDURES:

EYE CONTACT : Flush with large amounts of water for at least 15 minutes. Seek medical Assistance for persistent irritation.
 SKIN CONTACT : Flush with water for at least 5 minutes.
 INHALED : Remove to fresh air.
 SWALLOWED : Give 3 to 4 glasses of milk or water. Seek medical attention if necessary.

SUSPECTED CANCER AGENT?

No. This product's ingredients are not found in the list below.

Yes. FEDERAL OSHA NTP IARC

(California employers using CAL-OSHA regulated carcinogens, must register with CAL-OSHA. The CAL-OSHA and Federal OSHA carcinogen lists are similar).

GROWMORE

MSDS For Silo-Tec

Page -3-

VI – REACTIVITY DATASTABILITY : Stable Unstable

CONDITIONS TO AVOID: High temperature

INCOMPATIBILITY
Material to avoid) : Strong alkalis.HAZARDOUS POLYMERIZATION: May occur will not occur

CONDITIONS TO AVOID : Not known

VII – SPILL, LEAK & DISPOSAL PROCEDURES:

SPILL RESPONSE PROCEDURES (Include employee protection measures): Caution , floors may become slippery. Use absorbent or inert material to clean up.

PREPARING WASTES FOR DISPOSAL (Container types, neutralization), etc.): Customary procedures for industrial waste treatment. Dispose in compliance with Federal, State and local laws.

VIII – SPECIAL HANDLING INFORMATIONVENTILATION & ENGINEERING CONTROLS: Good general ventilation.RESPIRATORY PROTECTION (TYPE): Air Purifying respirator recommended for prolonged exposure..EYE PROTECTION (TYPE): Safety glasses or goggles.GLOVES (SPECIFIC MATERIAL): Rubber glovesOTHER CLOTHING & EQUIPMENT: Safety shower, eye wash station..WORK PRACTICES, HYGIENIC PRACTICES: Wash hands thoroughly with soap and water.OTHER HANDLING & STORAGE REQUIREMENTS: Store in cool dry place..PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Use normal care.