

Direct Bury Connector Kit

FEATURES

- Do not store above 150°F
- U.V. Stabilized
- Insulation material is non-toxic, waterproof and petroleum free.
- Operating temperature 20-150°F
- Voltage 36V Maximum

DBC-R/Y Solid Wire Combinations

#22 SOL or STR	1 2 3 4 5							
#20 SOL or STR	1 2 3 4 5							
#18 SOL	1 2 3 4 5 6							
#16 SOL	1 2 3 4 5 6							
#14 SOL	1 2 3 4 5 6							
#12 SOL	1 2 3 4							
#10 SOL	1 2 3							
R/Y+		1 2 3 4 5 6 #22 STR or SOL	1 2 3 4 5 6 #20 STR or SOL	1 2 3 4 5 6 #18 SOL	1 2 3 4 5 6 #16 SOL	1 2 3 4 5 #14 SOL	1 2 3 4 #12 SOL	1 2 3 #10 SOL



DBC-R/Y

Water proof, direct bury, gel filled splice housings



DBC-BR

Waterproof Logic receiver brass splice kit with direct bury gel filled housing for receiver to two-wire path connection.

Common AWG Wire combination

Quantity	Size	Combination
2-3	#10	1#10 to 1#12
2-4	#12	1#10 to 1 or 2#14
3-4	#14	1#12 to 1 or 2#14
4-6	#16	1#12 to 2 or 3#16

ORDER SPECIFICATION GUIDE : Model

Model

DBC-R/Y = Water proof, direct bury, gel filled splice housings

DBC-BR = Waterproof Logic receiver brass splice kit with direct bury gel filled housing for receiver to two-wire path connection.

DBC-SPL = Direct bury splice kit

