

# MINI-CLIK®

Sensor: **Rain**

## FEATURES

- Easily installs on any automatic irrigation system
- Debris tolerant for reliable operation without unnecessary shutdowns
- Can be set to shut system off from 1/8" to 3/4" of rainfall
- Includes 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Optional user-installed metal gutter mount for Mini-Clik (order SGM)
- Optional user-installed stainless steel sensor guard enclosure for Mini-Clik (order SG-MC, includes Mini-Clik)
- Warranty period: 5 years

## SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: 20 AWG, UL listed, typically interrupts the common ground wire between the solenoid valves and controller



**MINI-CLIK**  
Height: 2"  
Length: 6"



**SG-MC**  
Stainless steel sensor guard enclosure for Mini-Clik. Includes Mini-Clik.  
Height: 5 1/2"  
Length: 3"  
Width: 4"



**SGM**  
Optional gutter mount  
Height: 1/2"  
Length: 3"

### MINI-CLIK®

Model	Description
MINI-CLIK	Wired Rain Sensor
MINI-CLIK-NO	Wired Rain Sensor with "normally-open" switch

# FREEZE-CLIK®

Sensor: **Freeze**

## FEATURES

- Installs easily with no adjustment needed
- Accurate temperature sensing shuts system off when air temperature reaches 37°F
- Used with other sensors to enhance overall efficiency of irrigation systems
- Warranty period: 5 years

Note: Not intended for agricultural applications

## SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: Typically interrupts the common ground wire between the solenoid valves and the controller
- UL listed



**FREEZE-CLIK**  
Height: 2"  
Length: 6"

### FREEZE-CLIK®

Model	Description
FREEZE-CLIK	Wired freeze sensor interrupts irrigation when temperatures drop below 37°F