

MP ROTATOR® 800 SERIES

Radius: 6' to 16'

FEATURES

- Provides coverage from 6' to 16'
- Radius can be reduced up to approximately 25% on all models
- Color-coded for easy identification
- Removable filter screen prevents large objects from clogging nozzle
- Wind-resistant multi-stream technology
- Adjustable arc and radius
- ▶ Automatic matched precipitation
- ▶ Double-pop feature
- ▶ Distribution uniformity
- ▶ Low precipitation rate

OPERATING SPECIFICATIONS

- Recommended operating pressure: 40 PSI
To achieve minimum radius setting: 30 PSI
- MP800SR-90 uses a 60-mesh built-in nozzle filter
- MP800SR-360 and MP815 use a 40-mesh built-in nozzle filter
- Recommended filtering when operating on dirty water
- Hunter's HY filters are a great solution for zone-specific MP800 arrangements

OPTIONS

- Specify Pro-Spray® PRS40 pop-up for accurate pressure regulation to achieve typical radius settings
- Specify Pro-Spray PRS30 for accurate pressure regulation to achieve minimum radius settings

MP800SR 6' to 12' radius



MP800SR-90
90° to 210°



MP800SR-360
360°

MP815 8' to 16' radius



MP815-90
90° to 210°



MP815-210
210° to 270°



MP815-360
360°

MP800SR-90







MP815-90








MP ROTATOR PERFORMANCE DATA

MP800SR
 Radius: 6' to 12'
 Adjustable Arc
 ● Orange and Gray: 90° to 210°
 ● Lime Green and Gray: 360°

MAX RADIUS							MIN RADIUS	
Arc	Pressure PSI	Radius ft.	Flow		Precip in/hr		Radius ft.	Flow GPM
			GPM	GPH	■	▲		
90° 	30	8	0.17	9.6	0.90	1.04	6	0.13
	35	9	0.21	11.4	0.89	1.03	7	0.15
	40	10	0.23	13.8	0.83	0.96	8	0.16
	45	11	0.25	15.0	0.80	0.92	8	0.18
	50	11	0.27	16.2	0.79	0.92	9	0.19
180° 	30	8	0.33	19.2	0.88	1.02	6	0.26
	35	9	0.38	22.2	0.85	0.99	7	0.29
	40	10	0.42	25.2	0.81	0.93	8	0.32
	45	11	0.46	27.6	0.77	0.88	8	0.36
	50	11	0.48	28.8	0.76	0.88	9	0.38
210° 	30	8	0.35	22.2	0.80	0.93	6	0.30
	35	9	0.38	26.4	0.77	0.89	7	0.34
	40	10	0.43	29.4	0.81	0.91	8	0.37
	45	10	0.45	31.8	0.82	0.95	8	0.42
	50	11	0.49	33.6	0.73	0.85	9	0.44
360° 	30	8	0.66	37.8	0.89	1.03	6	0.47
	35	9	0.71	42.0	0.80	0.92	7	0.52
	40	10	0.78	46.8	0.79	0.91	8	0.56
	45	10	0.85	51.0	0.78	0.90	8	0.59
	50	11	0.88	52.8	0.73	0.85	9	0.63
55	12	0.98	58.8	0.70	0.81	10	0.70	

MP ROTATOR PERFORMANCE DATA

MP815
 Radius: 8' to 16'
 Adjustable Arc and Full-Circle
 ● Maroon and Gray: 90° to 210°
 ● Lt. Blue and Gray: 210° to 270°
 ● Olive and Gray: 360°

Arc	Pressure PSI	Radius ft.	Flow		Precip in/hr	
			GPM	GPH	■	▲
90° 	30	14	0.42	25.20	0.83	0.95
	35	15	0.46	27.60	0.79	0.91
	40	15	0.49	29.40	0.84	0.97
	45	16	0.52	31.20	0.78	0.90
	50	16	0.55	33.00	0.83	0.96
180° 	30	13	0.75	45.00	0.85	0.99
	35	14	0.86	51.60	0.84	0.98
	40	15	0.93	55.80	0.80	0.92
	45	15	0.96	57.60	0.82	0.95
	50	16	1.06	63.60	0.80	0.92
210° 	30	13	0.88	52.80	0.86	0.99
	35	14	0.96	57.60	0.81	0.93
	40	15	1.10	66.00	0.81	0.93
	45	15	1.16	69.60	0.85	0.98
	50	16	1.24	74.40	0.80	0.92
270° 	30	13	1.14	68.40	0.87	1.00
	35	14	1.24	74.40	0.81	0.94
	40	15	1.40	84.00	0.80	0.92
	45	15	1.47	88.20	0.84	0.97
	50	16	1.54	92.40	0.77	0.89
360° 	30	13	1.52	91.20	0.87	1.00
	35	14	1.70	102.00	0.83	0.96
	40	15	1.87	112.20	0.80	0.92
	45	15	2.00	120.00	0.86	0.99
	50	16	2.13	127.80	0.80	0.92
55	16	2.26	135.60	0.85	0.98	

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40, pressure regulated at 40 PSI.

MP ROTATOR