

ROAM

Range: **Up to 1,000 ft.**
Type: **Remote**

FEATURES

- Works with Hunter X-Core®, Pro-C®, PCC, Pro-C Hydrowise, ICC2, HCC, I-Core®, ACC, and ACC2 controllers through a SmartPort connection
- 128 programmable addresses for use of multiple Roam remotes in the same neighborhood
- Operate up to 240 stations
- Manually run watering cycles without modifying regular program
- Programmable run times: 1 to 90 minutes
- Range: 1000' (line of sight)
- Warranty: 2 years

REMOTE SPECIFICATION

- Transmitter power source: 4 AAA batteries included
- Receiver power source: 24 VAC, from controller through a SmartPort connector
- System operating frequency: 433 MHz band
- SmartPort connector can be mounted up to 50' (max.) from controller (use ROAM-SCWH shielded cable wiring harness)
- FCC approved: No FCC license required



Transmitter and Receiver

Height: 7"
Width: 2¼"
Depth: 1¼"



SmartPort

Hunter remotes require the installation of a SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.



Wall Mount Bracket for SmartPort

P/N 258200

CONTROLLER ACCESSORIES

ROAM	
Model	Description
ROAM-KIT	Transmitter, receiver, SmartPort wiring harness, and 4 AAA batteries
ROAM-TR	Transmitter unit and 4 AAA batteries included
ROAM-R	Receiver unit

OPTIONS (SPECIFY SEPARATELY)	
Model	Description
ROAM-WH	SmartPort wiring harness (length: 6' pack of 50)
ROAM-SCWH	Shielded SmartPort wiring harness (length: 25')
258200	Wall Mount Bracket for SmartPort