

PRODUCT RECAP

BARE COPPER WIRE

Soft Drawn Bare Copper, Suitable for Grounding Purposes

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	12.4	2x2000', 4x500', 2x1000'
12	Solid	19.8	2x1250', 4x500', 2x1000'
10	Solid	31.5	2x800', 4x500', 1x1000'
8	Solid	50	4x500', 1x1000'
6	Solid	79.5	4x315', 1x500', 1x1000'
4	Solid	126.3	4x200', 1x500', 1x1000'
2	Solid	200.9	2x125', 1x500', 1x1000'
8	7 Str.	51	4x500', 1x1000'
6	7 Str.	81	4x315', 1x500', 1x1000'
4	7 Str.	128.9	4x200', 1x500', 1x1000'
2	7 Str.	204.9	2x125', 1x500', 1x1000'

HUNTER® TWISTED DECODER CABLE

Soft Drawn Bare Copper, PE, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	43.4	1x500', 1x1000', 1x2500'
12	Solid	61.6	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

PARALLEL COMMUNICATION CABLE

Soft Drawn Bare Copper, PVC, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	80	1x500', 1x1000', 1x2500'
12	Solid	103	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

COMMUNICATION CABLES

Soft Drawn Bare Copper

Part No.	Size (AWG)	No. of Pairs	Wt./1000'	Std. Pkg.
PE-39	19	6	167	1x500', 1x1000'
PE-89	22	6	78	1x500', 1x1000'
PE-54	19	3	84	1x500', 1x1000'
DBS203P	20	3	59.7	1x500', 1x1000'
1804S	18	2	65	1x500', 1x1000'

Put-Up Code (P): 1-500', 2-1000'

TRAY CABLE, TYPE TC-DIRECT BURIAL

PVC Insulation with THHN/THWN Inners, 600V Rating

Part No.	Desc.	Wt./1000'	Std. Pkg.
123CTC(P)	12 Str/3 Cond.	141	1x500', 1x1000'
103CTC(P)	10 Str/3 Cond.	209	1x500', 1x1000'
083CTC(P)	8 Str/3 Cond. w/grd	323	1x500', 1x1000'
063CTC(P)	6 Str/3 Cond. w/grd	536	1x500', 1x1000'
043CTC(P)	4 Str/3 Cond. w/grd	701	1x500', 1x1000'
023CTC(P)	2 Str/3 Cond. w/grd	1020	1x500', 1x1000'

Put-Up Code (P): 1-500', 2-1000'

HUNTER® TWISTED DECODER CABLE JACKETED

Soft Drawn Bare Copper, PE, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	55.6	1x500', 1x1000', 1x2500'
12	Solid	75	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

TORO® DECODER CABLE

Soft Drawn Bare Copper, PE, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	76	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

TORO® COMMUNICATION CABLE

Soft Drawn Bare Copper, PVC, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
16	7 Strand	54	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'