

BUBBLER NOZZLES







Deliver a consistent flow regardless of inlet pressure with pressure-compensating bubbler nozzles.

KEY BENEFITS

- Pressure-compensating for constant water flow at any pressure
- Designed for deep watering of planted areas
- Nozzle threaded for use with Pro-Spray
- Warranty period: 2 years

NOZZLES

MULTI-STREAM BUBBLER PERFORMANCE DATA

Arc	Model	Flow GPM	Radius ft.
	MSBN-25Q	0.25	1.0
	MSBN-50Q	0.50	1.5
	MSBN-50H	0.50	1.0
	MSBN-10H	1.00	1.5
	MSBN-10F	1.00	1.0
	MSBN-20F	2.00	1.5

Multi-Stream Bubbler



MULTI-STREAM BUBBLER NOZZLES



MSBN-25Q
Flow: 0.25 GPM



MSBN-50Q/50H
Flow: 0.50 GPM



MSBN-10H/10F
Flow: 1.0 GPM



MSBN-20F
Flow: 2.0 GPM

Notes:





Typical spacing 2' to 4'. Flows shown for pressures between 15 and 70 PSI.



MSBN Installed on PROS-04

Combining Hunter Bubbler Nozzles with the Pro-Spray provides the watering precision of pressure-compensating bubblers paired with the benefit of retracting the nozzle out of sight.

PCN PERFORMANCE DATA

Model	Flow GPM	Pattern Type
 25	0.25	Trickle
 50	0.50	Trickle
 10	1.00	Umbrella
 20	2.00	Umbrella

PCN



PCN BUBBLER NOZZLES



PCN-25
Flow: 0.25 GPM



PCN-50
Flow: 0.50 GPM



PCN-10
Flow: 1.0 GPM




PCN-20
Flow: 2.0 GPM

Notes:

Typical spacing 2' to 4'. Flows shown for pressures between 15 and 70 PSI.

5-CST-B BUBBLER NOZZLE PERFORMANCE DATA

Pressure (PSI)	Radius (ft.)	Flow (GPM)
 20	5	0.30
25	5	0.32
30	5	0.38
35	5	0.40
40	5	0.42

5-CST-B



DUAL-STREAM BUBBLER NOZZLE



5-CST-B