

ACC2

The multi-flow monitoring and management capabilities of ACC2, with the option to upgrade to Centralus cloud-based control, make it the best choice for complex projects.

KEY BENEFITS

- Number of stations:
 - 12 to 225, for large projects
- Up to 6 flow sensor inputs and 6 P/MV outputs
- 32 automatic programs (10 start times each) for precise plant management
- Block function to group stations and consolidate large systems
- Built-in Solar Sync® logic for smart water savings
- Real-time flow monitoring detects and diagnoses leaks in up to 6 flow zones
- Flow management optimizes watering at safe velocities
- High-visibility, full-color display with reversible facepack
- Conditional Response “if/then” programming for active responses to sensor inputs
- User management password protection, with two levels of access
- Optional plug-in communications modules for cloud or network control
- Detailed alarm logs in plain language
- Extreme service lightning protection
- Easy Retrieve® programming backup and restore
- Non-Water Windows to inhibit accidental irrigation

OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Maximum AC current draw: 120 VAC, 2 A/230 VAC, 1 A
- Transformer output: 24 VAC, ~3 A
- P/MV outputs (24 VAC): Up to 6; 3 included, 0.8 A each
- Sensor inputs: 3 Clik, 1 Solar Sync, and up to 6 Flow sensors (3 included)
- Approvals: Wall Mounts IP55, Plastic Pedestal IP34, UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- ROAM/ROAM XL remote controls
- WSS-SEN or SOLAR-SYNC-SEN for automatic water savings
- Flow sensors (up to 6) including Flow-Sync, WFS, and other approved equals
- Centralus central control available with Wi-Fi, LAN, and cellular connection



Metal Wall Mount
(gray or stainless steel)
Height: 15⁷/₁₆"
Width: 15"
Depth: 6¹/₂"



Plastic Wall Mount
Height: 16³/₈"
Width: 16¹/₂"
Depth: 6⁵/₈"



Metal Pedestal
(gray or stainless steel)
Height: 37"
Width: 15¹/₂"
Depth: 5"



Plastic Pedestal
Height: 39¹/₂"
Width: 23¹/₂"
Depth: 17"

Compatible with:



**Solar Sync
Sensor**



**Flow-Sync
Sensor**



ROAM Remote

ROAM XL Remote

WFS Sensor



EPA WaterSense Approved

Add the WaterSense-labeled Solar Sync sensor to improve the water efficiency of this controller.

ADDITIONAL SPECIFICATIONS BY MODEL

ACC2 CONVENTIONAL

- Number of stations:
 - 12 to 54, for large projects
- Simultaneous station operation: Up to 14 solenoids
- Expands in 6-station increments
- Extreme service lightning protection, standard on all A2M-600 output modules
- Station outputs: 0.8 A each

ACC2 CONVENTIONAL MODELS	
Model	Description
A2C-1200-M	12-station base unit controller, expands to 54 stations, gray steel wall mount, outdoor
A2C-1200-P	12-station base unit controller, expands to 54 stations, plastic outdoor wall mount
A2C-1200-SS	12-station base unit controller, expands to 54 stations, stainless steel wall mount, outdoor
A2C-1200-PP	12-station base unit controller, expands to 54 stations, plastic pedestal
A2M-600	6-station plug-in module for use with the A2C-1200 series controllers

ACC2 ACCESSORIES FOR ALL MODELS

ACC2 ACCESSORIES	
Model	Description
A2C-F3	Optional flow meter expansion module (adds 3 inputs)
A2C-LEDKT	External status light shows controller status with door closed
A2C-WIFI	ACC2 Wi-Fi connection
A2C-LAN	ACC2 LAN (Ethernet) connection
A2C-LTE	ACC2 cell connection (monthly service plan required)
ACC-PED	Gray pedestal for wall mount
PED-SS	Stainless steel pedestal for wall mount

ACC2 DECODER

- Number of stations:
 - 75, 150, or 225, for large projects
- Simultaneous station operation: Up to 30 solenoids
- Operates Hunter's premium ICD decoders over ID wire:
 - Up to 10,000' (14 AWG wire)
 - Up to 15,000' (12 AWG wire)
- Up to 3 two-wire paths per output module
- Diagnostics including decoder inventory, wire tracker, solenoid finder, and more

ACC2 DECODER MODELS	
Model	Description
A2C-75D-M	75-station base model, gray metal outdoor, wall mount
A2C-75D-P	75-station base model, plastic outdoor, wall mount
A2C-75D-SS	75-station base model, stainless steel, wall mount
A2C-75D-PP	75-station base model, plastic pedestal
A2C-D75	75-station decoder expansion module

ACC2: REVERSIBLE FACEPACK

