

# I-25

Radius: **37' to 71'**  
Flow: **3.8 to 31.5 GPM**

The reliable, durable, and versatile I-25 offers an expansive nozzle selection that makes it the perfect choice for large turf applications.

## KEY BENEFITS

- Patented automatic arc return feature returns the turret back to the original arc pattern if vandalized; adjustable arc from 50° to 360°
- Non-strippable drive mechanism is protected from damage if turned in the opposite direction of travel
- Part- and full-circle in one model for installation flexibility and reduced inventory
- Color-coded nozzles make identification easy
- QuickCheck™ arc mechanism for fast arc adjustment
- Available stainless steel riser for extra durability
- Drain check valve prevents low-head drainage (up to 10' of elevation)

## OPERATING SPECIFICATIONS

- Nozzle choices: 11
- Radius: 37' to 71'
- Flow: 3.8 to 31.5 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rates: 0.4 in/hr approximately
- Nozzle trajectory: standard = 25°
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Reclaimed water ID
- High-speed rotation

## USER-INSTALLED OPTIONS

- HSJ-1 prefabricated 1" PVC swing joint



### I-25-04

Overall height: 7 7/8"  
Pop-up height: 4"  
Exposed diameter: 1 3/4"  
Inlet size: 1"



### I-25-06

Overall height: 10 1/4"  
Pop-up height: 6"  
Exposed diameter: 1 3/4"  
Inlet size: 1"



### I-25 Reclaimed

Available as a factory-installed option on all models



### I-25 High-Speed

Available as a factory-installed option on stainless steel models

## I-25 (PLASTIC) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04 = 4" pop-up I-25-06 = 6" pop-up	Adjustable arc, plastic riser, check valve, and 5 nozzles	<b>(blank)</b> = No option <b>R</b> = Reclaimed water ID	<b>#4 to #28</b> = Factory-installed nozzle number

## I-25 (STAINLESS STEEL) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04-SS = 4" pop-up I-25-06-SS = 6" pop-up	Adjustable arc, stainless steel riser, check valve, and 5 nozzles	<b>(blank)</b> = No option <b>R</b> = Reclaimed water ID <b>HS</b> = High-speed <b>HS-R</b> = High-speed and reclaimed water ID	<b>#4 to #28</b> = Factory-installed nozzle number

### Examples:

- I-25-04 = 4" pop-up, adjustable arc
- I-25-04-SS-R-18 = 4" pop-up, adjustable arc, stainless steel riser, reclaimed water ID, and #18 nozzle
- I-25-06-SS = 6" pop-up, adjustable arc, stainless steel riser