

# I-20

Radius: **17' to 46'**  
Flow: **0.36 to 14.8 GPM**

The I-20 is loaded with upgraded features such as FloStop control, check valves, and efficient nozzles that make it the perfect choice in a range of applications.

## KEY BENEFITS

- Patented automatic arc return feature returns the turret back to the original arc pattern if vandalized; adjustable arc from 50° to 360°
- Non-strippable drive mechanism is protected from damage if turned in the opposite direction of travel
- Part- and full-circle in one model for flexibility across landscapes and reduced inventory
- Headed and slotted setscrew allows radius adjustment with a Hunter wrench or flat-blade screwdriver
- FloStop® closes the flow of water from individual sprinklers to change the nozzle or perform repairs
- Flat-top nozzles allow fast, easy insertion
- QuickCheck™ arc mechanism for fast arc adjustment
- Available stainless steel riser for extra durability
- Drain check valve prevents low-head drainage (up to 10' of elevation)

## OPERATING SPECIFICATIONS

- Nozzle choices: 34
- Radius: 17' to 47'
- Flow: 0.36 to 14.8 GPM
- Recommended pressure range: 25 to 70 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rate: 0.4 in/hr approximately
- Nozzle trajectory: standard = 25°, low-angle = 13°
- Nozzle racks: 1.5 to 8.0 blue, 2.0 to 4.5 low-angle gray, 0.50 to 3.0 black, 6.0 to 13.0 green, MPR-25, MPR-30, MPR-35
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- No drain check valve (NCV models)
- Reclaimed water ID
- Blue #1.5-4.0 nozzles

## USER-INSTALLED OPTIONS

- HSJ-0 prefabricated ¾" PVC swing joint

### I-20 (PLASTIC) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
<b>I-20-00</b> = Shrub <b>I-20-04</b> = 4" pop-up <b>I-20-06</b> = 6" pop-up <b>I-20-12</b> = 12" pop-up	Adjustable arc, plastic riser, check valve, 8 standard nozzles, and 4 low-angle nozzles	<b>(blank)</b> = No option  <b>NCV</b> = Without check valve (only available on 4" model)  <b>R</b> = Drain check valve and reclaimed water ID	<b>Blue 1.5-8.0</b> <b>Gray low-angle</b> <b>Black short-radius</b> <b>Green high-flow</b> <b>MPR-25-Q, T, H, F</b> <b>MPR-30-Q, T, H, F</b> <b>MPR-35-Q, T, H, F</b> <b>1.5 to 4.0</b> = Only nozzles 1.5-4.0 can be factory-installed

### I-20 (STAINLESS STEEL) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
<b>I-20-04-SS</b> = 4" pop-up <b>I-20-06-SS</b> = 6" pop-up	Adjustable arc, stainless steel riser, check valve, 8 standard nozzles, and 4 low-angle nozzles	<b>(blank)</b> = No option  <b>NCV</b> = Without check valve (only available on 4" model)  <b>R</b> = Drain check valve and reclaimed water ID	<b>Blue 1.5-8.0</b> <b>Gray low-angle</b> <b>Black short-radius</b> <b>Green high-flow</b> <b>MPR-25-Q, T, H, F</b> <b>MPR-30-Q, T, H, F</b> <b>MPR-35-Q, T, H, F</b> <b>1.5 to 4.0</b> = Only nozzles 1.5-4.0 can be factory-installed

Example:

I-20-12-R-4.0 = 12" pop-up, adjustable arc, with reclaimed water ID, and 4.0 nozzle



#### I-20-00

Overall height: 7¾"  
Exposed diameter: 1¾"  
Inlet size: ¾"



#### I-20-04

Overall height: 7½"  
Pop-up height: 4"  
Exposed diameter: 1¾"  
Inlet size: ¾"



#### I-20-06

Overall height: 9¾"  
Pop-up height: 6"  
Exposed diameter: 1¾"  
Inlet size: ¾"



#### I-20-12

Overall height: 17"  
Pop-up height: 12"  
Exposed diameter: 1¾"  
Inlet size: ¾"



#### I-20 Reclaimed

Available as a factory-installed option on all models