

I-50

Radius: **44' to 76'**
Flow: **7.6 to 33.7 GPM**

The high-torque I-50 rotor is engineered to thrive in difficult water-quality conditions within large turf projects.

KEY BENEFITS

- Extra-strong, non-strippable, planetary gear drive mechanism is reliable and durable in harsh water conditions
- Tool-free, part- and full-circle arc adjustment mechanism makes fast, easy installation and reduces inventory (50° to 360°)
- Color-coded nozzles make identification easy
- QuickCheck™ arc mechanism for fast arc adjustment
- Stainless steel riser for extra durability
- Available opposing nozzle model for even watering in full-circle applications (I-50-ON model)
- Drain check valve prevents low-head drainage (up to 15' of elevation)

OPERATING SPECIFICATIONS

- Nozzle choices: 12
- Radius I-50: 44' to 69'
- Radius I-50-ON: 52' to 76'
- Flow I-50: 7.6 to 29.5 GPM
- Flow I-50-ON: 13.0 to 33.7 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rate: 0.4 in/hr approximately
- Nozzle trajectory: standard = 25°
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Reclaimed water ID

USER-INSTALLED OPTIONS

- HSJ-1 prefabricated 1" PVC swing joint



I-50-06-SS

Overall height: 10¼"
Pop-up height: 6"
Exposed diameter: 2"
Inlet size: 1"



I-50-06-SS-ON

Overall height: 10¼"
Pop-up height: 6"
Exposed diameter: 2"
Inlet size: 1"



I-50 Turf Cup Kit Option

Available as a field-installed option on all models
P/N TURFCUPKIT140



I-50 Reclaimed

Available as a factory-installed option on all models

I-50 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-50-06-SS = 6" pop-up	Adjustable arc, stainless steel riser, check valve, and 6 nozzles	(blank) = No option R = Reclaimed water ID	#8 to #25 = Factory-installed nozzle number

I-50-ON - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Opposing Nozzle Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-50-06-SS-ON = 6" pop-up	Full-circle, opposing nozzle, stainless steel riser, check valve, and 6 nozzles	(blank) = No option R = Reclaimed water ID	#15 to #28 = Factory-installed nozzle number

Examples:

I-50-06-SS = 6" pop-up, adjustable arc, stainless steel riser, with check valve

I-50-06-SS-ON-R-3 = 6" pop-up, adjustable arc, stainless steel riser, with check valve, reclaimed water ID, and #23 nozzle

I-50-06-SS-15 = 6" pop-up, adjustable arc, stainless steel riser, with check valve and #15 nozzle

I-50 Opposing Nozzle 360° Model



Below the turret arc adjustment



Robust planetary gear drive for extreme conditions

I-50 NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr	
				■	▲
8 (40) ●	40	44	7.6	0.76	0.87
	50	45	8.4	0.80	0.92
	Lt. Brown	60	46	9.2	0.84
10 (41) ●	50	49	10.3	0.83	0.95
	60	50	11.3	0.87	1.00
	Lt. Green	70	51	12.2	0.90
13 (42) ●	80	51	13.0	0.96	1.11
	50	50	11.1	0.85	0.99
	Lt. Blue	60	51	12.3	0.91
15 (43) ●	70	52	13.3	0.95	1.08
	80	53	14.2	0.97	1.12
	50	54	13.8	0.91	1.05
15 (43) ●	60	55	15.7	1.00	1.15
	70	57	16.6	0.98	1.14
	Gray	80	59	18.3	1.01
23 (44) ●	60	62	21.3	1.07	1.23
	70	64	23.0	1.08	1.25
	Dk. Green	80	65	24.5	1.12
25 (45) ●	90	66	25.9	1.14	1.32
	60	66	23.9	1.06	1.22
	70	67	25.8	1.11	1.28
25 (45) ●	80	68	27.7	1.15	1.33
	90	69	29.5	1.19	1.38


I-50 DUAL OPPOSING NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr		
				■	▲	
15 ●	50	52	13.0	0.46	0.53	
	60	54	13.2	0.44	0.50	
	Gray	70	56	14.4	0.44	0.51
	80	57	15.5	0.46	0.53	
18 ●	50	58	13.7	0.39	0.45	
	60	59	15.2	0.42	0.49	
	Red	70	60	16.6	0.44	0.51
20 ●	80	62	17.8	0.45	0.51	
	60	63	19.1	0.46	0.53	
	Dk. Brown	70	64	20.9	0.49	0.57
23 ●	80	66	22.3	0.49	0.57	
	90	66	23.9	0.53	0.61	
	60	65	20.4	0.46	0.54	
23 ●	70	66	22.3	0.49	0.57	
	80	67	24.0	0.51	0.59	
	Dk. Green	90	68	25.6	0.53	0.62
25 ●	60	66	22.0	0.49	0.56	
	70	68	24.0	0.50	0.58	
	Dk. Blue*	80	69	25.9	0.52	0.60
25 ●	90	70	27.2	0.53	0.62	
	70	70	28.9	0.57	0.66	
	80	72	30.9	0.57	0.66	
28 ●	90	74	32.9	0.58	0.67	
	100	76	33.7	0.56	0.65	

Notes:

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2. Precipitation rates for the ON-Opposing Nozzle model are calculated at 360°.


I-50 NOZZLES



Standard/High-Speed



I-50 NOZZLES



Opposing

Front



Back

