

6000 SERIES INDEXING VALVE



The 6000 line of indexing valves offers exceptional reliability and durability even under the dirtiest water conditions.

Features and Benefits

- **Metal Die-Cast Body** – Durable, long lasting and capable of high pressure applications.
- **Available in 4 and 6 Outlet Models** – Can easily change from two to six watering zones.
- **Simplicity of Design** – Valves are easily maintained and serviced for long product life.
- **Wide Pressure and Flow Operating Range** –
 - PSI Range: 25–150 (1,7–10,3 bar)
 - 15 GPM (57 LPM)
 - Ideal for pump-fed systems or high-flow city water systems
- **Built-in Atmospheric Vacuum Breaker** – Releases any vacuum created between the pump and the valve on shut down.



K-Rain Manufacturing Corp.

1640 Australian Avenue

Riviera Beach, FL 33404 USA

561.844.1002

FAX: 561.842.9493

1.800.735.7246 | www.krain.com

6000 Series Indexing Valves

With a metal die-cast body, the 6000 valves are capable of high pressure applications and are recommended to be used on pump fed systems or high-flow city water systems. The 6000 is also ideal for onsite wastewater and effluent water applications.

The 6000 valve is available in 4 or 6 outlet models that are cammed for 2 to 6 zone operation. With only one moving part (the stem and disc assembly), the valve is easily serviced and maintained.

The valve requires 15 GPM (57 LPM) with pre-installed stem and disk assembly to operate and works at pressures from 25 to 150 PSI (1,7 to 10,3 bar).

Models

FOUR OUTLET MODELS

- 6402** Cammed for 2 Zone Operation
- 6403** Cammed for 3 Zone Operation
- 6404** Cammed for 4 Zone Operation

SIX OUTLET MODELS

- 6605** Cammed for 5 Zone Operation
- 6606** Cammed for 6 Zone Operation

Other options add to part number:

- RCW** Reclaimed Water Use

Accessories*

- P8003050** Stem/disk Assembly Standard Heavy (.032-Red) 15 GPM** (57 LPM)
- P8003051** Stem/disk Assembly Light (.028-White) 10 GPM (38 LPM)
- P8003052** Stem/disk Assembly Extra Light (.025-Blue) 6 GPM (23 LPM)

*Color code identified at the bottom of the disk

**Pre-installed

Specifications

- Construction:
 - Valve Top/Housing: Die Cast Metal
 - Valve Outlets: High Strength ABS Polymer
- Inlet: Threaded 1 1/2" (3,8 cm) NPT Connection
- Outlets: Slip and Glue Connections to 1 1/2" (3,8 cm) PVC Pipe

OPERATING SPECIFICATIONS

- Pressure Rating: 25 - 150 PSI (1,7 to 10,3 bar)
- Flow Range: 15-150 GPM (57-568 LPM)
- Pressure Loss:

4 OUTLET VALVE

Flow Rate - GPM	20	40	60	80	100
PSI Loss	2.5	3.5	5.0	7.5	10.0

6 OUTLET VALVE

Flow Rate - GPM	20	40	60	80	100
PSI Loss	3.0	4.0	6.0	9.0	11.0

DIMENSIONS

- Height: 7" (17,8)
- Width: 8" (20,3)

Installation Tips

We Recommend the Installation of an Atmospheric Vacuum Breaker Between the Pump and the Valve.