



MATERIAL SAFETY DATA SHEET

SSP-1212K

MANUFACTURED BY: SPECIALTY SILICONE PRODUCTS, INC.
 CORPORATE TECHNOLOGY PARK
 3 MC CREA HILL ROAD
 BALLSTON SPA, NY 12020

EMERGENCY TELEPHONE: (518)-885-8826
REVISED: 06/19/2006
PREPARED BY: Frederic E. Sober, Sr.

SUPPLIED BY: SPECIALTY SILICONE PRODUCTS, INC.
 CORPORATE TECHNOLOGY PARK
 3 MC CREA HILL ROAD
 BALLSTON SPA, NY 12020

SECTION I: MATERIAL IDENTIFICATION

MATERIAL ID: SSP-1212K FORMULA: MIXTURE

COLOR: Opaque Transparent

CHEMICAL FAMILY: SILICONE GREASE CHEMICAL NAME: Dimethyl Polysiloxane

EMERGENCY OVERVIEW:

THIS IS A SOLID MIXTURE. NO SIGNIFICANT HAZARDS ARE EXPECTED UNDER NORMAL CONDITIONS OF HANDLING AND USE. REFER TO SPECIFIC INFORMATION THROUGHOUT THIS MSDS.

SECTION 2: CHEMICAL COMPONENTS

HAZARDOUS COMPONENTS	APPROX. WGT. %	ACGIH		OSHA		UNITS	CAS REG NO.
		TWA	STEL	TWA	STEL		
NONE							

SECTION 3: POTENTIAL HEALTH EFFECTS

SIGNS & SYMPTOMS OF EXPOSURE:

INGESTION: NONE KNOWN. SKIN CONTACT: A MILD SKIN IRRITANT

EYE CONTACT: MAY CAUSE MILD EYE IRRITATION INHALATION: NONE KNOWN

MEDICAL CONDITIONS AGGRAVATED: NONE KNOWN

CHRONIC EFFECTS OF EXPOSURE: THIS PRODUCT OR ONE OF ITS INGREDIENTS PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY NTP, IARC, OR OSHA.

PRINCIPAL ROUTES OF EXPOSURE: EYES

OTHER: THIS PRODUCT CONTAINS METHYLPOLYSILOXANE WHICH CAN GENERATE FORMALDEHYDE AT APPROXIMATELY 300°F (150°C) AND ABOVE, IN ATMOSPHERES WHICH CONTAIN OXYGEN. FORMALDEHYDE IS A SKIN AND RESPIRATORY SENSITIZER, EYE AND THROAT IRRITANT, ACUTE TOXICANT, AND POTENTIAL CANCER HAZARD. AN MSDS FOR FORMALDEHYDE IS AVAILABLE FROM SSP.

MATERIAL SAFETY DATA SHEET
SSP-1212K

SECTION 4: FIRST AID

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: NONE KNOWN.

SKIN: WASH WITH SOAP AND WATER.

INHALATION: NONE KNOWN.

EYES: IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION IF ANY IRRITATION PERSISTS.

NOTE TO PHYSICIAN: NONE KNOWN

SECTION 5: FIRE & EXPLOSION

FLASH PT. NA (F) NA (C) BY NA IGNITION TEMP: UNKNOWN (F) UNKNOWN (C)

FLAMMABLE LIMITS IN AIR (5): LOWER: NA UPPER: NA

EXTINGUISHING MEDIA: ALL STANDARD FIRE FIGHTING MEDIA.

SPECIAL FIRE FIGHTING PROCEDURES:

WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

SECTION 6: REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS:

CARBON MONOXIDE
CARBON DIOXIDE
SILICON DIOXIDE
FORMALDEHYDE

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN

CONDITIONS TO AVOID: NONE KNOWN

*** CONTINUED ON NEXT PAGE ***

MATERIAL SAFETY DATA SHEET
SSP-1212K

SECTION 7: SPILL & LEAK RESPONSE

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

SCRAPE, SWEEP OR GATHER UP MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL.

DISPOSAL METHOD: BURY IN A LICENSED LANDFILL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 8: PERSONAL PROTECTION/EXPOSURE CONTROLS:

RESPIRATORY PROTECTION: NONE PROTECTIVE GLOVES: NOT NECESSARY

EYE & FACE PROTECTION: SAFETY GLASSES

ENGINEERING CONTROLS: NONE

SECTION 9: STORAGE & HANDLING:

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE AT AMBIENT TEMPERATURES, PREFERABLY 65°-85° F

SECTION 10: PHYSICAL & CHEMICAL PROPERTIES

PRODUCT INFORMATION:

BOILING POINT:	NA (F) NA (C)	5 VOLATILE BY VOLUME:	<1
VAPOR PRESSURE (20°C):	NA mm hg	EVAPORATION RATE:	NEGLIGIBLE
VAPOR DENSITY (AIR=1):	NA	(BUTYL ACETATE=1)	
FREEZING POINT:	NA (F) NA (C)	SPECIFIC GRAVITY:	>1
MELTING POINT	NA (F) NA (C)	(WATER=1)	
PHYSICAL STATE:	SOLID	DENSITY:	>1
ODOR:	ESSENTIALLY ODORLESS		
COLOR:	TRANSLUCENT	ph:	NA
ODOR THRESHOLD:	NA		
SOLUBILITY IN WATER (20°C):	INSOLUBLE		

*** CONTINUED ON NEXT PAGE ***

MATERIAL SAFETY DATA SHEET
SSP-1212K

SECTION 11: TOXICOLOGICAL INFORMATION

PRODUCT INFORMATION

TOXICITY:

ACUTE ORAL LD ₅₀	NOT TESTED
ACUTE DERMAL LD ₅₀	NOT TESTED
ACUTE INHALATION LC ₅₀	NA

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: NONE KNOWN

CHEMICAL FATE INFORMATION: NONE KNOWN

SECTION 13: REGULATORY INFORMATION

DOT SHIPPING NAME: NOT DOT REGULATED.

DOT HAZARD CLASS: NONE

DOT LABEL(S) NONE

UN/NA NUMBER: NONE

US FEDERAL REGULATIONS:

SARA HAZARD CLASS (SECTION 311, 312):
NONE

SARA SECTION 313: NONE

TSCA: ALL INGREDIENTS IN THIS MATERIAL ARE ON THE TSCA INVENTORY.

*** CONTINUED ON NEXT PAGE ***

MATERIAL SAFETY DATA SHEET
SSP-1212K

SECTION 14: SUPPLEMENTAL INFORMATION

WASTE MANAGEMENT INFORMATION:

THIS PRODUCT AS SOLID IS NOT A HAZARDOUS WASTE ACCORDING TO 40 CFR 261.
DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

HAZARD RATING SYSTEMS

HMIS	FLAMMABILITY	0	REACTIVITY	0	HEALTH	0
NFPA	FLAMMABILITY	0	REACTIVITY	0	HEALTH	0

OTHER:

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS MADE.

KEY:

C:	CEILING LIMIT	NEGL:	NEGLIGIBLE
EST:	ESTIMATED	NF:	NONE FOUND
NA	NOT APPLICABLE	UNKN:	UNKNOWN
NE:	NONE ESTABLISHED	REC:	RECOMMENDED
ND:	NONE DETERMINED	V:	RECOMMENDED BY VENDOR
R:	RECOMMENDED	SKN:	SKIN
		TS:	TRADE SECRET

*** END ***