

LESCO®



Nutra-TECH™

Liquid Nutrition

18-0-6

GUARANTEED ANALYSIS

Total Nitrogen (N) 18.00%
9.00% Urea Nitrogen
9.00% Other Water Soluble Nitrogen*
Soluble Potash (K₂O) 6.00%
Sulfur (S) 1.00%
1.00% Combined Sulfur (S)

Derived from: Urea, Urea-Triazone Solution, Potassium Thiosulfate.

*9.00% Slowly Available Nitrogen from Urea-Triazone Solution.

According to state law in MD, NH, and NJ this product may not be applied at an application rate of more than 0.7 lbs. Nitrogen per 1,000 sq. ft. (in VA - no more than 1 lb. Nitrogen per 1,000 sq. ft.).

KEEP OUT OF REACH OF CHILDREN CAUTION



IN CASE OF SPILL OR MEDICAL EMERGENCY,
CONTACT CHEMTREC 1-800-424-9300

FIRST AID INSTRUCTIONS

If Skin Contact: Wash with soap and water. Consult a physician if any irritation persists.

If in the Eyes: Rinse with clean water for 15 minutes. Seek medical attention if irritation persists.

If Ingested: Call 911 or a physician for treatment advice. When calling a doctor or going for treatment, have the product label in your possession.

Prior to use, read the safety data sheet for additional first aid and safety information.

PRECAUTIONARY STATEMENTS

Avoid getting this product in the eyes or on the skin. When handling this product, it is recommended that you wear safety glasses with side shields (or goggles) and water repellent, chemical-resistant gloves. Do not contaminate food, feed, seed, or water supplies during the application or cleaning of equipment.

Do not apply near water, storm drains, or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn/garden, and sweep any product that lands on the driveway, sidewalk, or street, back onto your lawn/garden.

NET CONTENTS: 2.5 gal (9.46 L)
NET WEIGHT: 25.25 lb (11.45 kg)
DENSITY: 10.1 lb / gal @ 68°F

SiteOne.com/LESCO

F1560
511651-2.5



RECOMMENDED APPLICATION GUIDELINES

Program Type	Application Area	Application Rates & Frequency (Apply in a minimum of 1 to 3 gal (3.8 to 11.4 L) of water volume per 1,000 sq. ft. (93 sq. m.))
Lawn Care	Cool and Warm Season Grasses	Apply 4 to 10 oz (120 to 300 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 4 to 6 weeks as needed
Golf	Greens, Tees and Fairways	Apply 3 to 9 oz (90 to 270 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 10 to 14 days as needed
Athletic Field Management	Sports Turf	Apply 3 to 9 oz (90 to 270 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 10 to 14 days as needed

PRODUCT DESCRIPTION

LESCO® Nutra-TECH 18-0-6 provides Urea, Potassium, and Sulfur for consistent performance in a convenient formulation.

DIRECTIONS FOR USE

LESCO Nutra-TECH 18-0-6 may be applied undiluted or mixed with water when spray equipment requires a higher volume. Avoid high spray volumes (generally over 25 gallons per acre) where possible to avoid run-off. Nitrogen rates of 0.1 to 0.7 lb/1,000 sq. ft. are suggested, depending on application frequency, turf traffic, turf species, and season. For general conditions, apply 0.1 to 0.4 lbs. of N for frequent applications (1 to 2 weeks) or 0.5 to 0.7 lbs. of Nitrogen for less frequent applications (3 to 4 weeks). Apply fertilizer in accordance with best management practices established by your State University or Cooperative Extension Service. Observe and State or Local fertilizer regulations about fertilizer content, application rates, or timing of application specific to your locale.

In the state of Florida, depending on use site, this product should be applied at rates not exceeding those recommended in the following documents:

1. University of Florida, Institute of Food and Agricultural Sciences SL191 "Recommendations for N, P, K and Mg for Golf Course and Athletic Field Fertilization Based on Mehlich III Extractant,"
2. "Best Management Practices for the Enhancement of Environmental Quality on Florida Golf Courses," published by the Florida Department of Environmental Protection,
3. "Florida Friendly Best Management Practices for Protection of Water Resources by the Green Industries," published by the Florida Department of Environmental Protection

STORAGE AND CONTAINER DISPOSAL

Store above 32°F. Store this product in a dry place in the original container only. Keep the lid tightly closed. Keep away from open flames or intense heat. Triple-rinse the container and offer it for recycling or disposal in accordance with federal, state, and local authorities.

CONDITIONS OF SALE, LIMITED WARRANTY, AND LIMITATION OF LIABILITY

LESCO, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the Directions for Use. This limited warranty does not extend to the storage, handling, or use of this product contrary to label instructions or under abnormal conditions, and the buyer assumes the risk of any such storage, handling, or use. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, LESCO, INC. MAKES NO OTHER WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR ANY OTHER EXPRESS OR IMPLIED WARRANTY, EXCEPT AS STATED ABOVE. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, THE EXCLUSIVE REMEDY OF THE BUYER AND/OR USER SHALL BE A REFUND OF THE PRODUCT PURCHASE PRICE OR REPLACEMENT OF THE PRODUCT. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, IN NO EVENT SHALL LESCO, INC. OR ITS AFFILIATES BE LIABLE FOR ANY INCIDENTAL, INDIRECT, CONSEQUENTIAL, OR SPECIAL DAMAGES. LEGAL RIGHTS: THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION. The foregoing Conditions of Sale, Limited Warranty, and Limitation of Liability may not be modified except by written agreement signed by a duly authorized representative of LESCO, Inc.

For product information call 1-800-347-4272, Monday-Friday, 8:00 AM to 5:00 PM EST.

Information regarding the contents and levels of metals in this product is available at: https://www.aapfc.org/heavy_metals.html

Distributed by LESCO, Inc., 24500 Center Ridge Rd, Suite 350, Westlake, OH 44145



511651-2.5 VO

NET CONTENTS: 2.5 gal (9.46 L)
NET WEIGHT: 25.25 lb (11.45 kg)
DENSITY: 10.1 lb / gal @ 68°F

SiteOne.com/LESCO

F1560
511651-2.5