



12-0-0

#### GUARANTEED ANALYSIS

Total Nitrogen (N) .....	12.00%
12.00% Urea Nitrogen (N)	
Sulfur (S) .....	4.00%
4.00% Combined Sulfur (S)	
Iron (Fe) .....	6.00%
6.00% Water Soluble Iron (Fe)	
Manganese (Mn) .....	2.00%
2.00% Water Soluble Manganese (Mn)	

**Derived from:** Urea, Iron Sulfate, and Manganese Sulfate.

According to state law in MD, NH, and NJ this product may not be applied at an application rate of more than 0.7 lbs. Nitrogen per 1,000 sq. ft. (in VA - no more than 1 lb. Nitrogen per 1,000 sq. ft.).

#### PRECAUTIONARY STATEMENTS

Avoid getting this product in the eyes or on the skin. When handling this product, it is recommended that you wear safety glasses with side shields (or goggles) and water-repellent, chemical-resistant gloves. Do not contaminate food, feed, seed, or water supplies during the application or cleaning of equipment.

Do not apply near water, storm drains, or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn/garden, and sweep any product that lands on the driveway, sidewalk, or street, back onto your lawn/garden.

#### FIRST AID INSTRUCTIONS

**If Skin contact:** Wash with soap and water. Consult a physician if any irritation persists.  
**If in the Eyes:** Rinse with clean water for 15 minutes. Seek medical attention if irritation persists.

**If Ingested:** Call 911 or a physician for treatment advice. When calling a doctor or going for treatment, have the product label in your possession.

Prior to use, read the safety data sheet for additional first aid and safety information.

IN CASE OF SPILL OR MEDICAL EMERGENCY,  
CONTACT CHEMTREC 1-800-424-9300

**CAUTION**

KEEP OUT OF REACH OF CHILDREN



**NET CONTENTS: 2.5 GAL (9.46 L)**  
**NET WEIGHT: 28.0 LBS (12.7 KG)**  
**DENSITY: 11.2 LBS / GAL @ 68°F**

[WWW.SITEONE.COM](http://WWW.SITEONE.COM)

511660-2.5



## RECOMMENDED APPLICATION GUIDELINES

Program Type	Application Area	Application Rates & Frequency (Apply in a minimum of 1 to 3 gal. (3.8 to 11.4 liters) of water volume per 1,000 sq. ft. (93 sq. m.)
Lawn Care	Cool and Warm Season Grasses	Apply 6 to 12 oz (180 to 360 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 4 to 6 weeks as needed
Golf	Greens & Tees	Apply 3 to 9 oz (90 to 270 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 10 to 14 days as needed
	Fairways	Apply 3 to 9 oz (90 to 270 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 10 to 14 days as needed
Athletic Field Management	Sports Turf	Apply 3 to 9 oz (90 to 270 ml) per 1,000 sq. ft. (93 sq. m.) Repeat every 10 to 14 days as needed

## PRODUCT DESCRIPTION

LESCO Nutra-TECH 12-0-0 is a liquid fertilizer that contains urea plus a combination of water-soluble iron and water-soluble manganese to help promote dark green color in plants.

## DIRECTIONS FOR USE

Application rates should be based on tissue or petiole analysis. On plants with waxy leaf surfaces, 12 ounces (355 ml) of a non-toxic wetting agent per 100 gallons (380 L) of finished spray will aid leaf penetration. Add LESCO Nutra-TECH 12-0-0 to half of the water, then agitate while adding the remaining water. Add urea or other fertilizers. Add herbicides last while continuing to agitate tank contents. Spray solution as soon as possible. LESCO Nutra-TECH 12-0-0 tank mixes are generally stable; however, agitate before spraying if the spray tank mix has been standing for more than 24 hours.

## STORAGE AND CONTAINER DISPOSAL

Store above 32°F. Store this product in a dry place in the original container only. Keep the lid tightly closed. Keep away from open flames or intense heat. Triple-rinse the container and offer it for recycling or disposal in accordance with federal, state, and local authorities.

## CONDITIONS OF SALE, LIMITED WARRANTY, AND LIMITATION OF LIABILITY

LESCO, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the Directions for Use. This limited warranty does not extend to the storage, handling, or use of this product contrary to label instructions or under abnormal conditions, and the buyer assumes the risk of any such storage, handling, or use. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, LESCO, INC. MAKES NO OTHER WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR ANY OTHER EXPRESS OR IMPLIED WARRANTY, EXCEPT AS STATED ABOVE. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, THE EXCLUSIVE REMEDY OF THE BUYER AND/OR USER SHALL BE A REFUND OF THE PRODUCT PURCHASE PRICE OR REPLACEMENT OF THE PRODUCT. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, IN NO EVENT SHALL LESCO, INC. OR ITS AFFILIATES BE LIABLE FOR ANY INCIDENTAL, INDIRECT, CONSEQUENTIAL, OR SPECIAL DAMAGES. LEGAL RIGHTS: THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION. The foregoing Conditions of Sale, Limited Warranty, and Limitation of Liability may not be modified except by written agreement signed by a duly authorized representative of LESCO, Inc.

Information regarding the contents and levels of metals in this product is available at: [https://www.aapfco.org/heavy\\_metals.html](https://www.aapfco.org/heavy_metals.html)

Information concerning the raw materials composing this product can be obtained by writing to:  
LESCO, Inc., 24500 Center Ridge Rd, Suite 350, Westlake, OH 44145, referring to the item number found on this product label.



barcode here



7 58073 02483 5

**NET CONTENTS: 2.5 GAL (9.46 L)  
NET WEIGHT: 28.0 LBS (12.7 KG)  
DENSITY: 11.2 LBS / GAL @ 68°F**

[WWW.SITEONE.COM](http://WWW.SITEONE.COM)

**F1560  
511660-2.5**