

HydroCover™ – #089772

Wood Blend with Tack

Quality fibers deliver superior results for fewer callbacks...



Advantages:

- Combination of Thermally Refined® wood fiber and cellulose, pre-mixed with a premium polymer tackifier
- HydroCover™ Blend with Tack reduces friction in the hose, while increasing shooting distance
- Eliminates the extra step and mess of field-mixing tackifier
- Provides superior erosion control and germination performance compared to 100% paper
- Delivers up to 15% greater yield to contractors versus competitive blend products without a big jump in price
- Assists in seed survival rates with enhanced water-holding capacity due to Thermally Refined® fibers
- Non-toxic, environmentally safe and biodegradable
- Maximum slope length of 25 feet
- For optimum pumping and application performance, use approved mechanically agitated equipment
- HydroCover Blend with Tack functional longevity is ≤ 3 months



Composition:

Thermally Refined® Wood Fibers – 58% \pm 3%
 Cellulose Fiber – 27% \pm 3%
 Polymer-based Tackifier – 3% \pm 1%
 Moisture Content – 12% \pm 3%

(40) 50-lb bales per pallet

Slope Gradient/Condition

$\leq 4:1$
 $< 4H:1V$ and $\leq 3H:1V$

lb/acre

2000 lb/acre
 2500 lb/acre

