

HydroCover™ – #089785

Wood with Tack

Eliminate the extra step of field mixing!



Advantages:

- Thermally Refined® wood fibers hold 50% more water than competitive wood fiber products
- HydroCover™ Wood with Tack is pre-blended, evenly dispersed within the mulch — no extra bags at the job site!
- Forms a moisture retention blanket, allowing for enhanced germination
- Greater yield — reduces the number of bales you buy and load
- Assists in seed survival rates with enhanced water-holding capacity due to Thermally Refined® fibers
- An environmentally superior product that controls erosion and then decomposes over time
- Greater productivity — eliminates clogs from the coarse fiber found in competitive mulches
- Long wood fibers interlock to safely secure bare soil
- Non-toxic, environmentally safe and biodegradable
- Maximum slope length is 30 feet
- For optimum pumping and application performance, use approved mechanically agitated equipment
- HydroCover Wood with Tack functional longevity is ≤ 3 months



Composition:

Thermally Refined® Wood Fibers – $85\% \pm 3\%$
 Polymer-based Tackifier – $3\% \pm 1\%$
 Moisture Content – $12\% \pm 3\%$

(40) 50-lb bales per pallet

Slope Gradient/Condition

4H:1V	2000 lb/acre
> 4H:1V and $\leq 3H:1V$	2500 lb/acre
> 3H:1V and $\leq 2H:1V$	3000 lb/acre



PROFILE Products LLC · 750 Lake Cook Road · Suite 440 · Buffalo Grove, IL 60089

Technical Assistance: 800-508-8681

www.profileproducts.com