

## HydroCover™ – #089791 Wood Fiber

**TriFlo™** — makes the best hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



### Covers 20–30% more ground than cellulose!

- Thermally Refined® is an advanced technology, which produces fibers that hold 50% more water than competitive wood fiber products
- 100% premium wood fibers maximize coverage and performance, therefore reducing callbacks due to washouts
- Greater yield — reduces the number of bales you buy and load
- Assists in seed survival rates with enhanced water-holding capacity due to Thermally Refined fibers
- An environmentally superior product that controls erosion and then decomposes over time
- Greater productivity — eliminates clogs from the coarse fiber found in competitive mulches
- Long wood fibers interlock to safely secure bare soil
- Non-toxic, environmentally safe and biodegradable
- Maximum slope length of 28 feet
- Use approved mechanically agitated equipment for optimum pumping and application performance
- HydroCover™ Wood functional longevity is  $\leq 3$  months



#### Product Composition:

Thermally Refined® Wood Fibers – 88%  $\pm$  3%  
Moisture Content – 12%  $\pm$  3%  
(40) 50-lb bales per pallet

#### Slope Gradient/Condition

$\leq 4H:1V$   
 $> 4H:1V$  and  $\leq 3H:1V$   
 $> 3H:1V$  and  $\leq 2H:1V$

#### Rate

2000 lb/acre  
2500 lb/acre  
3000 lb/acre

