

LES-TL80(SS) Checklist

<u>Activity</u>	<u>Completed</u>
Assemble unit per instructions	Grease 2 axle fittings
	Tire pressure should be 15 PSI
	Ensure unit pushes easy
Quickly turn pump on then off to verify battery has some power. - If not you will need to charge it for a few hours	
Put 1 gallon of water in the tank and proceed outside	
Turn selector valve (pictured below) to the left position which is to broadcast spray	
Turn pump on & verify water is coming out of nozzle - It might take a moment before it sprays as the pump has to be primed Once output is confirmed, turn the pump off	
Turn selector valve to the right position which is for the spray wand	
Turn pump on, grab the wand assembly, pull the trigger & verify water is coming out of nozzle Once output is confirmed, turn the pump off	
If the weather is such that it is freezing during the day/night you will need to remove the water from the tank, hoses, and pump	
Disconnect electrical harness while displaying (prevents unit from getting turned on and making a mess on your floor)	
Sprayer Reference:	LES-TL80 – 12 Gal Walk Behind Sprayer LES-TL80SS – 12 Gal Walk Behind Sprayer Stain Steel Frame

Item # of Unit:	
Serial # of Unit:	
Completed By:	
Completion Date:	
Customer #/Name:	
Please staple the completed checklist to the sales ticket	

