NOT FOR COLOR MATCH • PROOF IS FOR COLOR BREAKS ONLY

PLEASE NOTE:

Please read and check closely all information on the proof: color, color breaks, spelling, missing text. This information is extremely important. The job will not be sent to print until final ok is received. All information contained with the label and info box are the responsibility of the final approver.

CUSTOMER SIGN OFF

☐ **APPROVED** ☐ **NOT APPROVED**

INITIAL & DATE: _____

COLOR BREAKS ONLY • NOT FOR COLOR MATCH • color proof

PrePress INSTRUCTIONS **Date:** 09/24/08 **Plate#:** 8091-58237G **Job #:** 87724 **Item #:** LM018180000A

Sherwin Williams/58237G M Lesco Tournament Paint **Program:** CS3

Size: (8.625"x7.449") **Artist:** Monica

IMAGES: White.eps, Yellow.eps, Orange.eps, Red.eps, Blue.eps, Green.eps, Tourn background.psd **FOUND IN:** 58237G M/Art Setup

PANTONE® BS Eyemark | PANTONE® Yellow | PANTONE® Magenta | PANTONE® Cyan | PANTONE® Black | PANTONE® Line Black

Revisions: 02/24/09(Amber) Removed the word Golf from front and back panels. 03/06/09(Amber) Cahinged the product name to "Tournament Turf Marking Paint" and removed the word grass. 5/15/09 (Stephanie) Add "A" to the CPN code in glue flap.

LESCO®
Professional Turf Products

TOURNAMENT™
Turf Marking Paint

- Bright, vivid lines
- Long lasting
- Safe on turf
- No-clog nozzle

COLORS AVAILABLE

DANGER! EXTREMELY FLAMMABLE - VAPORS MAY CAUSE FLASH FIRES! CONTENTS UNDER PRESSURE. VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT. Before using, carefully read CAUTIONS on back panel.

¡PELIGRO! ¡EXTREMADAMENTE INFLAMABLE - LOS VAPORES PUEDEN CAUSAR FUEGOS RELÁMPAGOS! CONTENIDO A PRESIÓN. VAPORES NOCIVOS. IRRITA LOS OJOS, PIEL Y VÍAS RESPIRATORIAS. Antes de usarlo, lea cuidadosamente las PRECAUCIONES en la parte posterior de la etiqueta.

17 oz (1 lb 1 oz) • 481 g

Lesco® Tournament™ Marking Paints are specially formulated for bright, vivid lines on turf grass, soil, gravel and pavement.

Applications: Golf courses, landscaping, surveyors, contractors, utilities and athletic fields. Apply by hand or use a marking wand for consistent marking and to reduce back strain. For best results use when can is between 70-80°F. Tap bottom of can until mixing ball breaks loose. Hold can at top and swing bottom of can in a circle until ball travels freely (repeat during extended use for 30 seconds). To spray, invert can and point spray button 4-6 inches above surface. Press button to the side to actuate. After completion of job: Avoid clogging by turning can right side up and spray until only clear gas appears. Wipe any paint off spray button.

- One pass mark for bold, bright, visible markings
- High solids formula for one coat coverage
- UV resistant formula
- Non-clogging, locking spray tip
- Penetrates and adheres to hot, cold or wet surfaces
- VOC/MIR compliant as of August 2008

Las pinturas de marcar de Lesco® están formuladas especialmente para trazar líneas brillantes y vívidas en césped, tierra, grava y pavimento.

Aplicaciones: Campos de golf, jardinería, levantamientos topográficos, contratistas, conducciones de servicio y pistas de atletismo. Aplique con la mano o use una varilla marcadora para dejar marcas uniformes y reducir la tensión en la espalda. Para obtener los mejores resultados, úsela cuando la lata esté a una temperatura entre 70°F y 80°F. Golpee ligeramente el fondo de la lata hasta que se desprenda la bolsa de mezcla. Sujete la lata por la parte de arriba y haga girar en círculo la parte inferior de la lata hasta que la bola se desplace libremente (repita esto durante un empleo prolongado durante 30 segundos). Para rociar, invierta la lata y apunte el botón de rociado a 4-6 pulgadas por encima de la superficie. Oprima el botón hacia un lado para accionar. Después de terminar el trabajo: evite las obstrucciones girando el lado de la lata hacia arriba y rocíe hasta que sólo aparezca gas transparente. Limpie la pintura del botón de rociado.

- Se requiere una sola pasada para obtener marcas bien definidas, brillantes y visibles
- Fórmula de alta concentración de sólidos para lograr una cobertura de una capa
- Fórmula resistente a la luz ultravioleta
- Punta de rociado de bloqueo que no se obstruye
- Penetra y se adhiere a superficies calientes, frías o mojadas
- Cumple con VOC/MIR a partir de Agosto de 2008

CAUTIONS CONTAINS ALIPHATIC HYDROCARBONS, HEXANE, TOLUENE & XYLENE. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. **DO NOT SMOKE -** Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. **CONTENTS UNDER PRESSURE.** Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. **VAPOR HARMFUL.** Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

PRECAUCIONES CONTIENE HIDROCARBUROS ALIFÁTICOS, HEXANO, TOLUENO Y XILENO. ¡PELIGRO! EXTREMADAMENTE INFLAMABLE. Manténgalo alejado del calor, chispas y llamas. Los vapores se acumularán rápidamente y pueden encenderse y explotar. Durante su uso y hasta que los vapores hayan desaparecido: Mantenga ventilado el lugar – **NO FUME -** Apague todo tipo de llamas, llamas de encendido y calentadores - Apague las cocinas, las herramientas y los aparatos eléctricos o cualquier otra fuente de ignición. **CONTENIDO A PRESIÓN.** Evite exponerlo por mucho tiempo a la luz del sol, al calor que irradian los radiadores, cocinas, tanques de agua caliente o a cualquier otra fuente de calor que pueda hacerlo reventar. No perfore, queme o almacene los envases a una temperatura mayor de 49°C (120°F). Manténgalo en posición vertical en un lugar fresco y seco. No tire las latas vacías en los compactadores de basura. **VAPORES NOCIVOS.** Use únicamente con la ventilación adecuada. Evite respirar por mucho tiempo el vapor y la niebla para la atomización. Para evitar ésto, abra las ventanas y las puertas o use otros medios para circular aire puro durante la aplicación y secado. Si le lagrimean los ojos, siente dolor de cabeza o mareo, aumente la circulación de aire puro o use un respirador (aprobado por NIOSH) o salga del lugar. Evite el contacto con los ojos y la piel. Lávese las manos después de usar la pintura. **PRIMEROS AUXILIOS:** Si hubo contacto con los ojos láveselos durante 15 minutos usando mucha agua. Consulte a un médico. Si hubo contacto con la piel, lávese bien la parte afectada con agua y jabón. En caso de existir problema respiratorio, respire aire puro y llame a un médico. **EFECTOS POSTERIORES DEBIDO AL CONTACTO POR MUCHO TIEMPO.** Contiene solventes que pueden causar daños permanentes al cerebro y al sistema nervioso. El uso erróneo deliberadamente concentrando e inhalando el contenido puede ser peligroso y hasta fatal. **CUIDADO:** Este producto contiene químicos que a conocimiento del estado de California puede causar cáncer y defectos de nacimiento u otros daños reproductivos. **NO ES PARA USO INTERNO. MANTÉNGA FUERA DEL ALCANCE DE LOS NIÑOS.**

Manufactured for Lesco:
1301 East 9th Street, Suite 1300 • Cleveland, OH 44114-1849
For MSDS call (800) 321-5325 or refer to www.paintdocs.com.

LESCO is a registered trademark of LESCO Inc.
Tournament is a trademark of LESCO, Inc.
©2008 LESCO Made in the USA / Hecho en los E.E.U.U. 018180000

CPD®

LM018180000A

BLACK EYEMARK PRINTS .0625" AWAY FROM CUT ON BACKSIDE OF LABEL • CODE NUMBER IN GLUE FLAP PRINTS ON FRONT OF LABEL