



LESCO®

STAND-ON APPLICATOR MODEL 200

EQUIPMENT | LSS200160H

The LESCO Model 200 is a rugged ride-on spreader/sprayer that releases both dry and liquid material.



FEATURES AND BENEFITS

- Dual setting spray system allows 3' and 10' spray settings for multiple applications.
- 100% stainless steel frame and coated Peerless transaxle resist corrosive chemicals for added life.
- Narrow width of 35.5" allows for easy access through gates for residential areas and condominium complexes.

SPECS

POWER TRAIN

- Honda Engine: GX200-URH2
- RPM Full Speed: 3,750 RPM (No Load) Idle: 1,400 RPM
- Fuel Capacity: 2.5 gal (9.5 L)
- Fuel Type: Regular unleaded gasoline, 87 octane or higher
- Fuel Shut-Off Valve located on engine and below tank
- Transmission Model: Peerless 855 Series, coated for corrosion resistance

FUNCTIONAL

- Speed (Low Gear): 3.5 mph (5.6 km/hr)
Speed (High Gear): 5.0 mph (8.0 km/hr)
- Spreader Model: Spyker 220 Series
- Spreader Hopper Capacity: 200 lbs.
- Spray Pump 2.0 gpm mechanically driven diaphragm pump
- Sprayer Tank Capacity - gal (L): 16.0 (60.6)
- Nozzles Broadcast: Turbo FloodJet TF-VS5 Trim: TurboTeeJet TT11004VP
- Spray Rate Adjustable from 1/4 to 1/2 gallon per 1000 sq. ft.
- Spreader Warranty Standard: 1 year
Rental: 90 days
- Belts, Tires, Brake Pads, Hoses, Battery
Warranty (Standard): 90 days
Rental: 90 days
- Accessories Warranty Standard: 1 year
Rental: 90 days

DIMENSIONS

- Overall Length: 58.0 in. (147 cm.)
- Overall Width: 35.5 in. (90 cm.)
- Overall Height: 49.0 in. (124 cm.)
- Dry Weight: 450 lbs. (204 kg.)
- Full Weight: 670 lbs. (304kg.)
- Front Tires: 18" x 9.5 - 8
- Rear Tires: 13" x 6.5 - 6

— Exclusively at —
SiteOne
LANDSCAPE SUPPLY

LESCO.com | 800.321.5325