

20-00-20

With Polymer-Coated, Sulfur-Coated Urea (XCU™)

Contains 2% Iron

MINIMUM GUARANTEED ANALYSIS

Total Nitrogen (N)	20.00%
20.000% Urea Nitrogen*	
Soluble Potash (K ₂ O)	20.00%
Sulfur (S)	4.790%
1.395% Free Sulfur (S)	
3.395% Combined Sulfur (S)	
Iron (Fe)	2.000%

Derived From: Urea, Polymer Coated Sulfur Coated Urea, Muriate of Potash, Sulfate of Potash and Iron Sulfate.

*13.95% Slowly available urea nitrogen from Polymer-Coated, Sulfur-Coated Urea.

DIRECTIONS FOR APPLICATION

FOR TURF USES: The best results with this product are obtained when it is applied to actively growing grass, and watered into the turf soon after application. Avoid mowing immediately following application to prevent pick-up. Apply only when foliage is dry. Sweep, brush or blow off any non-target areas to alleviate any staining or unwanted effects.

APPLICATION RATES:		
Desired Nitrogen & Potassium	Lbs. To Apply Per 1000 Sq. Ft.	Lbs. To Apply Per Acre
1.50 Lb(s).	7.50	326.70
1.00 Lb(s).	5.00	217.80
0.75 Lb(s).	3.75	163.35
Age and condition of spreader may cause variations in application rate.		

Recommended applications are at the rate of one pound of nitrogen and potash per 1,000 Sq. Ft. Actual rates and timing of applications will vary with weather, soil and turf conditions.

COVERAGE: 1 - 50 pound bag of 20-00-20 covers approximately 10,000 Sq. Ft. at the application rate of one pound of nitrogen and potash (5.00 lbs. of actual product) per 1,000 sq. ft.

Note: For fertilizer application rates suitable for your geographical area or the maximum allowable non-nutrient application rates per acre, consult a trained soil specialist (local horticulturist) or contact the manufacture or distributor listed below.

CAUTION: THIS PRODUCT CONTAINS MICRO-NUTRIENTS. IT IS HIGHLY RECOMMENDED TO SWEEP OR BLOW OFF ANY NON-TARGET AREAS TO AVOID UNWANTED STAINING. DO NOT WASH OFF WITH WATER.

Manufactured and Guaranteed By:

Mears Fertilizer, Inc.

P.O. Box 1271, 629 North Industrial Road
El Dorado, KS 67042

Phone: (800) 345-9143

FIRST AID & CONTAINER DISPOSAL

FIRST AID

May cause eye or skin irritation (particularly in sensitive persons). May be harmful if swallowed. Product users should wash thoroughly after using or handling this product. In case of eye contact, flush eyes with running water for at least 15 minutes. In case of skin contact, wash from skin with soap and water. In case of ingestion, dilute with water or milk. If necessary, induce vomiting only when victim is conscious. Call a physician.

CAUTION

KEEP OUT OF REACH OF CHILDREN.

HARMFUL IF SWALLOWED. DO NOT INHALE.

STORAGE AND CONTAINER DISPOSAL

- Do not contaminate potable water, ponds, food or feed by storage or disposal. Store in the original container only.
- Completely empty bag into application equipment. Then dispose of empty bag in a sanitary landfill or by incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

LIMIT OF WARRANTY AND LIABILITY

The manufacturer and seller warrant that this product conforms to the chemical description on the label and is reasonably fit for the purpose stated on such label only when used in accordance with the directions under normal use conditions. Except as specifically stated below, NO WARRANTIES, WHETHER EXPRESSED OR IMPLIED, ARE MADE WITH RESPECT TO THE PRODUCT OR ITS USE, AND NO AGENT OF THE MANUFACTURER OR OF THE SELLER IS AUTHORIZED TO DO SO.

Buyer and user of this product assume all responsibility for handling, storage and use not in accordance with directions. It is impossible to eliminate all risks inherently associated with the use of the product. Plant injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond manufacturer's and seller's control. In no case shall the manufacturer or seller be liable for consequential, special or indirect damages resulting from the use or handling of this product.

XCU™ is a registered trademark of Agrium Advanced Technologies.

SGN Size: 200 To 230

Net Wt. 50 Lbs. (22.68 Kgs.)