NON-PRESSURE COMPENSATING DRIPPERS

EASY TO INSTALL IN POLYETHYLENE TUBING

ADAPTABLE TO MANY APPLICATIONS - POSITION THE DRIPPER EXACTLY WHERE IT'S NEEDED

BUTTON DRIPPER (BD)

WOODPECKER DRIPPER (WP)

PRODUCT ADVANTAGES

- Industry's widest flow path and wider dripper cross section allow large particles through the dripper's short flow path.
- Designed with a barbed base for easy installation into blank polyethylene tubing.
- Several flow rates provide adaptability to many applications.

APPLICATIONS

- Vineyards
- Orchards
- Greenhouses and Nurseries

SPECIFICATIONS

- BD Outlet Hole Color and Flow: Red 0.5 GPH, Black 1.0 GPH and Green 2.0 GPH
- WP Base Color and Flow: Red 0.5 GPH, Black 1.0 GPH and Green 2.0 GPH
- Maximum Recommended Operating Pressure: 40 psi
- Recommended Filtration: 120 Mesh
- Barbed outlet of WP Dripper accepts the following micro-tubing: 3mm, 5mm or 1/8"

TURBONET TECHNOLOGY

Improves dripper performance by widening the tooth pattern, maximizing flow path velocity, allowing contaminants to pass easily through the dripper.