

anti-siphon valve bodies

V-19-466 series



features

- reliable brass anti-siphon valve body with back-flow prevention.
- full size water ways for low pressure loss.
- flow range: 5-35 GPM.
- operating pressure 25 - 150 PSI.
- not designed for constant pressure applications.

base model	V-19-466-075Y	V-19-466-100Y	V-19-466P075Y	V-19-466P-100Y
description	3/4" body, with outlet union	1" body, with outlet union	3/4" body, no union	1" body, no union
weight (lbs)	2.2	2.6	1.8	2.34
case qty	25	20	30	20

V-19-466P series



repair & replacement parts

anti-siphon rebuild kit	anti-siphon rebuild kit	3/4" manual anti-siphon valve rebuild kit	1" manual anti-siphon valve rebuild kit		
# RK-4C 3/4" anti-siphon rebuild kit for 466 series AS valves	# RK-5C 1" anti-siphon rebuild kit for 466 series AS valves	# RK-30C seat washer, packing washer, plastic float, float washer, (2) red fiber gasket seals	# RK-31C assembly rebuild kit for 3/4" valves		
anti-siphon cap	anti-siphon cap	anti-siphon cap	anti-siphon cap	anti-siphon cap	
# RK-41C-075 brass anti-siphon cap 3/4"	# RK-41C-100 brass anti-siphon cap 1"	# RK-41C-125 brass anti-siphon cap 1-1/4"	# RK-41C-150 brass anti-siphon cap 1-1/2"	# RK-41C-200 brass anti-siphon cap 2"	