


ORIGINAL TREESTRAP® & COTTON BIODEGRADEABLE TREESTRAP®



- ① TREESTRAP® (SEE PRODUCT SPECIFICATIONS)
- ② WIRE OR GUYING LINE TYPE
14 GAUGE or 12 GAUGE
GALVANIZED WIRE



INSTALLATION NOTES:

INSTALL USING 2 OR 3 TREE STRAPS PER TREE. WRAP STRAP AROUND TREE TRUNK AND FEED WIRE OR GUYING LINE THROUGH GROMMETS AND WIRE TO STAKE OR POST. THESE STRAPS CAN BE USED FOR STAKING TO GROUND, OR GUYING PARELLEL TO TREE. WIRE NEVER GOES AROUND TREE. TO ENHANCE THE BIODEGRADABLE ASPECT, A COTTON CORDAGE MAY BE USED, INSTEAD OF WIRE, WHEN ATTACHING TO STAKES.

SPECIFICATIONS FOR ORIGINAL TREESTRAP®

POLYPROPYLENE (NON-STRETCH) RECOMMENDED
FOR 5 cm-7.5 cm, 2"-3" caliper tree
COLOR: BEIGE
WIDTH: 2.5 cm, 1"
LENGTH: 12", 18" or 24"
BREAK STRENGTH: 90 kg, 200 lbs
WEIGHT: .028 kg, 1 oz each
GROMMETS: 2/#1 Brass

SPECIFICATIONS FOR 3700 SERIES BIODEGRADABLE ORIGINAL TREESTRAP®

COTTON
RECOMMENDED FOR 2"-4" caliber tree
COLOR: Natural/Green (OD)
WIDTH: 2.5 cm, 1"
LENGTH: 30 cm-60 cm, 12" -24"
BREAK STRENGTH: 147 kg, 325 lbs
WEIGHT: .028 kg, 1oz each
GROMMETS: 2/#1 Brass Meets US Green Building Council Standards V4 b,d,c