

FLEXIBLE SWING PIPE

FEATURES/BENEFITS

- Textured material for easy and secure handling in wet or dry conditions
- Kink resistant for enhanced reliability
- Maximum flexibility for use in the most challenging terrain
- Easy-feed packaging so coil remains intact and simple to manage

SPECIFICATIONS

Inside Diameter	0.49"
Outside Diameter	0.686"
Wall Thickness	0.98"
Operating Pressure	Up To 87 psi @ 140°F
Coil Length	100 ft

PRODUCT	DESCRIPTION
PT-SP-100	Flexible Swing Pipe (100 ft coil)



SWING PIPE FITTINGS

FEATURES/BENEFITS

- Acetal material construction for strength and rigidity
- Full offering of shapes and sizes
- Easy to insert and install - no adhesives needed

SPECIFICATIONS

Operating Pressure	Up To 87 psi @ 140°F
--------------------	----------------------

KEY	PRODUCT	DESCRIPTION
A	PT-SPF-ELB50	1/2" MIPT x 1/2" Spiral Barb Elbow (Bag of 20)
B	PT-SPF-ELB75	3/4" MIPT x 1/2" Spiral Barb Elbow (Bag of 20)
C	PT-SPF-TEE50	1/2" Spiral Barb Tee (Bag of 10)
D	PT-SPF-CPL50	1/2" Spiral Barb Coupling (Bag of 10)
E	PT-SPF-ADP50	1/2" MIPT X 1/2" Spiral Barb Adapter (Bag of 10)
F	PT-SPF-ADP75	3/4" MIPT X 1/2" Spiral Barb Adapter (Bag of 10)

