



FEATURES/BENEFITS

- Pressure-compensating flat emitter guarantees maximum emission uniformity
- Premium resin and UV resistance assures durability and longevity
- Anti-siphoning—eliminates dirt and debris entering the system (CV models)
- Non-draining check valve design means no low-point pooling and simultaneous opening/closing of emitters (CV models)
- 7 ft. check height reduces system runoff (CV models)
- Color-coded stripes to easily identify flow rate
- Banded and shrink-wrapped coils stay intact

STRIPE COLOR CODING



| PRODUCT SPECIFICATIONS | |
|--------------------------|---|
| Available Flow Rates | 0.6 GPH and 0.9 GPH |
| Emitter Spacing | 12 in. and 18 in. |
| Tubing Dimensions | 0.660 in. x 0.560 in. (Outside Diameter x Inside Diameter) |
| OPERATING SPECIFICATIONS | |
| Operating Range | 10 PSI to 58 PSI |
| Minimum Filtration | 120 Mesh |
| Warranty | 7 Years |

| MAXIMUM RUN LENGTHS | | | | |
|---------------------|----------------|----------------|----------------|----------------|
| PRESSURE (PSI) | 0.6 GPH | | 0.9 GPH | |
| | 12 in. SPACING | 18 in. SPACING | 12 in. SPACING | 18 in. SPACING |
| 10 | 169 | 216 | 113 | 165 |
| 15 | 246 | 316 | 165 | 241 |
| 20 | 293 | 376 | 197 | 288 |
| 25 | 328 | 423 | 221 | 324 |
| 30 | 358 | 460 | 241 | 352 |
| 35 | 383 | 493 | 258 | 378 |
| 40 | 406 | 523 | 273 | 400 |
| 45 | 426 | 549 | 287 | 420 |
| 50 | 445 | 573 | 300 | 438 |
| 55 | 462 | 595 | 311 | 459 |
| 58 | 472 | 607 | 318 | 465 |

| PRO-TRADE SKU | DESCRIPTION | EMITTER SPACING | FLOW RATE | CHECK VALVE | LENGTH | |
|--------------------|---|-----------------|-----------|-------------|---------|---------|
| PT-DL17-0912CV-100 | Pro-Trade 17mm Dripline CV 0.9 GPH 12 in. 100 ft. | 12 in. | 0.9 GPH | YES | 100 ft. | |
| PT-DL17-0912CV-250 | Pro-Trade 17mm Dripline CV 0.9 GPH 12 in. 250 ft. | | | YES | 250 ft. | |
| PT-DL17-0912CV-500 | Pro-Trade 17mm Dripline CV 0.9 GPH 12 in. 500 ft. | | | YES | 500 ft. | |
| PT-DL17-0912PC-100 | Pro-Trade 17mm Dripline PC 0.9 GPH 12 in. 100 ft. | | | NO | 100 ft. | |
| PT-DL17-0912PC-250 | Pro-Trade 17mm Dripline PC 0.9 GPH 12 in. 250 ft. | | | NO | 250 ft. | |
| PT-DL17-0912PC-500 | Pro-Trade 17mm Dripline PC 0.9 GPH 12 in. 500 ft. | | | NO | 500 ft. | |
| PT-DL17-0612CV-100 | Pro-Trade 17mm Dripline CV 0.6 GPH 12 in. 100 ft. | | | YES | 100 ft. | |
| PT-DL17-0612CV-250 | Pro-Trade 17mm Dripline CV 0.6 GPH 12 in. 250 ft. | | YES | 250 ft. | | |
| PT-DL17-0612CV-500 | Pro-Trade 17mm Dripline CV 0.6 GPH 12 in. 500 ft. | | YES | 500 ft. | | |
| PT-DL17-0612PC-100 | Pro-Trade 17mm Dripline PC 0.6 GPH 12 in. 100 ft. | | NO | 100 ft. | | |
| PT-DL17-0612PC-250 | Pro-Trade 17mm Dripline PC 0.6 GPH 12 in. 250 ft. | | NO | 250 ft. | | |
| PT-DL17-0612PC-500 | Pro-Trade 17mm Dripline PC 0.6 GPH 12 in. 500 ft. | | NO | 500 ft. | | |
| PT-DL17-0918CV-250 | Pro-Trade 17mm Dripline CV 0.9 GPH 18 in. 250 ft. | | 18 in. | 0.9 GPH | YES | 250 ft. |
| PT-DL17-0918CV-500 | Pro-Trade 17mm Dripline CV 0.9 GPH 18 in. 500 ft. | | | | YES | 500 ft. |
| PT-DL17-0918PC-250 | Pro-Trade 17mm Dripline PC 0.9 GPH 18 in. 250 ft. | NO | | | 250 ft. | |
| PT-DL17-0918PC-500 | Pro-Trade 17mm Dripline PC 0.9 GPH 18 in. 500 ft. | NO | | | 500 ft. | |
| PT-DL17-0618CV-250 | Pro-Trade 17mm Dripline CV 0.6 GPH 18 in. 250 ft. | YES | | | 250 ft. | |
| PT-DL17-0618CV-500 | Pro-Trade 17mm Dripline CV 0.6 GPH 18 in. 500 ft. | YES | | 500 ft. | | |
| PT-DL17-0618PC-250 | Pro-Trade 17mm Dripline PC 0.6 GPH 18 in. 250 ft. | NO | | 250 ft. | | |
| PT-DL17-0618PC-500 | Pro-Trade 17mm Dripline PC 0.6 GPH 18 in. 500 ft. | NO | | 500 ft. | | |
| PT-DL17-BLNK100 | Pro-Trade Dripline Blank 100 ft. | N/A | | N/A | N/A | 100 ft. |
| PT-DL17-BLNK250 | Pro-Trade Dripline Blank 250 ft. | | | | N/A | 250 ft. |
| PT-DL17-BLNK500 | Pro-Trade Dripline Blank 500 ft. | | N/A | | 500 ft. | |

