

## Quick-Coupling Valves

Convenient water access in potable and non-potable systems

### Features

- Industrial-strength brass quick-coupling valves for convenient water access in potable and non-potable systems.
- Rugged, red brass construction for long life and reliable performance.
- Reliable leak proof operation with strong corrosion-resistant stainless steel spring.
- Optional locking cover on models 33-DLRC, 44-LRC, 5-LRC, 33-DNP.
- 44-NP and 5-NP (use \* 2049 key to unlock). Metal cover on model 7 only.
- One-piece body design (models 3-RC, 5-RC and 7)
- Two-piece body design for easy servicing (models 33-DLRC, 33-DRC, 44-LRC, 44-RC, 33-DNP, 44-NP, and 44-NP ACME)
- Thermoplastic rubber cover for durability
- 33-DNP, 44-NP, 44-NP ACME, and 5-NP covers marked with "Do Not Drink" warnings in English and Spanish
- Three-year trade warranty

### Specifications

- Pressure: 5 to 125 psi (0.35 to 8.63 bar)
- Flow: 10 to 125 gpm (2.27 to 28.38 m<sup>3</sup>/h; 37.8 to 473 l/m)
- 33-DNP, 44-NP and 5-NP flow: 10 to 70 gpm (2.27 to 15.89 m<sup>3</sup>/h; 37.8 to 265 l/m)

### Models

- 3-RC: 3/4" (20/27) Rubber Cover, 1-Piece Body
- 33-DRC: 3/4" (20/27) Double Track Key Lug, Rubber Cover, 2-Piece Body
- 33-DLRC: 3/4" (20/27) Double Track Key Lug, Locking Rubber Cover, 2-Piece Body
- 44-RC: 1" (26/34) Rubber Cover, 2-Piece Body
- 44-LRC: 1" (26/34) Locking Rubber Cover, 2-Piece Body
- 5-RC: 1" (26/34) Rubber Cover, 1-Piece Body
- 5-LRC: 1" (26/34) Locking Rubber Cover, 1-Piece Body
- 7: 1 1/2" (40/49) Metal Cover, 1-Piece Body
- 5-RC-BSP: 1" (26/34) Rubber Cover, 1-Piece Body, BSP threaded



Quick Coupling Valves



Quick-Coupling Valve Cutaway



33-DNP, 44-NP, 44-NP ACME



7



3-RC, 5-RC, 5-LRC



33-DRC, 33-DLRC, 44-RC, 44-LRC

- 5-LRC-BSP: 1" (26/34) Locking Rubber Cover, 1-Piece Body, BSP threaded
- 33-DNP: 3/4" (20/27) Non-potable, Purple Locking Rubber Cover, 2-Piece Body
- 44-NP: 1" (26/34) Non-potable, Purple Locking Rubber Cover, 2-Piece Body
- 44-NP ACME: 1" (26/34) Non-potable, Purple Locking Rubber Cover, 2-Piece Body, ACME thread
- 5-NP: 1" (26/34) Non-potable, Purple Locking Rubber Cover, 1-Piece Body

*Note: For non-US applications, it is necessary to specify NPT or BSP thread type*

### Dimensions (height)

- 3-RC: 4 1/4" (10.8 cm)
- 33-DRC: 4 3/4" (11.1 cm)
- 33-DLRC: 4 5/8" (11.7 cm)
- 44-RC: 6" (15.2 cm)
- 44-LRC: 6" (15.2 cm)
- 5-RC: 5 1/2" (14.0 cm)

- 5-LRC: 5 1/2" (14.0 cm)
- 7: 5 3/4" (14.6 cm)
- 33-DNP: 4 3/4" (11.1 cm)
- 44-NP: 6" (15.2 cm)
- 44-NP ACME: 6" (15.2 cm)
- 5-NP: 5 1/2" (14.0 cm)

### How To Specify

#### 33 - DLRC

Model	Cover	Thread
33	RC	Blank: NPT
44	DRC	BSP: 5-RC, 5-LRC only
5	DLRC	ACME: 44-NP only
7	LRC	
	DNP	
	NP	

*Note: This specifies a 33-DLRC valve: 3/4" (20/27) quick coupling type; optional locking cover.*