

PCT SERIES PRESSURE COMPENSATING THREADED LOW-FLOW BUBBLERS

Low-Flow Just Got Tougher

- The medium-flow options provide more flexibility for commercial applications
- Color Coded to identify flow rate
- Bubblers are ideal for a variety of applications including shrub plantings, trees, containers, large pots, annual color, and flower beds.

FEATURES

- Durable – Designed for a rugged environment. UV-resistant durable plastic construction with ½" threads.
- Flexible – Pressure compensating design delivers uniform flow throughout a wide pressure range (1.03-3.45 bar).
- Easy to Identify – Color-coded caps make

identifying the flow rate easy. Light Brown = 18.93 l/h, Violet = 26.50 l/h and Green = 37.85 l/h

SPECIFICATIONS

Flow rates: 18.93 to 37.85 l/h
Pressure: 1.03 to 3.45 bar
Required Filtration: 150 micron

Inlet: ½" FPT threads are specifically designed to be used with:

- ½" PVC risers
- Rain Bird 1800 Retrofit kit
- Xeri-Pop spray head
- Shrub adapter



MODELS

PCT-05 (P/N: X73005): Light brown, 18.93 l/h
PCT-07 (P/N: X73007): Violet, 26.50 l/h
PCT-10 (P/N: X73010): Green, 37.85 l/h

XERI-BIRD™ 8-OUTLET EMISSION DEVICE

The Most Flexible and Feature-Rich Multi-Outlet Device on the market

FEATURES

- The only multi-outlet device on the market with 8 configurable ports and 10 flow options for each port for maximum flexibility
- Easy to maintain, because body can be easily removed from riser
- Each port accepts a Xeri-Bug™ Emitter or PC Module for independent flows from (2 to 90 l/h) or use a self-piercing barb connector (SPB-025) for unrestricted flow
- XBD-81 model feature an integral 75 micron filter which is easily serviceable from the top of the unit
- Eight bottom-mounted, sure-grip barbed outlets securely retain

¼" Distribution Tubing (XQ)

- Unique union base nut allows removal of Xeri-Bird 8 body from riser for easy installation and maintenance
- Emitters must be installed inside the Xeri-Bird to prevent excess back pressure

SPECIFICATIONS

Flow rates: 0 to 90 l/h per outlet
Pressure: 1.03 to 3.5 bar

MODEL

XBD-81 (P/N: X61000)



XBD-81

SXB-360 SPYK AND XS-360TS-SPYK

Adjustable Flow Micro-spray on Spike

APPLICATIONS

These adjustable micro-sprinklers with full circle pattern are shipped ready to install. Ideal for shrub plantings, trees, containers and flower beds.

FEATURES

- Micro-Sprinkler mounted on 12.7cm spike
- 360° spray pattern
- Adjust flow and radius by turning outer cap
- Shipped with 4-6 mm barb connection for installation into 13-16 mm tubing.
- Excellent distribution uniformity

SPECIFICATIONS

Pressure: 1 to 2.0 bar
Flow: adjustable from 0 to 49l/h for SXB-360-SPYK and 0 to 90 l/h for XS-360TS-SPYK
Radius: adjustable from 0 to 46 cm for SXB-360-SPYK and from 0 to 2 m to XS-360TS-SPYK

MODELS

XS-360TS-SPYK (P/N: XPD1303)/SXB-360-SPYK (P/N: XPD1403): Adjustable flow micro-spray on spike



PERFORMANCE				
	* (SXB-360-SPYK)		● (XS-360TS-SPYK)	
bar	cm	l/h	m	l/h
1,0	0-19	0-33	0-1,4	0-64
1,5	0-32	0-41	0-1,8	0-78
2,0	0-46	0-49	0-2,0	0-90