

1400 SERIES

Pressure Compensating Full Circle Bubblers

APPLICATIONS

These pressure compensating bubblers are designed for trees, flower and shrub areas where low flow rates are required.

FEATURES

- Pressure compensating between 1.5 and 6.2 bar
- Exceptionally low flow rates
- No adjustment required
- Shipped with inlet filter screen
- Durable, non-corrosive plastic and rubber construction
- Used with ½" (15/21) male threaded risers

SPECIFICATIONS

Flow: 0.06 to 0.46 m³/h
 Spacing: 0.3 to 0.9 m
 Pressure: 1.4 to 6.2 bars

DIMENSIONS

½" (15/21) female threaded inlet
 Height: 2.5 cm
 Top diameter: 2.5 cm

MODELS

1401 (P/N: A16110): 0.06 m³/h
 1402 (P/N: A16120): 0.11 m³/h
 1404 (P/N: A16130): 0.23 m³/h
 1408 (P/N: A16140): 0.46 m³/h



Models	Flow l/h	Pattern
1401	57	Trickles down the riser
1402	114	Trickles down the riser
1404	227	Umbrella pattern
1408	454	Umbrella pattern

PA-8S

Plastic Shrub Adapter for 1800™ and UNI-Spray™ Series Nozzles

APPLICATIONS

Adapts 1800™ and UNI-Spray™ nozzles for use with ½" (15/21) male threaded risers.

FEATURES

- Accepts protective, non-clogging filter screen shipped with nozzles
- ½" (15/21) female inlet threads
- Durable, non-corrosive plastic construction
- Fine top threads accept all Rain Bird plastic spray head nozzles

MODEL

PA-8S
 (P/N: A16501)



1800-EXT

Plastic Extension for Pop-up Spray Heads: 1800™ and UNI-Spray™ Series

APPLICATIONS

The 1800-EXT extension adds an extra 16.5 cm to the pop-up height of all models to avoid spray interference with taller shrubs

MODEL

1800-EXT (P/N: A44500)

FEATURES

- Rugged thermoplastic construction
- Easily installed. No tools required
- Fits all Rain Bird spray heads and nozzles. Exception : cannot be used with bubblers
- Maximum of 2 extensions per pop-up spray head

