

Adhesive

Lasting, beautiful hardscapes depend on adhesives that are easy to use & stand the test of time. That's why we've created a line of adhesives that lock quickly & hold strong.

Our diverse line of adhesives can be used for a variety of projects & many applications including retaining walls, natural stone & veneers.



SEE IT IN ACTION
Vertical Instant Lock Demo

Application Patterns for Optimal Moisture Drainage*

<p>For Superior Strength Solvent-Based & Rapid-Set Polyurethane Adhesive</p> <p>Concrete Overlay</p> <p>Against Building No Water Flow</p> <p>Front & Side Edges Optimal Water Flow</p> <p>Retaining Wall</p> <p>(Very Moist Soil)</p> <p>Optimal Water Flow</p>	<p>For Vertical Instant Lock Adhesive</p> <p>Vertical Applications</p> <p>Top</p> <p>Bottom</p> <p>Optimal Water Flow Using Vertical Instant Lock</p>
---	---



DON'T FORGET!

Don't forget caulking guns! We offer three types of caulking guns, available in 10oz (295ml) & 28oz (828ml) sizes.

*For illustrative purposes only



Vertical Instant Lock



Applications

- ▶ Natural Stone
- ▶ Manufactured Stone
- ▶ Brick, Block & Pavers
- ▶ Metal & Wood
- ▶ Glass & Ceramic Tile
- ▶ Veneers
- ▶ Dry Stack
- ▶ Masonry
- ▶ Outdoor Kitchens
- ▶ Indoor/Outdoor

Benefits

- ▶ Instantly locks building materials in place
- ▶ Low odor, ideal for indoor or outdoor use
- ▶ Repositionable for 10 minutes
- ▶ Quick curing & non-corrosive
- ▶ V-notch nozzle—perfect application every time
- ▶ 12 month shelf life

Details

- ▶ Holds strong in under 5 seconds
- ▶ High temperature compatible
- ▶ VOC compliant
- ▶ Requires a caulking gun with a **minimum 14:1 thrust ratio**.

SRW Vertical Instant Lock Adhesive

PART #	SIZE	AMT PER CTN	QUANTITY
AVIL 10	9.5 oz	12/CTN	64 CTNS/PLT

COVERAGE: Approximate Length of Bead

9.5 oz
210 linear inches

Superior Strength Solvent-Based



Applications

- ▶ Retaining Walls
- ▶ Pavers/Block
- ▶ Firepits
- ▶ Concrete
- ▶ Metals/Wood
- ▶ Natural Stone
- ▶ Works on most common landscaping & construction materials
- ▶ Indoor/Outdoor

Benefits

- ▶ Superior strength & longevity
- ▶ Works on wet or frozen surfaces
- ▶ High temperature compatible
- ▶ Extrudes down to 10°F
- ▶ Interior/exterior use
- ▶ 18 month shelf life

Details

- ▶ VOC compliant option

SRW Superior Strength Solvent-Based Adhesive

PART #	SIZE	AMT PER CTN	QUANTITY
A 10	10 oz	12/CTN	64 CTNS/PLT
A 28	28 oz	12/CTN	44 CTNS/PLT

*Not VOC Compliant

SRW Superior Strength Solvent-Based Adhesive VOC

PART #	SIZE	AMT PER CTN	QUANTITY
AP 10	10 oz	12/CTN	64 CTNS/PLT
AP 28	28 oz	12/CTN	44 CTNS/PLT

COVERAGE: Approximate Length of Bead

Bead Size	10 oz	28 oz
1/4"	32 ft	89 ft
3/8"	14 ft	35 ft

Rapid-Set Polyurethane



Applications

- ▶ Retaining Walls
- ▶ Pavers/Concrete
- ▶ Pool Copings
- ▶ Foam/Vinyl/PVC
- ▶ Firepits
- ▶ Brick
- ▶ Metals/Wood
- ▶ Natural Stone
- ▶ Non-porous substrates
- ▶ Works on most common landscaping & construction materials
- ▶ Indoor/Outdoor

Benefits

- ▶ Fastest set-up time on the market
- ▶ Designed for construction & landscape projects
- ▶ Suitable for dry or damp surfaces
- ▶ High temperature compatible
- ▶ Interior/exterior applications
- ▶ Premium, long-lasting strength
- ▶ 12 month shelf life

Details


- ▶ VOC compliant

SRW Rapid-Set Polyurethane Adhesive


PART #	SIZE	AMT PER CTN	QUANTITY
APU 10	10 oz	12/CTN	64 CTNS/PLT
APU 28	28 oz	12/CTN	44 CTNS/PLT

COVERAGE: Approximate Length of Bead


Bead Size	10 oz	28 oz
1/4"	32 ft	89 ft
3/8"	14 ft	35 ft

 Adhesive APPLICATION CHART PAGES 10-11	Surface Material													
	Retaining Walls	Pavers/Concrete	Pool Copings	Natural Stone & Veneers	Manufactured Stone	Brick	Firepits/Outdoor Kitchens	Masonry	Metals	Wood	Foamboard	Most Plastics	Glass & Mirror	Ceramic Tile
VERTICAL INSTANT LOCK*	X	X		X	X	X	X	X	X	X		X	X	
SUPERIOR STRENGTH SOLVENT	X	X	X	X	X		X	X	X	X				
RAPID-SET POLYURETHANE	X	X	X	X	X	X	X	X	X	X	X			


**Always make sure at least one surface is porous. Always test a small area. Check product label for interior/exterior use.*

 Specialty Seal™ APPLICATION CHART PAGES 14-17	Surface Material										SRW Sealer Benefits				
	Concrete Pavers	Clay Pavers	Granite/Quartz	Limestone	Marble/Travertine	Bluestone/Sandstone	Manufactured Stone	Fieldstone/Boulders	Wetcast	Penetrating/Natural Look	Film-Forming/Enhancing	Reduce Salt & Freeze/Thaw Damage	UV Resistance	Stain Resistance	Commercial Grade
PRX PAVER RESTORE X-TREME	X		X	X	X			X			X	X	X		X
SGX STAIN GUARD X-TREME	X	X							X		X			X	X
JS JOINT STABILIZER	X	X							X	X	X				X
CG COUNTER GUARD			X	X	X	X	X	X	X		X			X	X
2PX TWO PART X-TREME	X	X		X	X						X	X	X		X
S-PS PENETRATING			X	X	X	X	X				X				
S-PSX PENETRATING X-TREME			X	X	X	X	X				X			X	X

Always test a small area. Check product label for interior/exterior use. Refer to surface material manufacturer's recommendations on whether or not to seal.

 Premium Seal™ APPLICATION CHART PAGES 20-21	Surface Material										SRW Sealer Benefits				
	Concrete Pavers	Clay Pavers	Concrete Permeable Pavers	Granite/Quartz	Limestone	Marble/Travertine	Wetcast	Manufactured Stone	Fieldstone	Concrete Retaining Walls	Penetrating/Natural Look	Film-Forming/Enhancing	Reduce Salt & Freeze/Thaw Damage	UV Resistance	Commercial Grade
PSX PENETRATING X-TREME	X	X	X				X	X	X	X	X		X	X	X
LGX LOW GLOSS X-TREME	X			X	X	X	X	X	X			X	X	X	X
HGX HIGH GLOSS X-TREME	X			X	X	X	X	X	X			X	X	X	X
DG DUAL GUARD	X			X	X	X	X	X	X	X		X	X	X	X

Always test a small area. Check product label for interior/exterior use. Refer to surface material manufacturer's recommendations on whether or not to seal.

 Paver Seal™ APPLICATION CHART PAGES 22-23	Surface Material			SRW Sealer Benefits				
	Concrete Pavers	Clay Pavers	Concrete Permeable Pavers	Penetrating/Natural Look	Film-Forming/Enhancing	Reduce Salt & Freeze/Thaw Damage	Stabilizes Joint Sand	UV Resistance
PS PENETRATING	X	X	X	X		X		
LG LOW GLOSS	X				X	X	X	X
HG HIGH GLOSS	X				X	X	X	X

Always test a small area. Check product label for interior/exterior use. Refer to surface material manufacturer's recommendations on whether or not to seal.