

IH-SERIES RISERS

H-SERIES RISERS

FEATURES

- Pre-assembled with two ½" MIPT UVR male adapters
- Accepts any ½" FIPT emitter
- Cost less preassembled than purchased separately in parts
- Ideal for slope applications
- Pre-assembly reduces installation cost by up to 50%
- On grade or below grade installation
- Custom lengths available
- Also available pre-assembled with PST emitters

OPERATING RANGE

Max Flow: 7 gpm
 Max Pressure: 60 psi



RISER ASSEMBLIES PRE-ASSEMBLED WITH SALCO PST EMITTERS

MODEL	ADAPTER COLOR
SLV-PVC-y-ACLxx	Black
SLV-PVC-y-M-ACLxx	Black
SLV-PVC-y-D-ACLxx	Black
SLV-PVC-y-G-ACLxx	Black
SLV-PVC-y-R-ACLxx	Black

y = Emitter flow rate ("050" = ½ gph, "1" = 1 gph, "2" = 2 gph, and "4" = 4 gph)
 xx = Length of riser ("12" or "18" or "24")

NO EMITTER RISER ASSEMBLIES PRE-ASSEMBLED RISERS WITH 2 MALE ADAPTERS

MODEL	ADAPTER COLOR
SLV-PVC-ACLxx	Black
SLV-PVC-M-ACLxx	Black
SLV-PVC-D-ACLxx	Black
SLV-PVC-G-ACLxx	Black
SLV-PVC-R-ACLxx	Black

xx = Length of riser ("12" or "18" or "24")

