

Bronze Check Valves



500 SB SERIES CERTIFIED LEAD FREE Check Valve

- Silicon bronze cast body.
- Silicon bronze stemmed poppet.
- Female threads.

MADE IN U.S.A.



1/2" - 2" are VFD Compatible
2-1/2" - 6" See page 9 for VFD Compatible

Part No.	Size	Weight Each lbs.
501SB	1/2	.6
502SB	3/4	.8
503SB	1	1.1
513SB*	1	1.2
504SB	1 1/4	1.6
514SB**	1 1/4	1.7
505SB	1 1/2	2.1
506SB	2	3.7
507SB	2 1/2	9.8
508SB	3	10.8
509SB	4	23.6
510SB***	5	25.1
511SB	6	41.5

513SB* has longer threads.
514SB** has longer threads.
510SB*** has 5" male threads both ends.



2500 SB SERIES CERTIFIED LEAD FREE Stemless Check Valve

- Silicon bronze cast body.
- Silicon bronze stemless poppet.
- Female threads.

MADE IN U.S.A.



Not VFD Compatible

Part No.	Size	Weight Each lbs.
2503SB	1	1.3
2504SB	1 1/4	1.8
2505SB	1 1/2	2.1
2506SB	2	3.7



CERTIFIED LEAD FREE Submersible Check Valve

- Silicon bronze cast body.
- Silicon bronze cast stemmed poppet.
- Female-Male threads.

MADE IN U.S.A.



1" - 2" are VFD Compatible
3" - 6" See page 9 for VFD Compatible

Part No.	Size	Weight Each lbs.
610SB**	1 x 1 Long	1.4
611SB**	1 1/4 x 1 1/4 Long	2.0
616SB	1 x 1	1.4
617SB	1 x 1 1/4	1.4
618SB	1 1/4 x 1 1/4	1.8
622SB	2 x 2	3.9
623SB	3 x 3	10.4
624SB	4 x 4	22.6
625SB	6 x 6	41.4

** Extended male and female threads



CERTIFIED LEAD FREE Dual Purpose Check Valve

- Silicon bronze cast body.
- Silicon bronze cast stemmed poppet.
- Female-Male threads both ends.

MADE IN U.S.A.



VFD Compatible

Part No.	Size FxM	Size FxM	Weight Each lbs.
641SB	1 x 1 1/4	1 x 1 1/4	1.2

Check Valves furnished with Buna-N O-Ring, stainless steel spring, stainless steel washer, and stainless steel locknut.
All valves 1/2" through 1-1/2" have a working pressure of 400 psi. All valves 2" and larger have a working pressure of 600 psi.
190° F. Maximum Temperature Rating