

SynLok Adhesives

PO Box 137

Stony Point, NC 28678 (P) 1.888.796.5655

(F) 1.828.635.1518

Safety Data Sheet

Product and Company Information

Product Name	SeamLok 1200 Red Stripe Seam Tape
Manufacturer	SynLok Adhesive Contract Item
Telephone:	1.888.796.5655
Fax:	1.828.635.1518

Composition on Ingredients

Chemical Ingredient

Polyethylene Terephthalate (PET)	CAS NO.: 25038-59-9
Perflouroalkylethylacrylate	

VOC

Formaldehyde	None detectable	CAS NO.: 50-00-0
Acetaldehyde	< 0.25 ppm	CAS NO.: 75-07-0
Toluene	< 0.05 ppm	CAS NO.: 108-88-3
Ethyl benzene	None detectable	CAS NO.: 100-41-4
Xylene	None detectable	CAS NO.: 1330-20-7
Styrene	None detectable	CAS NO.: 100-42-5
Tetradecane	None detectable	CAS NO.: 629-59-4
DBP	None detectable	CAS NO.: 84-74-2
DEHP	None detectable	CAS NO.: 117-81-7

SOC

Pb, Cd, Hg, Cr	< 30 ppm
----------------	----------

Possible Hazards

Not a hazardous product under normal conditions.

First Aid Measures

Eye:	Flush with water for 15 minutes or more and consult the Doctor.
Skin:	Flush with water. For hot product, immediately flush or immerse the affected area in cold water, then cover with clean cotton sheeting and seek medical attention.
Inhalation:	In case of harmful exposure to vapors and/or aerosols, administer artificial respiration if breathing is stopped. Call for prompt medical attention.
Ingestion:	Normally not required.

SynLok Adhesives
PO Box 137
Stony Point, NC 28678 (P) 1.888.796.5655 (F) 1.828.635.1518

Fire and Explosion Hazard

Flash Point:	N/A
Flammability:	N/A
Fire Extinguishing Media:	Water, powder, foam, carbon dioxide.
Special Fire Precautions:	Eye Protection and respiratory required for Fire fighting personnels.
Hazardous Combustion Products:	Under oxygen lean conditions, carbon monoxide and irritating smoke may be produced.

Accidental Release

Handling in accordance with local plastic waste regulation.

Handling and Storage

Handling:	Avoid ignition source.
Storage:	Use caution when stacking to avoid instable conditions. Avoid storing near strong oxidizer.

Exposure Controls and Personal Protection

Eye Protection:	Not required.
Hand Protection:	Not required.
Respiratory Protection:	Not required.
Ventilation Protection:	Not required.

Physical and Chemical Properties

Physical State:	Fiber
Odor:	None
Appearance:	Rolled Sheet
Color:	White and Red

Stability and Reactivity

Flash Point	346-399degrees C
Explosion limit (%) Upper	None
Lower	None
Flammability	Probable
Oxidizibility	Improbable
Autignition temperature	483-488degrees C
Combustibility	The ignition temperature is 483degrees C
Spontaneous-Reactivity with Water	None

SynLok Adhesives

PO Box 137

Stony Point, NC 28678 (P) 1.888.796.5655 (F) 1.828.635.1518

Toxicological Information

Corrosion Hazards	None
Irritation to Skin and Eyes:	No data available
Sensitization:	No data available
Acute Toxicity (LD50):	No data available
Short-term (Subacute) Toxicity:	No data available
Long-Term (Chronic) Toxicity:	No data available
Carcinogenicity:	No data available
Mutagenicity:	No data available
Reproductive Toxicity:	No hazardous decomposition products known in room temperature

Ecological Information

Degradability:	No data available
Bioaccumulative Potential:	No data available
Aquatic Toxicity:	No data available

Disposal Considerations

Follow the local regulation for plastic waste

Transportation

According to national and international guidelines, which regulate the road-, rail-, air-, and sea transport, this product is classified as not dangerous.

Other Information

This information stated above is based on present state of our best knowledge, therefore, does not guarantee any properties. Precipitants of our products must take responsibility for observing local law and regulations.