





PRODUCT SPECIFICATIONS

Pipe Type	Polyethylene, HDPE and Styrene Drain Pipe
Cement Uses:	Drain Pipe Adhesive and Root Inhibitor for Polyethylene, Polypropylene, HDPE and Styrene
Maximum Diameter	For Polyethylene, HDPE and Styrene drain pipe systems though 6" (150 mm)
Color	Electric Green
Relative Set Time	Strong Flexible Set
Body	Medium Body
Brookfield Viscosity	Minimum 900 cP @73°F +/- 2°F @23°C +/- 1°C
Specific Gravity	Typical 0.852 +/- 0.04
Max VOC Emissions	250 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

ROOT-BAN™ DRAIN PIPE ADHESIVE

Drain Pipe Adhesive and Root Inhibitor for Polyethylene, HDPE and Styrene

Root intrusion is the leading cause of failure in landscape drainage systems. Roots enter drain lines through poorly-protected push-fit connections and quickly impede water flow, causing premature system failure. Damage and reduced system performance is permanent until the roots are mechanically removed or the system is excavated and replaced. In many instances, the failure can be catastrophic. Christy's Root-Ban Drain Pipe Adhesive bonds and seals the connection to provide a flexible seal that inhibits root growth.

- **The first and only Drain Pipe Adhesive and Root Inhibitor for Polyethylene, HDPE and Styrene drain pipe up through 6" (150 mm)**
- **Easily applies with in-cap dauber to create a permanent leak-proof joint seal**
- **Creates a strong, flexible joint that minimizes risk of separation while keeping pipe clear of roots**
- **Eliminates chemical or mechanical cleaning or repair of drainage system joints**
- **A simple, cost effective solution that saves time and money for the life of the drainage system**
- **Low VOC**

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-ROOT-PT-12	Pint, 16 oz (473 ml)	12	044752346399
RH-ROOT-QT-12	Quart, 32 oz (946 ml)	12	044752346405
RH-ROOT-GL-6	Gallon, 128 oz (3.785 l)	6	044752346412

SPECIAL CONSIDERATIONS: Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. **DO NOT USE** a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE

THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASSES.