



MINI-CRETA 3" ARCHITECTURAL

DESCRIPTION: Wall double-sided **TEXTURE:** Split face with straight edged corners

PALLET OVERVIEW



COMPATIBLE CAPS

See page 140 for product compatibility.

NOTES

When building a double-sided wall one pallet will cover an average of 21.76 ft².

A unit can be used as a regular or vertical unit.

See page 135 to 156 for more technical information.

Specifications per pallet	Imperial	Metric
Cubing	24 ft²	2.23 m ²
	95.01 lin. ft	28.96 lin. m
Approx. Weight	2 465 lbs	1 118 kg
Minimum radius	7 ft	2.1 m
Number of rows	8	
Coverage per row	3 ft ²	0.28 m ²
Linear coverage per row	11.88 lin. ft	3.62 lin. m

	Unit dimensions	in	mm	Units/pallet
A	Height	2 15/16	75	32 units
	Depth	9 13/16	250	
	Length 1	9 1/16	230	
	Length 2	7 1/16	180	
B	Height	2 15/16	75	24 units
	Depth	9 13/16	250	
	Length 1	11 13/16	300	
	Length 2	9 13/16	250	
B'	Height	2 15/16	75	8 units
	Depth	9 13/16	250	
	Length 1	11 13/16	300	
	Length 2	11 13/16	300	
C	Height	2 15/16	75	16 units
	Depth	9 13/16	250	
	Length 1	14 3/8	375	
	Length 2	12 13/16	325	
D	Height	2 15/16	75	16 units 8 right corners 8 left corners
	Depth	9 13/16	250	
	Length 1	14 3/8	375	
	Length 2	13 3/8	350	

Chocolate Brown

Oxheart Brown

Saddlewood

Quaintain Grey

Shale Grey

Onyx Black

