





BLU 60 mm

DESCRIPTION: Slab **TEXTURE:** Slate and HD² Slate

PALLET OVERVIEW



NOTES





See page 31 to 33 for more technical information. When used in a permeable pavement application, see page 99 to 104 for more technical information.

See page 28 for more information about applications.


* Sandlewood HD² Slate is only available in Eastern States. See page 17 for list of Eastern and Midwestern States.

JOINT WIDTH: 9/32" (7 mm)
% OF SURFACE OPENING: 3.0 %
INFILTRATION RATE: 570 in./hr
 (14 475 mm/hr)


Specifications per pallet	Imperial	Metric
Cubing	116.82 ft²	10.96 m ²
Approx. Weight slate	3 148 lbs	1 428 kg
Approx. Weight slate aged	3 170 lbs	1 438 kg
Approx. Weight HD ² Slate	3 268 lbs	1 482 kg
Number of rows	11	
Coverage per row	10.62 ft ²	0.99 m ²
Linear coverage per row	9.81 lin. ft	3.02 lin. m

	Unit dimensions	in	mm	Units/pallet
	Height	2 3/8	60	44 units
	Width	13	330	
	Length	6 1/2	165	
	Height	2 3/8	60	44 units
	Width	13	330	
	Length	13	330	
	Height	2 3/8	60	22 units
	Width	13	330	
	Length	19 1/2	495	


01 | Modular pattern



02 | Modular pattern



03 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

