

## UltraMax™ Green Hose Data Sheet

**Application:**

An economic, lightweight, general-purpose water hose for a wide range of uses listed as:

- Municipal,
- Construction,
- Institutional,
- Landscape,
- Golf or
- Agricultural applications.



**Value:** Lightweight, yet durable and thick outer wall. Non-conductive hose, minimum electrical resistance, greater than one (1) megohm per inch of hose length at 1000 DC volts. Non-slip smooth finish good for golf greens and clear material provides visual confirmation when used with applicators.

**Working Pressure:** 200 Psi @ 70 F (13.79 bars @ 21.1 C)

**Burst Pressure:** 800 Psi @ 70 F (55.16 bars @ 21.1 C)



**Tube:** Green flexible PVC, RMA Class B (medium oil resistance)

**Cover:** Flexible PVC, smooth finish, RMA Class B (medium oil resistance)

**Reinforcement:** Polyester fiber

**Temperature Range:** 0°F to 158°F (-17.78°C to 70°C)

**Hose Diameters:** (Imperial and metric values)

	¾"	1"
<b>ID:</b>	0.74 to 0.77" (18.8 to 19.5 mm)	0.98 to 1.02" (25.0 to 25.8 mm)
<b>OD:</b>	1.07 – 1.12" (27.3 to 28.5 mm)	1.34 to 1.40" (34.0 to 35.6 mm)

**Weight/ft.** (imperial and metric values)

¾"	1"
0.300 lbs. max (0.14 kg)	0.390 lbs. max (0.18 kg)