



PRODUCT DATA 2023

UNILOCK®

Calculate

paver and
wall projects
FASTER!



Email
directly
to your
Unilock
Dealer

Try **SPEED-CALC**™
by **UNILOCK**®



TABLE OF CONTENTS - OHIO

PAVERS

Arcana™	4
Artline™	5
Beacon Hill™ Flagstone	6
Beacon Hill™ Smooth	7
Boulevard™	8
Bristol Valley®	9
Brussels Block®	10
Camelot™	11
Copthorne®	12
Courtstone®	13
Eco-Line®	14
Eco-Optiloc™	15
Eco-Priora™	16
Eco-Promenade®	17
Hex Paver™	18
Hollandstone™	19
Holland Premier™	20
Il Campo®	21
Mattoni™	22
Natural Stone - Sandstone	23
Natural Stone - Limestone	25
Optiloc®	27
Porcelain	28
Promenade™ Plank Paver	31
Promenade™ Premier	32
Richcliff®	34
Series™	35
Skyline™	36
Soreno™	37
Thornbury™	38
Town Hall®	39
Treo® Premier	40
Treo® Smooth NEW	41
Tribeca Cobble™	42
Turfstone™	43
Umbriano®	44
Westport™	47


RETAINING WALLS

Brussels Dimensional System™	48
Dimensional Smooth™ NEW	49
DuraHold®	50
DuraHold2®	52
Estate Wall™	53
Lineo™ Dimensional Stone	54
Pisa2™ & Pisa XL	55
Pisa Smooth™ NEW	56
RomanPisa™	57
RomanStack™	58
SienaEdge™	59
SienaStone™	60
Split'nStack™	61
U-Cara®	62
U-Cara® Modular System	66
U-Cara® Wall Mount System	67


COPING, STEPS, PILLAR CAPS

Architectural Coping	68
Brussels Fullnose™/DBL Fullnose	69
Ledgestone™ Coping, Cap & Step	70
SienaStone Coping	72
Umbriano Coping NEW	73
Universal Coping	74

DESCRIPTION OF EDGE DETAILS



APPLICATION INDEX



FIRE FEATURES

Sunset Fire Pit	75
Unilock Elements	76

ACCESSORIES

Paver Cleaners	77
Natural Stone Cleaners	77
Paver Sealers	77
Natural Stone Sealers	77
Adhesive	78
Sands	78
Sand Charts	80
Edging, Edge Restraints	80
Drainage / Base Systems	81
Tools & Accessories	83

PRODUCT & INSTALLATION INFORMATION

Calculations	84
Bedding & Base Thickness Charts	85
Important Notes	86
Finishes & Color Blends	89
Product Directory	90



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 0 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYSOIL™

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 1782
Eligible for LEED v4.1 credits

		12 X 24	18 X 24	24 X 24
	Bundle Type	SINGLE	SINGLE	SINGLE
	Plant Produced	CHICAGO	CHICAGO	CHICAGO
	Thickness (mm)	50 MM	50 MM	50 MM

SQFT PER	Bundle	36.00	54.00	72.00
	Layer	4.00	6.00	8.00
	Section	-	-	-
	Stone	2.00	3.00	4.00

PER BUNDLE	Layers	9.00	9.00	9.00
	Sections	-	-	-

SOILDR LNFT PER	SqFt	0.49	0.50	0.50
	Section	-	-	-
	Layer	1.98	2.97	3.98
	Bundle	17.78	26.75	35.79


SAILOR LNFT PER	SqFt	0.99	0.66	0.50
	Section	-	-	-
	Layer	3.98	3.98	3.98
	Bundle	35.79	35.79	35.79

UNITS PER	SqFt	0.50	0.33	0.25
	Section	-	-	-
	Bundle	18.00	18.00	18.00


LBS PER	Layer	96	144	192
	Section	-	-	-
	Bundle	864	1,296	1,728

COLORS	Reflectance	Stock	Stock	Stock
Avorio	SR .56 SRI 66	✓	✓	✓
Corvara	SR n/a SRI n/a	✓	✓	✓
Modena	SR n/a SRI n/a	✓	✓	✓
Vivanto	SR n/a SRI n/a	✓	✓	✓


LAYING PATTERNS




Arcana Multi-Unit
Random A



Arcana Multi-Unit
Random C



Arcana Multi-Unit
Random F



X & T SLAB SPACERS BAGGED
SEPARATELY (SEE PAGE 80)

Single Units		12 X 24 301 X 606 X 50MM 11 7/8 X 23 7/8 X 2" 18 Units/Bundle 2 Sq.Ft./Stone		18 X 24 453 X 606 X 50MM 17 7/8 X 23 7/8 X 2" 18 Units/Bundle 3 Sq.Ft./Stone		24 X 24 606 X 606 X 50MM 23 7/8 X 23 7/8 X 2" 18 Units/Bundle 4 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro

Surface Texture - Smooth / Brushed (Il Campo®)

Joint Spacing - 3 mm

Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™ (Smooth only)

Factory sealed to provide integral stain resistance

COMFORT STEP (Smooth only)


Ultra smooth surface texture

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



Artline Fixed
Random A

		SMOOTH FINISH
Bundle Type		RANDOM
Plant Produced		OHIO
Thickness (mm)		70 MM

SQFT PER	Bundle	93.25
	Layer	11.66
	Section	-
	Stone	0.49

PER BUNDLE	Layers	8.00
	Sections	-



SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-





SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.06
	Section	-
	Bundle	192.00

LBS PER	Layer	364
	Section	-
	Bundle	2,911

COLORS	Reflectance	Stock
Birch	SR n/a SRI n/a	✓
Fossil	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓
Granite Fusion (Il Campo)	SR .28 SRI 29	✓

7 Unit Random Bundle		
	UNIT A 125 X 169 X 70MM 4 7/8 X 6 3/4 X 2 3/4" 32 UNITS/BUNDLE .23 SQ.FT./STONE	UNIT B 125 X 262.5 X 70MM 4 7/8 X 10 3/8 X 2 3/4" 32 UNITS/BUNDLE .35 SQ.FT./STONE

7 Unit Random Bundle					
	UNIT C 125 X 337.5 X 70MM 4 7/8 X 13 3/8 X 2 3/4" 32 UNITS/BUNDLE .45 SQ.FT./STONE	UNIT D 125 X 450 X 70MM 4 7/8 X 17 3/4 X 2 3/4" 32 UNITS/BUNDLE .61 SQ.FT./STONE	UNIT E 187.5 X 225 X 70MM 7 1/2 X 8 7/8 X 2 3/4" 32 UNITS/BUNDLE .45 SQ.FT./STONE	UNIT F 187.5 X 337.5 X 70MM 7 1/2 X 13 3/8 X 2 3/4" 16 UNITS/BUNDLE .58 SQ.FT./STONE	UNIT G 187.5 X 450 X 70MM 7 1/2 X 17 3/4 X 2 3/4" 16 UNITS/BUNDLE .91 SQ.FT./STONE

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

Beacon Hill™ Flagstone 60mm

ENDURACOLOR™



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Textured
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

Bundle Type		RANDOM
Plant Produced		OHIO
Thickness (mm)		60 MM

SQFT PER	Bundle	116.57
	Layer	11.66
	Section	-
	Stone	1.46

PER BUNDLE	Layers	10.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	93.50

UNITS PER	SqFt	0.69
	Section	-
	Bundle	80.00


LBS PER	Layer	320
	Section	-
	Bundle	3,199

COLORS	Reflectance	Stock
Birch	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓
River	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓
Walnut	SR n/a SRI n/a	✓


LAYING PATTERNS



BeaconHill Fixed
Random A



BeaconHill Fixed
Random B



BeaconHill Multi-
Unit Random C

Random Bundle		LARGE RECTANGLE 15 X 22 1/2 X 2 3/8" 380 X 570 X 60MM 20 Units/Bundle XX SqFt./Stone
		SQUARE 380 X 380 X 60MM 15 X 15 X 2 3/8" 30 Units/Bundle XX Sq.Ft./Stone
		SMALL RECTANGLE 380 X 190 X 60MM 15 X 7 1/2 X 2 3/8" 30 Units/Bundle XX Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


		NEW		XL	RECTANGLE
	Bundle Type	RANDOM	RANDOM	SINGLE	SINGLE
	Plant Produced	OHIO	OHIO	OHIO	OHIO
	Thickness (mm)	80 MM	60 MM	60 MM	60 MM
SQFT PER	Bundle	83.68	116.57	116.57	116.57
	Layer	10.46	11.66	11.66	11.66
	Section	-	-	-	-
	Stone	1.31	1.46	5.83	0.78
PER BUNDLE	Layers	8.00	10.00	10.00	10.00
	Sections	-	-	-	-
SOILDER LNFT PER	SqFt	-	-	0.32	0.80
	Section	-	-	-	-
	Layer	-	-	3.74	9.35
	Bundle	-	-	37.40	93.50
SAILOR LNFT PER	SqFt	0.85	0.80	0.53	1.60
	Section	-	-	-	-
	Layer	8.86	9.35	6.23	18.70
	Bundle	65.45	93.50	62.30	187.01
UNITS PER	SqFt	0.76	0.69	0.17	1.29
	Section	-	-	-	-
	Bundle	64.00	80.00	20.00	150.00
LBS PER	Layer	362	320	320	320
	Section	-	-	-	-
	Bundle	2,896	3,199	3,199	3,199

COLORS	Reflectance	Stock	Stock	Stock	Stock
Dark Charcoal NEW	SR n/a SRI n/a	-	-	-	✓
Fossil	SR n/a SRI n/a	✓	✓	✓	✓
Granite Fusion	SR n/a SRI n/a	✓	✓	✓	✓
Opal	SR n/a SRI n/a	-	✓	✓	-
Tuscany NEW	SR n/a SRI n/a	-	✓	-	-

LAYING PATTERNS



BeaconHill Fixed
Random A



BeaconHill Multi-
Unit Random C

3 Unit Random Bundle



LARGE RECTANGLE
380 X 570 X 80MM
15 X 22 1/2 X 3 1/8"
16 Units/Bundle



SQUARE
380 X 380 X 80MM
15 X 15 X 3 1/8"
24 Units/Bundle



SMALL RECTANGLE
380 X 190 X 80MM
15 X 7 1/2 X 3 1/8"
24 Units/Bundle

3 Unit Random Bundle



LARGE RECTANGLE
380 X 570 X 60MM
15 X 22 1/2 X 2 3/8"
18 Units/Bundle



SQUARE
380 X 380 X 60MM
15 X 15 X 2 3/8"
27 Units/Bundle



SMALL RECTANGLE
380 X 190 X 60MM
15 X 7 1/2 X 2 3/8"
27 Units/Bundle

Single Units




SMALL RECTANGLE
380 X 190 X 60MM
15 X 7 1/2 X 2 3/8"
135 Units/Bundle
.78 Sq.Ft./Stone



XL UNIT
950 X 570 X 60MM
37 1/2 X 22 1/2 X 2 3/8"
18 Units/Bundle
5.83 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES


ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION




Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERN



Boulevard Fixed
Random B

Bundle Type		RANDOM
Plant Produced		OHIO
Thickness (mm)		70 MM
SQFT PER	Bundle	93.00
	Layer	11.63
	Section	-
	Stone	1.45
PER BUNDLE	Layers	8.00
	Sections	-
SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	1.03
	Section	-
	Layer	12.00
	Bundle	96.04
UNITS PER	SqFt	0.69
	Section	-
	Bundle	64.00
LBS PER	Layer	372
	Section	-
	Bundle	2,978
COLORS		Reflectance
Granite Fusion	SR n/a SRI n/a	✓
River	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

Random Bundle		LARGE RECTANGLE 610 X 305 X 70MM 24 X 12 X 2 3/4" 24 Units/Bundle 2.00 SqFt./Stone		MEDIUM RECTANGLE 457 X 305 X 70MM 18 X 12 X 2 3/4" 16 Units/Bundle 1.50 Sq.Ft./Stone		SQUARE 305 X 305 X 70MM 12 X 12 X 2 3/4" 24 Units/Bundle 1.00 Sq.Ft./Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Textured
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory sealed to provide integral stain resistance


COMFORT STEP

Ultra smooth surface texture


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Bristol Valley Fixed
Random A



Bristol Valley Fixed
Random B

Bundle Type	RANDOM	XL
Plant Produced	MARENGO	MARENGO
Thickness (mm)	60 MM	60 MM

SQFT PER	Bundle	116.57	116.57
	Layer	11.66	11.66
	Section	-	-
	Stone	1.46	5.83

PER BUNDLE	Layers	10.00	10.00
	Sections	-	-





SOILDER LNFT PER	SqFt	-	0.32
	Section	-	-
	Layer	-	3.74
	Bundle	-	37.40

SAILOR LNFT PER	SqFt	0.80	0.53
	Section	-	-
	Layer	9.35	6.23
	Bundle	93.50	62.30

UNITS PER	SqFt	0.69	0.17
	Section	-	-
	Bundle	80.00	20.00

LBS PER	Layer	311	295
	Section	-	-
	Bundle	3,113	2,946

COLORS	Reflectance	Stock	Stock
Bavarian	SR n/a SRI n/a	✓	✓
Fossil	SR n/a SRI n/a	✓	✓
Steel Mountain	SR n/a SRI n/a	✓	✓

Random Bundle		LARGE RECTANGLE 380 X 570 X 60MM 15 X 22 1/2 X 2 3/8" 20 Units/Bundle 2.08 Sq.Ft./Stone		SQUARE 380 X 380 X 60MM 15 X 15 X 2 3/8" 30 Units/Bundle 1.39 Sq.Ft./Stone		SMALL RECTANGLE 380 X 190 X 60MM 15 X 7 1/2 X 2 3/8" 30 Units/Bundle .69 Sq.Ft./Stone	Single Units		XL UNIT 900 X 540 X 60MM 35 1/2 X 21 1/4 X 2 3/8" 20 Units/Bundle 5.23 Sq.Ft./Stone
---------------	---	--	---	---	---	--	--------------	---	--

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 2 mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix


ANTIQUED™

Distressed, timeworn finish


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



Brussels Multi-Unit
Random AC



Brussels Multi-Unit
Random AD



Brussels Multi-Unit
Random AE

	HALF	STANDARD	XL
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	OHIO	OHIO
Thickness (mm)	70 MM	70 MM	70 MM

SQFT PER	Bundle	88.70	88.60	76.56
	Layer	11.09	11.08	9.57
	Section	12.67	12.66	25.52
	Stone	0.20	0.40	0.80

PER BUNDLE	Layers	8.00	8.00	8.00
	Sections	7.00	7.00	3.00

SOILDER LNFT PER	SqFt	1.72	1.44	0.86
	Section	21.84	18.27	21.84
	Layer	19.11	15.98	8.19
	Bundle	152.86	127.87	65.51

SAILOR LNFT PER	SqFt	2.87	1.73	1.43
	Section	36.33	21.84	36.54
	Layer	31.78	19.11	13.70
	Bundle	254.28	152.86	109.61

UNITS PER	SqFt	5.05	2.53	1.25
	Section	64.00	32.00	32.00
	Bundle	448.00	224.00	96.00

LBS PER	Layer	344	344	316
	Section	393	393	843
	Bundle	2,752	2,749	2,528

COLORS	Reflectance	Stock	Stock	Stock
Limestone	SR .28 SRI 29	✓	✓	✓
Sandstone	SR .41 SRI 46	✓	✓	✓
Sierra	SR n/a SRI n/a	✓	✓	✓

Single Units



HALF
104 X 173 X 70MM
4 X 6 7/8 X 2 3/4"
448 Units/Bundle
.20 Sq.Ft./Stone



STANDARD
173 X 208 X 70MM
6 7/8 X 8 1/4 X 2 3/4"
224 Units/Bundle
.40 Sq.Ft./Stone



XL
208 X 348 X 70MM
8 1/4 X 13 3/4 X 2 3/4"
96 Units/Bundle
.80 Sq.Ft./Stone

Notes: **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

	SQUARE SMOOTH	RECTANGLE SMOOTH
Bundle Type	SINGLE	SINGLE
Plant Produced	OHIO	OHIO
Thickness (mm)	60 MM	60 MM

SQFT PER	Bundle	92.40	98.96
	Layer	11.55	12.37
	Section	13.20	19.79
	Stone	0.28	0.41

PER BUNDLE	Layers	8.00	8.00
	Sections	7.00	5.00

SOILDER LNFT PER	SqFt	1.79	1.19
	Section	23.62	23.62
	Layer	20.67	14.76
	Bundle	165.35	118.11


SAILOR LNFT PER	SqFt	1.79	1.79
	Section	23.62	35.43
	Layer	20.67	22.15
	Bundle	165.35	177.17

UNITS PER	SqFt	3.64	2.43
	Section	48.00	48.00
	Bundle	336.00	240.00


LBS PER	Layer	325	350
	Section	371	560
	Bundle	2,598	2,800

COLORS	Reflectance	Stock	Stock
Granite	SR .26 SRI 27	✓	✓
River	SR .32 SRI 34	✓	✓
Sierra	SR n/a SRI n/a	✓	✓


LAYING PATTERNS



Camelot 6x9_HB_A



Camelot 6x9_HB_B



Camelot Multi-Unit_Random_F

Single Units



SQUARE
159.8 X 159.8 X 60MM
6 3/8 X 6 3/8 X 2 3/8"
336 Units/Bundle
.28 Sq.Ft./Stone



RECTANGLE
160 X 240 X 60MM
6 3/8 X 9 1/2 X 2 3/8"
240 Units/Bundle
.41 Sq.Ft./Stone

Notes: Camelot is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured
Joint Spacing - 3 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

REALA™

Cast from European cobblestones

ULTIMA™

Up to 4x stronger than poured-in-place concrete


EASYSOIL™

Factory Sealed to provide integral stain resistance


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Copthorne BW A



Copthorne RB C

Bundle Type		SINGLE
Plant Produced		AYR
Thickness (mm)		60 MM

SQFT PER	Bundle	89.20
	Layer	11.15
	Section	-
	Stone	0.15

PER BUNDLE	Layers	8.00
	Sections	-

SOILDER LNFT PER	SqFt	1.43
	Section	-
	Layer	15.99
	Bundle	127.95

SAILOR LNFT PER	SqFt	4.41
	Section	-
	Layer	49.21
	Bundle	393.70

UNITS PER	SqFt	6.73
	Section	-
	Bundle	600.00

LBS PER	Layer	294
	Section	-
	Bundle	2,349

COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓

Single Unit



STANDARD
360 X 540 X 60MM
2 5/8 X 7 7/8 X 2 3/8"
600 Units/Bundle
.15 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 79. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Textured
Joint Spacing - 15 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

REALA™

Cast from European cobblestones

ULTIMA™

Up to 4x stronger than poured-in-place concrete

EASYCLEAN™

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Courtstone Random A

Bundle Type		RANDOM
Plant Produced		AYR
Thickness (mm)		60 MM
SQFT PER	Bundle	98.30
	Layer	12.29
	Section	-
	Stone	0.26
PER BUNDLE	Layers	8.00
	Sections	-
SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	2.25
	Section	-
	Layer	27.69
	Bundle	221.52
UNITS PER	SqFt	3.91
	Section	-
	Bundle	384.00
LBS PER	Layer	291
	Section	-
	Bundle	2,326
COLORS		
Reflectance	Stock	
Basalt	SR n/a SRI n/a	✓

Random Bundle	XL RECTANGLE	LARGE RECTANGLE	RECTANGLE	SMALL RECTANGLE	SQUARE
	215 X 130 X 60MM 8 3/8 X 5 1/8 X 2 3/8"	185 X 130 X 60MM 7 1/4 X 5 1/8 X 2 3/8"	165 X 130 X 60MM 6 1/2 X 5 1/8 X 2 3/8"	145 X 130 X 60MM 5 3/4 X 5 1/8 X 2 3/8"	130 X 130 X 60MM 5 1/8 X 5 1/8 X 2 3/8"
	128 Units/Bundle .30 SqFt/Stone	64 Units/Bundle .28 SqFt/Stone	64 Units/Bundle .23 SqFt/Stone	64 Units/Bundle .20 SqFt/Stone	64 Units/Bundle .18 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 79. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro

Surface Texture - Smooth Joint Spacing - 6.25 mm

Void - 5.80%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

EASYSOIL™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLOR FUSION™ (Umbriano)

Subtly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

	SMOOTH ENDURA
Bundle Type	SINGLE
Plant Produced	OHIO
Thickness (mm)	100 MM

SQFT PER	Bundle	66.20
	Layer	11.03
	Section	-
	Stone	0.34

PER BUNDLE	Layers	6.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.90
	Section	-
	Bundle	192.00









LBS PER	Layer	504
	Section	-
	Bundle	3,025

COLORS	Reflectance	Stock
All Colors & Finishes	SR n/a SRI n/a	SO


LAYING PATTERN



EcoLine Fixed
Random A

Random Bundle								
	UNIT A 357 X 84 X 100MM 14 X 3 3/8 X 3 3/8" 24 Units/Bundle .32 SqFt/Stone	UNIT B 317 X 84 X 100MM 12 1/2 X 3 3/8 X 3 3/8" 24 UNITS/BUNDLE .29 SQFT/STONE	UNIT C 277 X 84 X 100MM 10 7/8 X 3 3/8 X 3 3/8" 24 Units/Bundle .25 SqFt/Stone	UNIT D 237 X 84 X 100MM 9 3/8 X 3 3/8 X 3 3/8" 24 Units/Bundle .21 SqFt/Stone	UNIT E 357 X 114 X 100MM 14 X 4 1/2 X 3 3/8" 24 Units/Bundle .44 SqFt/Stone	UNIT F 317 X 114 X 100MM 12 1/2 X 4 1/2 X 3 3/8" 24 Units/Bundle .39 SqFt/Stone	UNIT G 277 X 114 X 100MM 10 7/8 X 4 1/2 X 3 3/8" 24 Units/Bundle .34 SqFt/Stone	UNIT H 237 X 114 X 100MM 9 3/8 X 4 1/2 X 3 3/8" 24 UNITS/BUNDLE .29 SQFT/STONE

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Smooth
Joint Spacing - 7 mm
Void - 7.30%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through


CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERN



Pattern Cluster C

		STANDARD SMOOTH
Bundle Type		SINGLE
Plant Produced		OHIO
Thickness (mm)		80 MM

SQFT PER	Bundle	84.80
	Layer	10.60
	Section	-
	Stone	0.50

PER BUNDLE	Layers	8.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.98
	Section	-
	Bundle	168.00

LBS PER	Layer	354
	Section	-
	Bundle	2,831

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	✓
River	SR .32 SRI 34	✓

Single Unit



STANDARD
250 X 250 X 80MM
9 7/8 X 9 7/8 X 3 1/8"
168 Units/Bundle
.50 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 7mm
Void - 4.6-7.08%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

Bundle Type		SINGLE
Plant Produced		OHIO
Thickness (mm)		80 MM

SQFT PER	Bundle	75.95
	Layer	10.85
	Section	15.19
	Stone	0.31

PER BUNDLE	Layers	7.00
	Sections	5.00

SOILDER LNFT PER	SqFt	1.27
	Section	19.29
	Layer	13.78
	Bundle	96.46


SAILOR LNFT PER	SqFt	2.25
	Section	34.17
	Layer	24.41
	Bundle	170.87

UNITS PER	SqFt	3.23
	Section	49.00
	Bundle	245.00


LBS PER	Layer	381
	Section	534
	Bundle	2,669

COLORS	Reflectance	Stock
Natural	SR n/a SRI n/a	SO
River	SR n/a SRI n/a	✓


LAYING PATTERNS



EcoPriora 5x10
RB_A



EcoPriora 5x10
HB_E



EcoPriora Multi-Unit
Random C

Single Unit



5 X 10
120 X 240 X 80MM
4 ¾ X 9 ½ X 3 ⅛"
245 Units/Bundle
.31SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded

Surface Texture - Smooth / Series™ Exposed

Joint Spacing - 7 mm

Void - 10.12%

TECHNOLOGIES

ENDURACOLOR™ (8x12 & 3x12)

Refined surface and long-lasting color

PERMEABLE (8x12 & 3x12)

Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

	6"X24" SMOOTH	3"X12" PERMEABLE SMOOTH	3"X12" PERMEABLE SERIES
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	CHICAGO	CHICAGO
Thickness (mm)	70 MM	100 MM	100 MM

SQFT PER	Bundle	93.00	63.94	63.94
	Layer	11.63	10.66	10.66
	Section	-	-	-
	Stone	0.97	0.24	0.24

PER BUNDLE	Layers	8.00	6.00	6.00
	Sections	-	-	-

SOILDER LNFT PER	SqFt	0.51	1.02	1.02
	Section	-	-	-
	Layer	5.91	10.83	10.83
	Bundle	47.25	64.96	64.96


SAILOR LNFT PER	SqFt	2.03	4.06	4.06
	Section	-	-	-
	Layer	23.62	43.31	43.31
	Bundle	188.98	259.84	259.84

UNITS PER	SqFt	1.03	4.13	4.13
	Section	-	-	-
	Bundle	96.00	264.00	264.00


LBS PER	Layer	372	465	483
	Section	-	-	-
	Bundle	2,978	2,789	2,898

COLORS	Reflectance	Stock	Stock	Stock
All Finishes/Colors	SR n/a SRI n/a	SO	SO	SO


LAYING PATTERNS



EcoPromenade 3x12
RB_A



EcoPromenade 3x12_
DHB_B



EcoPromenade 3x12
HB_C

Single Units



6X24 SMOOTH
150 X 600 X 70MM
5 7/8 X 6 3/8 X 2 3/4"
96 Units/Bundle
.97 Sq.Ft./Stone



3X12 SMOOTH
75 X 300 X 100MM
3 X 11 1/2 X 3 3/8"
264 Units/Bundle
.24 Sq.Ft./Stone



3X12 SERIES
75 X 300 X 100MM
3 X 11 1/2 X 3 3/8"
264 Units/Bundle
.24 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro / Zero (Umbriano)

Surface Texture - Smooth / Umbriano Mottled

Joint Spacing - 3 mm / 7mm (Umbriano)

Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLORFUSION™ (Umbriano)


Subtly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERN



Pattern A

	HEX SMOOTH ENDURACOLOR	HEX UMBRIANO® MOTTLED
Bundle Type	SINGLE	SINGLE
Plant Produced	OHIO	CHICAGO
Thickness (mm)	70 MM	60 MM

SQFT PER	Bundle	73.92	108.31
	Layer	9.24	10.83
	Section	-	-
	Stone	0.39	0.45

PER BUNDLE	Layers	8.00	10.00
	Sections	-	-

SOILDER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

SAILOR LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

UNITS PER	SqFt	2.60	2.22
	Section	-	-
	Bundle	192.00	240.00

LBS PER	Layer	306	273
	Section	-	-
	Bundle	2,450	2,732

COLORS	Reflectance	Stock	Stock
Dark Charcoal	SR n/a SRI n/a	✓	
French Grey	SR .18 SRI 17		✓
Granite Fusion	SR n/a SRI n/a	✓	
Summer Wheat	SR .42 SRI 48		✓
Winter Marvel	SR .35 SRI 38		✓

Single Unit



HEX SMOOTH ENDURACOLOR
200 X 200 X 70MM
7 7/8 X 7 7/8 X 2 3/4"
192 Units/Bundle
.39 SqFt/Stone



HEX SMOOTH UMBRIANO
200 X 200 X 70MM
7 7/8 X 7 7/8 X 2 3/4"
240 Units/Bundle
.45 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 3 mm
 Void - n/a

TECHNOLOGIES


CLASSIC

Budget-friendly traditional product mix


TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits


LAYING PATTERNS



Pattern RB_B



Pattern HB_C



Pattern BW_D

		SMOOTH - CLASSIC
Bundle Type		SINGLE
Plant Produced		OHIO
Thickness (mm)		60 MM

SQFT PER	Bundle	106.20
	Layer	11.80
	Section	17.70
	Stone	0.22

PER BUNDLE	Layers	9.00
	Sections	6.00

SOILDER LNFT PER	SqFt	1.50
	Section	26.57
	Layer	17.72
	Bundle	159.45

SAILOR LNFT PER	SqFt	3.00
	Section	53.15
	Layer	35.43
	Bundle	318.90

UNITS PER	SqFt	4.58
	Section	81.00
	Bundle	486.00

LBS PER	Layer	319
	Section	478
	Bundle	2,868

COLORS	Reflectance	Stock
Charcoal	SR .12 SRI 9	✓
River	SR .32 SRI 34	✓
Rustic Red	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

Single Unit



STANDARD

100 X 200 X 60MM
 3 7/8 X 7 7/8 X 2 3/8"
 540 Units/Bundle
 .22 Sq.Ft./Stone

Notes: Hollandstone is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



Pattern RB_B



Pattern HB_C



Pattern BW_D

		SMOOTH ENDURACOLOR
Bundle Type		SINGLE
Plant Produced		OHIO
Thickness (mm)		60 MM

SQFT PER	Bundle	106.20
	Layer	11.80
	Section	17.70
	Stone	0.22

PER BUNDLE	Layers	9.00
	Sections	6.00

SOILDER LNFT PER	SqFt	1.50
	Section	26.57
	Layer	17.72
	Bundle	159.45

SAILOR LNFT PER	SqFt	3.00
	Section	53.15
	Layer	35.43
	Bundle	318.90

UNITS PER	SqFt	4.58
	Section	81.00
	Bundle	486.00

LBS PER	Layer	307
	Section	460
	Bundle	2,759

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓
Fossil	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓
Ivory NEW	SR n/a SRI n/a	✓
Mocha Brown	SR n/a SRI n/a	✓

Single Unit



STANDARD
100 X 200 X 60MM
3 1/8 X 7 7/8 X 2 3/8"
486 Units/Bundle
.22 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Il Campo® Brushed
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™
Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

		BRUSHED ENDURACOLOR
Bundle Type		SINGLE
Plant Produced		OHIO
Thickness (mm)		70 MM

SQFT PER	Bundle	94.40
	Layer	11.80
	Section	15.73
	Stone	0.22

PER BUNDLE	Layers	8.00
	Sections	6.00

SOILDER LNFT PER	SqFt	1.50
	Section	23.62
	Layer	17.72
	Bundle	141.73


SAILOR LNFT PER	SqFt	3.00
	Section	47.24
	Layer	35.43
	Bundle	283.46

UNITS PER	SqFt	4.58
	Section	72.00
	Bundle	432.00


LBS PER	Layer	362
	Section	483
	Bundle	2,898

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓
Mocha Brown	SR n/a SRI n/a	✓


LAYING PATTERNS



Pattern 4x8_RB_F



Pattern 4x8_SB_G



Pattern 4x8_HB_H

Single Unit



STANDARD
100 X 200 X 70MM
3 3/8 X 7 7/8 X 2 3/4"
432 Units/Bundle
.22 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid.. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Smooth

Joint Spacing - 4 mm

Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

ANTIQUED™


Distressed, timeworn finish

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits


LAYING PATTERNS



Pattern RB_A



Pattern HB_C



Pattern DHB_D

		STANDARD
Bundle Type		SINGLE
Plant Produced		MARENGO
Thickness (mm)		70 MM

SQFT PER	Bundle	89.28
	Layer	11.16
	Section	-
	Stone	0.16

PER BUNDLE	Layers	8.00
	Sections	-

SOILDER LNFT PER	SqFt	1.27
	Section	-
	Layer	14.17
	Bundle	113.39

SAILOR LNFT PER	SqFt	5.08
	Section	-
	Layer	56.69
	Bundle	453.54

UNITS PER	SqFt	6.45
	Section	-
	Bundle	576.00

LBS PER	Layer	357
	Section	-
	Bundle	2,859

COLORS	Reflectance	Stock
Cocoa Brown	SR n/a SRI n/a	✓
Dark Charcoal	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓
Sable	SR n/a SRI n/a	✓

Single Unit



STANDARD

60 X 240 X 70MM

2 3/8 X 9 1/2 X 2 3/4"

576 Units/Bundle

.16 SqFt/Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Brushed / Riven

Joint Spacing - 0 mm

Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

BRUSHED FINISH	4 PC BUNDLE	24" X 24"	24" X 36"
Bundle Type	RANDOM	SINGLE	SINGLE
Thickness (mm)	22 MM	22 MM	22 MM

SQFT PER	Crate	174.00	160.00	180.00
	Units	3.63	4.00	6.00

UNITS PER	Crate	48.00	40.00	30.00
	SqFt	0.28	0.25	0.17


LBS PER	Unit	47	46	69
	Bundle	2,265	1,851	2,082

COLORS	Reflectance	Stock	Stock	Stock
Autumn Harvest (Riven)	SR n/a SRI n/a	✓	✓	✓
Golden Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓
Indian Coast (Brushed)	SR n/a SRI n/a	✓	✓	✓
Ivory Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓
Stone Cliff Grey (Riven)	SR n/a SRI n/a	✓	✓	✓

LAYING PATTERNS



NaturalStone
Multi-Unit D



NaturalStone
Multi-Unit E



NaturalStone
Multi-Unit F

Random Bundle					Single Units		
	12 X 24"	18 X 24"	24 X 24"	24 X 36"		24 X 24"	24 X 36"
	300 X 600 X 22MM 11 3/4 X 23 5/8 X 7/8"	450 X 600 X 22MM 17 3/4 X 23 5/8 X 7/8"	600 X 600 X 22MM 23 5/8 X 23 5/8 X 7/8"	600 X 900 X 22MM 23 5/8 X 35 1/2 X 7/8"		600 X 600 X 22MM 23 5/8 X 23 5/8 X 7/8"	600 X 900 X 22MM 23 5/8 X 35 1/2 X 7/8"
			Also sold separately in all colors	Also sold separately in all colors		Also sold separately in all colors	Also sold separately in all colors

Notes: **SOLD IN FULL CRATES ONLY.** Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Brushed / Riven

Joint Spacing - 0 mm

Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

	48 X 12" FULLNOSE COPING	48 X 12" ROCK FACED COPING	24 X 24" PILLAR CAP
Bundle Type	SINGLE	SINGLE	SINGLE
Thickness (mm)	50 MM	50 MM	64 MM

UNITS PER	Crate	20.00	20.00	14.00
	SqFt	-	-	-

LBS PER	Unit	101	106	137
	Bundle	2,028	2,116	1,914

COLORS	Reflectance	Stock	Stock	Stock
Autumn Harvest (Riven)	SR n/a SRI n/a	✓	✓	✓
Golden Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓
Indian Coast (Brushed)	SR n/a SRI n/a	✓	✓	✓
Ivory Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓
Stone Cliff Grey (Riven)	SR n/a SRI n/a	✓	✓	✓

	48" X 16" STEP
Bundle Type	SINGLE
Thickness (mm)	150 MM

FCFT PER	Crate	32.00
-----------------	-------	-------

LNFT PER	Crate	24.00
-----------------	-------	-------

UNITS PER	Crate	6.00
------------------	-------	------

LBS PER	Bundle	2,526
----------------	--------	-------

COLORS	Reflectance	Stock
Autumn Harvest (Riven)	SR n/a SRI n/a	✓
Golden Sand (Brushed)	SR n/a SRI n/a	✓
Indian Coast (Brushed)	SR n/a SRI n/a	✓
Ivory Sand (Brushed)	SR n/a SRI n/a	✓
Stone Cliff Grey (Riven)	SR n/a SRI n/a	✓

Single Units



4' FULLNOSE
1,200 X 50 X 300MM
47 1/4 X 2 X 11 7/8"



4' ROCK FACE
1,200 X 50 X 300MM
47 1/4 X 2 X 11 7/8"



PILLAR CAP
600 X 600 X 64MM
23 5/8 X 23 5/8 X 2 5/8"



48 X 16" STEP
1,200 X 150 X 400MM
47 1/4 X 5 7/8 X 15 3/4"
Indian Coast, Ivory Sand, Golden Sand
& Stone Cliff Grey only

Notes: Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Riven
Joint Spacing - 0 mm
Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

BRUSHED FINISH	4 PC BUNDLE	24" X 24"	24" X 36"
Bundle Type	RANDOM	SINGLE	SINGLE
Thickness (mm)	22 MM	22 MM	22 MM

SQFT PER	Crate	174.00	160.00	180.00
	Units	3.63	4.00	6.00

UNITS PER	Crate	48.00	40.00	30.00
	SqFt	0.28	0.25	0.17

LBS PER	Unit	47	46	69
	Bundle	2,265	1,851	2,082

COLORS	Reflectance	Stock	Stock	Stock
Black River	SR n/a SRI n/a	✓	✓	✓
Winter Mist	SR n/a SRI n/a	✓	✓	✓

LAYING PATTERNS









NaturalStone
Multi-Unit D



NaturalStone
Multi-Unit E



NaturalStone
Multi-Unit F

Random Bundle					Single Units		
	12 X 24" 300 X 600 X 22MM 11 3/4 X 23 5/8 X 7/8"	18 X 24" 450 X 600 X 22MM 17 3/4 X 23 5/8 X 7/8"	24 X 24" 600 X 600 X 22MM 23 5/8 X 23 5/8 X 7/8" Also sold separately in all colors	24 X 36" 600 X 900 X 22MM 23 5/8 X 35 1/2 X 7/8" Also sold separately in all colors		24 X 24" 600 X 600 X 22MM 23 5/8 X 23 5/8 X 7/8" Also sold separately in all colors	24 X 36" 600 X 900 X 22MM 23 5/8 X 35 1/2 X 7/8" Also sold separately in all colors

Notes: **SOLD IN FULL CRATES ONLY.** Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**

Natural Stone - Limestone

Steps, Coping and Pillar Cap



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Riven
Joint Spacing - 0 mm
Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

	36 X 12" ROCK FACED COPING	36 X 12" FULLNOSE COPING	48 X 12" ROCK FACED COPING	48 X 12" FULLNOSE COPING	24 X 24" PILLAR CAP
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	50 MM	50 MM	50 MM	50 MM	64MM

UNITS PER	Crate	30.00	20.00	20.00	20.00	14.00
	SqFt	-	-	-	-	-

LBS PER	Unit	-	79	104	159	137
	Bundle	2,425	1,587	2,072	3,175	1,914

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
Black River	SR n/a SRI n/a			✓	✓	✓
Winter Mist	SR n/a SRI n/a	✓	✓			✓

	48" X 16" STEP
Bundle Type	SINGLE
Thickness (mm)	150 MM

FCFT PER	Crate	32.00
-----------------	-------	-------

LNFT PER	Crate	24.00
-----------------	-------	-------

UNITS PER	Crate	6.00
------------------	-------	------

LBS PER	Bundle	2,646
----------------	--------	-------

COLORS	Reflectance	Stock
Black River	SR n/a SRI n/a	✓

Single Units



4' FULLNOSE
1,200 X 50 X 300MM
47 1/4 X 2 X 11 7/8"



3' FULLNOSE
900 X 50 X 300MM
35 1/2 X 2 X 11 7/8"



4' ROCK FACE
1,200 X 50 X 300MM
47 1/4 X 2 X 11 7/8"



PILLAR CAP
600 X 600 X 64MM
23 5/8 X 23 5/8 X 2 5/8"



48 X 16" STEP
1,200 X 150 X 400MM
47 1/4 X 5 7/8 X 15 3/4"
Black River only

Notes: Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurement are nominal. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Smooth
Joint Spacing - 8 mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

	SMOOTH CLASSIC
Bundle Type	SINGLE
Plant Produced	OHIO
Thickness (mm)	80 MM

SQFT PER	Bundle	77.33
	Layer	9.67
	Section	-
	Stone	0.54

PER BUNDLE	Layers	8.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.86
	Section	-
	Bundle	144.00


LBS PER	Layer	350
	Section	-
	Bundle	2,801

COLORS	Reflectance	Stock
All Colors & Finishes	SR n/a SRI n/a	SO

LAYING PATTERNS



Optiloc A



Optiloc B

Single Unit



STANDARD
100 X 200 X 80MM
3 7/8 X 7 7/8 X 3 1/8"
378 Units/Bundle
.22 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.

Porcelain 24" x 24"



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Stone Finish

Joint Spacing - n/a

Void - n/a


TECHNICAL INFORMATION

Visit Unilock.com for more information.


		DEL CONCA SQUARE PRESSED EDGE	DEL CONCA SQUARE PRESSED EDGE
Bundle Type		SINGLE	RANDOM
Plant Produced			
Thickness (mm)		20 MM	20 MM
SQFT PER	Pallet	248.00	434.00
	Box	7.75	-
	Unit	3.88	-
PER PALLET	Box	32.00	-
	SqFt	248.00	-
	Unit	64.00	-
UNITS PER	Pallet	64.00	192
	Box	2.00	-
LBS PER	Unit	36	-
	SqFt	9	-
	Box	72	-
	Pallet	2,310	4,005

COLORS	Reflectance	Stock	Stock
Chamonix Beige	SR n/a SRI n/a	✓	
Chamonix Bianco	SR n/a SRI n/a	✓	
Chamonix Dark Grey	SR n/a SRI n/a	✓	
Chamonix Grey	SR n/a SRI n/a	✓	
Gotham Bianco	SR n/a SRI n/a	✓	
Gotham Grey	SR n/a SRI n/a	✓	✓
Gotham Nero	SR n/a SRI n/a	✓	
Travestone Beige	SR n/a SRI n/a	✓	✓
Travestone Grey	SR n/a SRI n/a	✓	
West 57th Bianco	SR n/a SRI n/a	✓	
West 57th Grey	SR n/a SRI n/a	✓	

LAYING PATTERNS



Porcelain 24x24 RB_A



Porcelain 24x24 SB_B

AVAILABLE IN GOTHAM GREY & TRAVSTONE BEIGE ONLY			
Single Unit		12X12 300 X 300 X 20MM 11 7/8 X 11 7/8 X 7/8"	12X24 300 X 600 X 20MM 11 7/8 X 23 5/8 X 7/8"
Random Bundle		24X24 600 X 600 X 20MM 23 5/8 X 23 5/8 X 7/8"	24X24 600 X 600 X 20MM 23 5/8 X 23 5/8 X 7/8"

Notes: **SOLD IN FULL CRATES ONLY.** All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**

Porcelain 16" x 32"



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Stone / Woodgrain (WG) Finish

Joint Spacing - n/a

Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.


		DEL CONCA RECTANGLE PRESSED EDGE (STONE)	DEL CONCA RECTANGLE PRESSED EDGE (WOOD)
Bundle Type		SINGLE	SINGLE
Plant Produced			
Thickness (mm)		20 MM	20 MM
SQFT PER	Pallet	165.36	268.71
	Box	6.89	6.89
	Unit	3.45	3.45
PER PALLET	Box	24.00	39.00
	SqFt	165.36	268.71
	Unit	48.00	78.00
UNITS PER	Pallet	48.00	78.00
	Box	2.00	2.00
LBS PER	Unit	32	32
	SqFt	9	9
	Box	65	64
	Pallet	1,552	2,504

COLORS	Reflectance	Stock	Stock
Arbor Bianco (WG)	SR n/a SRI n/a		✓
Quartzite Bianco	SR n/a SRI n/a	✓	
Quartzite Dark Grey	SR n/a SRI n/a	✓	
Quartzite Grey	SR n/a SRI n/a	✓	
Quartzite Sand	SR n/a SRI n/a	✓	
Travestone Beige	SR n/a SRI n/a	✓	
Travestone Grey	SR n/a SRI n/a	✓	

LAYING PATTERNS



Porcelain 16x32 RB_C



Porcelain 16x32 HB_D

Single Unit



PRESSED EDGE RECTANGLE

400 X 800 X 20MM

15 3/4 X 31 1/2 X 7/8"

3.45 Sq.Ft./Stone

Notes: **SOLD IN FULL CRATES ONLY.** All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**

Porcelain 16" x 48"



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Woodgrain Finish

Joint Spacing - n/a

Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

		DEL CONCA RECTANGLE PRESSED EDGE
Bundle Type		SINGLE
Plant Produced		
Thickness (mm)		20 MM

SQFT PER	Pallet	279.18
	Box	5.17
	Unit	5.17

PER PALLET	Box	54.00
	SqFt	279.18
	Unit	54.00

UNITS PER	Pallet	54.00
	Box	1.00

LBS PER	Unit	52
	SqFt	10
	Box	52
	Pallet	2,797

COLORS	Reflectance	Stock
Monteverde Beige	SR n/a SRI n/a	✓
Monteverde Grey	SR n/a SRI n/a	✓
Monteverde Noce	SR n/a SRI n/a	✓

LAYING PATTERNS



Porcelain 16x48 RB_E



Porcelain 16x48 HB_F

Single Unit



DEL CONCA RECTANGLE
400 X 1200 X 20MM
15 3/4 X 47 1/4 X 7/8"
5.17 Sq.Ft./Stone

Notes: **SOLD IN FULL CRATES ONLY.** All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth,
Series™ Exposed & Il Campo® Brushed
Joint Spacing - 4 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™


Refined surface and long-lasting color

TECHNICAL INFORMATION


Conforms to ASTM C 936
Eligible for LEED v4.1 credits

		SMOOTH 4 X 16	SMOOTH 8 X 24	SERIES EXPOSED 8 X 24	IL CAMPO 8 X 24
	Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
	Plant Produced	PICKERING	PICKERING	GEORGETOWN	GEORGETOWN
	Thickness (mm)	100 MM	100 MM	100 MM	100 MM
SQFT PER	Bundle	51.67	51.67	51.67	51.67
	Layer	10.33	10.33	10.33	10.33
	Section	-	-	-	-
	Stone	0.43	1.29	1.29	1.29
PER BUNDLE	Layers	5.00	5.00	5.00	5.00
	Sections	-	-	-	-
SOLDIER LNFT PER	SqFt	0.76	0.51	0.51	0.51
	Section	-	-	-	-
	Layer	7.87	5.25	5.25	5.25
	Bundle	39.37	26.25	26.25	26.25
SAILOR LNFT PER	SqFt	3.05	1.52	1.52	1.52
	Section	-	-	-	-
	Layer	31.50	15.75	15.75	15.75
	Bundle	157.48	78.74	78.74	78.74
UNITS PER	SqFt	2.32	0.77	0.77	0.77
	Section	-	-	-	-
	Bundle	120.00	40.00	40.00	40.00
LBS PER	Layer	488	478	478	478
	Section	-	-	-	-
	Bundle	2,440	2,391	2,391	2,391
COLORS		Reflectance	Stock	Stock	Stock
Black Granite (Series)		SR n/a SRI n/a			✓
Dk Charcoal (Il Campo)		SR n/a SRI n/a			✓
Granite (Il Campo)		SR n/a SRI n/a			✓
Light Grey (Il Campo)		SR n/a SRI n/a			✓
Opal (Smooth)		SR .24 SRI 24		✓	
Steel Grey d (Sm)		SR n/a SRI n/a	✓		


LAYING PATTERNS



Promenade 8x24
RB_D



Promenade 8x24
HB_F



Promenade 4x16
RB_A

Single Units					
		4" X 16" SMOOTH 100 X 400 X 100MM 3 7/8 X 15 3/4 X 3 7/8" 120 Units/Bundle .43 Sq.Ft./Stone		8" X 24" SMOOTH 200 X 600 X 100MM 7 7/8 X 23 5/8 X 3 7/8" 40 Units/Bundle 1.29 Sq.Ft./Stone	
				8" X 24" SERIES EXPOSED 200 X 600 X 100MM 7 7/8 X 23 5/8 X 3 7/8" 40 Units/Bundle 1.29 Sq.Ft./Stone	
					8" X 24" IL CAMPO BRUSHED 200 X 600 X 100MM 7 7/8 X 23 5/8 X 3 7/8" 40 Units/Bundle 1.29 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded

Surface Texture - Smooth, Series™ Exposed & Umbriano®

Joint Spacing - 4 mm

Void - n/a

TECHNOLOGIES

PERMEABLE (Umbriano)

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

EASYSOAK™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLORFUSION™ (Umbriano)


Subtly mottled colored finish

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



Promenade 4x12
RB_A



Promenade 4x12
HB_C

	4 X 12 SMOOTH	4 X 12 SERIES®	4 X 12 UMBRIANO®
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	CHICAGO	MARENGO
Thickness (mm)	80 MM	80 MM	80 MM

SQFT PER	Bundle	81.41	93.04	93.04
	Layer	11.63	11.63	11.63
	Section	-	-	-
	Stone	0.32	0.32	0.32

PER BUNDLE	Layers	7.00	8.00	8.00
	Sections	-	-	-

SOLDIER LNFT PER	SqFt	1.02	1.02	1.02
	Section	-	-	-
	Layer	11.81	11.81	11.81
	Bundle	82.68	94.49	94.49

SAILOR LNFT PER	SqFt	3.05	3.05	3.05
	Section	-	-	-
	Layer	35.43	35.43	35.43
	Bundle	248.03	283.46	283.46

UNITS PER	SqFt	3.10	3.10	3.10
	Section	-	-	-
	Bundle	252.00	288.00	288.00

LBS PER	Layer	425	426	426
	Section	-	-	-
	Bundle	2,978	3,404	3,404

COLORS	Reflectance	Stock	Stock	Stock
Arctic Grey (SER)	SR n/a SRI n/a		✓	
Nordic Star (SER)	SR n/a SRI n/a		✓	
Opal Blend (SM)	SR n/a SRI n/a	✓		
Dark Charcoal(SM)	SR n/a SRI n/a	✓		
Medium Grey (SM)	SR n/a SRI n/a	✓		
French Grey (UMB)	SR .17 SRI 15			✓
Midnight Sky (UMB)	SR .17 SRI 15			✓
Winter Marvel (UMB)	SR .17 SRI 15			✓

Single Units



4" X 12"
SMOOTH
100 X 300 X 80MM
3 7/8 X 11 7/8 X 3 1/8"
252 Units/Bundle
.32 Sq.Ft./Stone



4" X 12"
SERIES® EXPOSED
100 X 300 X 80MM
3 7/8 X 11 7/8 X 3 1/8"
288 units/Bundle
.32 Sq.Ft./Stone



4" X 12"
UMBRIANO®
100 X 300 X 80MM
3 7/8 X 11 7/8 X 3 1/8"
288 Units/Bundle
.32 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

Promenade® Premier 4x12" - 100mm

ENDURACOLOR™



APPLICATIONS



APPEARANCE

Edge Detail - Rounded

Surface Texture - Smooth, Series™ Exposed,

Il Campo® Brushed & Umbriano®

Joint Spacing - 4 mm / 7mm (Umbriano)

Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

	4X12" SMOOTH	4X12" SERIES	4X12" IL CAMPO
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	PICKERING	GEORGETOWN	GEORGETOWN
Thickness (mm)	100 MM	100 MM	100 MM

SQFT PER	Bundle	58.13	58.13	58.13
	Layer	11.63	11.63	11.63
	Section	-	-	-
	Stone	0.32	0.32	0.32

PER BUNDLE	Layers	5.00	5.00	5.00
	Sections	-	-	-

SOILDER LNFT PER	SqFt	1.02	1.02	1.02
	Section	-	-	-
	Layer	11.81	11.81	11.81
	Bundle	59.06	59.06	59.06


SAILOR LNFT PER	SqFt	3.05	3.05	3.05
	Section	-	-	-
	Layer	35.43	35.43	35.43
	Bundle	177.17	177.17	177.17

UNITS PER	SqFt	3.10	3.10	3.10
	Section	-	-	-
	Bundle	180.00	180.00	180.00


LBS PER	Layer	532	532	532
	Section	-	-	-
	Bundle	2,659	2,659	2,659

COLORS	Reflectance	Stock	Stock	Stock
Black Granite (SER)	SR n/a SRI n/a		✓	
Light Grey (ILC)	SR n/a SRI n/a			✓
Sandstone (SM)	SR n/a SRI n/a	✓		




LAYING PATTERNS



Promenade 4x12_
RB_H



Promenade 4x12
HB_I

Single Units		4" X 12" SMOOTH 100 X 300 X 100MM 3 7/8 X 11 7/8 X 3 7/8" 180 Units/Bundle .32 Sq.Ft./Stone		4" X 12" SERIES EXPOSED 100 X 300 X 100MM 3 7/8 X 11 7/8 X 3 7/8" 180 Units/Bundle .32 Sq.Ft./Stone		4" X 12" IL CAMPO BRUSHED 100 X 300 X 100MM 3 7/8 X 11 7/8 X 3 7/8" 180 Units/Bundle .32 Sq.Ft./Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
 Surface Texture - Textured
 Joint Spacing - 10 mm
 Void - n/a

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of
 Realta and Ultima technologies

EASYCLEAN™

Factory Sealed to provide integral stain resistance

REALTA™

Cast from natural stone

ULTIMA™

Up to 4x stronger than poured-in-place concrete

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

Bundle Type		RANDOM
Plant Produced		AYR
Thickness (mm)		60 MM

SQFT PER	Bundle	90.30
	Layer	11.29
	Section	-
	Stone	0.56

PER BUNDLE	Layers	8.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	1.31
	Section	-
	Layer	14.78
	Bundle	118.22

UNITS PER	SqFt	1.77
	Section	-
	Bundle	160.00


LBS PER	Layer	309
	Section	-
	Bundle	2,472

COLORS	Reflectance	Stock
Dawn Mist	SR n/a SRI n/a	✓
Pebble Taupe	SR n/a SRI n/a	✓

LAYING PATTERNS



Richcliff Fixed
Random A



Richcliff Fixed
Random B



Richcliff LargeRec
HB_H

Random Bundle		RECTANGLE 226 X 300 X 60MM 8 7/8 X 11 7/8 X 2 3/8" 64 Units/Bundle .75 SqFt./Stone
		SQUARE 226 X 226 X 60MM 8 7/8 X 8 7/8 X 2 3/8" 32 units/Bundle .58 SQ.FT./Stone
		SMALL RECTANGLE 150 X 226 X 60MM 5 7/8 X 8 7/8 X 2 3/8" 64 units/Bundle .38 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Series Exposed
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES


ENDURACOLOR™
Refined surface and long-lasting color

TECHNICAL INFORMATION


Conforms to ASTM C 936
Eligible for LEED v4.1 credits

		SERIES EXPOSED
Bundle Type		4X8
Plant Produced		CHICAGO
Thickness (mm)		60 MM
SQFT PER	Bundle	117.90
	Layer	11.79
	Section	-
	Stone	0.22
PER BUNDLE	Layers	10.00
	Sections	-
SOILDER LNFT PER	SqFt	1.50
	Section	-
	Layer	17.72
	Bundle	177.17
SAILOR LNFT PER	SqFt	3.01
	Section	-
	Layer	35.43
	Bundle	354.33
UNITS PER	SqFt	4.58
	Section	-
	Bundle	540.00
LBS PER	Layer	328
	Section	-
	Bundle	3,283
COLORS		
Reflectance	Stock	
Onyx Black	SR n/a SRI n/a	✓

LAYING PATTERNS



Series 4x8_HB_G



Series 4x8_RB_F

Single Units



4 X 8
100 X 200 X 60MM
3 7/8 X 7 7/8 X 2 3/8"
540 Units/Bundle
.22 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 2mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 1782
Eligible for LEED v4.1 credits

	24 X 24
Bundle Type	SINGLE
Plant Produced	OHIO
Thickness (mm)	50 MM

SQFT PER	Bundle	80.00
	Layer	8.00
	Section	-
	Stone	4.00

PER BUNDLE	Layers	10.00
	Sections	-

SOILDER LNFT PER	SqFt	0.50
	Section	-
	Layer	4.00
	Bundle	40.00


SAILOR LNFT PER	SqFt	0.50
	Section	-
	Layer	4.00
	Bundle	40.00

UNITS PER	SqFt	0.25
	Section	-
	Bundle	20.00

LBS PER	Layer	183
	Section	-
	Bundle	1,833

COLORS	Reflectance	Stock
Chamois NEW	SR n/a SRI n/a	✓
Silver Grey	SR n/a SRI n/a	✓

LAYING PATTERNS




Skyline 24x24 SB_A



Skyline 24x24 RB_B

Single Unit



24 X 24
606 X 606 X 50MM
23 7/8 X 23 7/8 X 2"
20 Units/Bundle
4.00 Sq.Ft./Stone

Pedestal System

Contact your local Unilock Rep for more information.



Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Product is not intended vehicular applications.** Minimum quantities apply. Unilock offers adjustable and stackable pedestal systems; please contact your Territory Manager for pricing and availability. All measurements are nominal.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - X mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color


COMFORT STEP

Ultra-smooth surface texture

TECHNICAL INFORMATION

Conforms to ASTM C 1782
Eligible for LEED v4.1 credits

LAYING PATTERNS



Soreno 16x32 RB_A

	16 X 32
Bundle Type	SINGLE
Plant Produced	CHICAGO
Thickness (mm)	50 MM

SQFT PER	Bundle	64.27
	Layer	3.57
	Section	-
	Stone	3.57

PER BUNDLE	Layers	18.00
	Sections	-

SOLDIER LNFT PER	SqFt	0.37
	Section	-
	Layer	1.34
	Bundle	24.04

SAILOR LNFT PER	SqFt	0.75
	Section	-
	Layer	2.67
	Bundle	48.13

UNITS PER	SqFt	0.28
	Section	-
	Bundle	18.00

LBS PER	Layer	85
	Section	-
	Bundle	1,536

COLORS	Reflectance	Stock
Light Granite	SR n/a SRI n/a	✓
Toscana Beige	SR n/a SRI n/a	✓

**Weight has been estimated - product has not yet been produced.
Please confirm weight upon ordering.**

Single Unit



16 X 32
407 X 815 X 50MM
16 X 32 X 2"
18 Units/Bundle
3.57 Sq.Ft./Stone

Pedestal System

Contact your local Unilock
Rep for more information.



Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Textured
Joint Spacing - 11-18 mm
Void - 4.4%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™


Refined surface and long-lasting color

TECHNICAL INFORMATION


Conforms to ASTM C 936
Eligible for LEED v4.1 credits

Bundle Type		RANDOM
Plant Produced		OHIO
Thickness (mm)		70 MM
SQFT PER	Bundle	88.61
	Layer	11.08
	Section	-
	Stone	0.92
PER BUNDLE	Layers	8.00
	Sections	-
SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
UNITS PER	SqFt	1.08
	Section	-
	Bundle	96.00
LBS PER	Layer	330
	Section	-
	Bundle	2,638
COLORS		Reflectance
Fossil	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

LAYING PATTERNS






Thornbury Fixed
Random A



Thornbury Fixed
Random B



Thornbury Fixed
Random C

Random Bundle		LARGE RECTANGLE 350 X 420 X 70MM 13 7/8" X 16 5/8" X 2 3/4" 32 Units/Bundle 1.58 SqFt./Stone
		SQUARE 210 X 350 X 70MM 8 3/8" X 13 7/8" X 2 3/4" 32 Units/Bundle .79 Sq.Ft./Stone
		SMALL RECTANGLE 173 X 210 X 70MM 6 7/8" X 8 3/8" X 2 3/4" 32 Units/Bundle .39 Sq.Ft./Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ELEGANCE™

Timeless, long-lasting beauty with the combination of Realta and Ultima technologies

EASYSOIL™

Factory Sealed to provide integral stain resistance

REALTA™

Cast from historical brick

ULTIMA™

Up to 4x stronger than poured-in-place concrete


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


Bundle Type		SINGLE
Plant Produced		AYR
Thickness (mm)		70 MM
SQFT PER	Bundle	88.41
	Layer	11.05
	Section	-
	Stone	0.28
PER BUNDLE	Layers	8.00
	Sections	-
SOILDR LNFT PER	SqFt	1.19
	Section	-
	Layer	13.12
	Bundle	104.99
SAILOR LNFT PER	SqFt	2.97
	Section	-
	Layer	32.81
	Bundle	262.47
UNITS PER	SqFt	3.62
	Section	-
	Bundle	320.00
LBS PER	Layer	361
	Section	-
	Bundle	2,888

COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓

LAYING PATTERNS



TownHall 4x10 HB_B



TownHall 4x10 RB_C

Single Unit



STANDARD
100 X 250 X 70MM
3 7/8 X 9 7/8 X 2 3/4"
320 Units/Bundle
.28 SqFt/Stone



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Textured
Joint Spacing - 4mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

		TREO PREMIER TEXTURED
Bundle Type		RANDOM
Plant Produced		OHIO
Thickness (mm)		60 MM

SQFT PER	Bundle	98.09
	Layer	10.90
	Section	-
	Stone	0.45

PER BUNDLE	Layers	9.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	1.79
	Section	-
	Layer	19.56
	Bundle	176.06

UNITS PER	SqFt	2.20
	Section	-
	Bundle	216.00

LBS PER	Layer	285
	Section	-
	Bundle	2,565

COLORS	Reflectance	Stock
Granite Fusion	SR n/a SRI n/a	✓
River	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓




LAYING PATTERNS



TreoSmooth Fixed
Random_R



TreoSmooth Fixed
Random_S

Random Bundle		LARGE RECTANGLE 225 X 337.5 X 60MM 8 7/8 X 13 3/8 X 2 3/8" 45 Units/Bundle .82 Sq.Ft./Stone		SQUARE 225 X 225 X 60MM 8 7/8 X 8 7/8 X 2 3/8" 54 Units/Bundle .55 Sq.Ft./Stone		SMALL RECTANGLE 112.5 X 225 X 60MM 4 1/2 X 8 7/8 X 2 3/8" 117 Units/Bundle .27 Sq.Ft./Stone
---------------	---	--	---	--	---	--

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Textured
Joint Spacing - 7mm
Void - 5.5 %

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

PERMEABLE

Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



TreoSmooth Fixed
Random_R



TreoSmooth Fixed
Random_S

		TREO SMOOTH PERMEABLE
Bundle Type		RANDOM
Plant Produced		OHIO
Thickness (mm)		60 MM

SQFT PER	Bundle	108.99
	Layer	10.90
	Section	-
	Stone	0.52

PER BUNDLE	Layers	10.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	1.35
	Section	-
	Layer	14.76
	Bundle	147.64

UNITS PER	SqFt	1.93
	Section	-
	Bundle	210.00

LBS PER	Layer	296
	Section	-
	Bundle	2,960

COLORS	Reflectance	Stock
Fossil	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓
Tuscany	SR n/a SRI n/a	✓

Random Bundle



LARGE RECTANGLE
225 X 337.5 X 60MM
8 7/8 X 13 3/8 X 2 3/8"
60 Units/Bundle
.82 Sq.Ft./Stone



SQUARE
225 X 225 X 60MM
8 7/8 X 8 7/8 X 2 3/8"
70 Units/Bundle
.55 Sq.Ft./Stone



SMALL RECTANGLE
112.5 X 225 X 60MM
4 1/2 X 8 7/8 X 2 3/8"
80 Units/Bundle
.27 Sq.Ft./Stone



APPLICATIONS



APPEARANCE

Edge Detail - Micro

Surface Texture - Series Exposed Textured

Joint Spacing - 10mm

Void - 5.6%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

		SERIES EXPOSED TEXTURED
Bundle Type		RANDOM
Plant Produced		CHICAGO
Thickness (mm)		70 MM

SQFT PER	Bundle	97.53
	Layer	12.19
	Section	12.19
	Stone	0.32

PER BUNDLE	Layers	8.00
	Sections	8.00

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	2.34
	Section	28.49
	Layer	28.49
	Bundle	227.95

UNITS PER	SqFt	3.12
	Section	38.00
	Bundle	304.00

LBS PER	Layer	398
	Section	398
	Bundle	3,186

COLORS	Reflectance	Stock
Cobalt Grey	SR n/a SRI n/a	✓
Peppered Granite	SR .38 SRI 42	✓

LAYING PATTERNS



Tribeca Cobble
Fixed Random_A

Random Bundle		LARGE RECTANGLE 130 X 305 X 70MM 5 X 12 X 2 ¾" 88 Units/Bundle .43 Sq.Ft./Stone		RECTANGLE 130 X 230 X 70MM 5 X 9 X 2 ¾" 88 Units/Bundle .32 Sq.Ft./Stone		SMALL RECTANGLE 130 X 175 X 70MM 5 X 6 ½ X 2 ¾" 128 Units/Bundle .25 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices on page 79. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 2mm
Void - 40%

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

PERMEABLE

Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C1319
Eligible for LEED v4.1 credits

		SMOOTH
	Bundle Type	RANDOM
	Plant Produced	OHIO
	Thickness (mm)	80 MM

SQFT PER	Bundle	70.00
	Layer	10.00
	Section	-
	Stone	2.50

PER BUNDLE	Layers	7.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	0.40
	Section	-
	Bundle	28.00

LBS PER	Layer	249
	Section	-
	Bundle	1,746

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	✓

LAYING PATTERNS



Turfstone A

Single Unit

LARGE RECTANGLE
400 X 600 X 80MM
15 3/4 X 23 5/8 X 3 1/8"
28 Units/Bundle
2.50 Sq.Ft./Stone

Notes: Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Umbriano Mottled
Joint Spacing - 7mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance


COLORFUSION™

Subtly mottled colored finish


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Umbriano Fixed
Random_A



Umbriano Fixed
Random_B

		4 x 8	21 x 35 Slab
Bundle Type	RANDOM	SINGLE	SINGLE
Plant Produced	GEORGETOWN	MARENGO	GEORGETOWN
Thickness (mm)	60 MM	60 MM	60 MM

SQFT PER	Bundle	94.14	106.20	62.76
	Layer	10.46	11.80	10.46
	Section	-	-	-
	Stone	1.31	0.22	-

PER BUNDLE	Layers	9.00	9.00	6.00
	Sections	-	-	-

SOILDER LNFT PER	SqFt	-	1.50	-
	Section	-	-	-
	Layer	-	17.72	-
	Bundle	-	159.45	21.26

SAILOR LNFT PER	SqFt	0.85	3.00	-
	Section	-	-	-
	Layer	8.86	35.43	-
	Bundle	79.72	318.90	35.43

UNITS PER	SqFt	0.76	4.58	0.19
	Section	-	-	-
	Bundle	72.00	486.00	12

LBS PER	Layer	287	322	287
	Section	-	-	-
	Bundle	2,584	2,900	1,722

COLORS	Reflectance	Stock	Stock	Stock
French Grey	SR .18 SRI 17	✓		✓
Grenada White	SR .17 SRI 15	✓		✓
Midnight Sky (4x8 only)	SR .17 SRI 15		✓	
Summer Wheat	SR .42 SRI 48	✓		✓
Winter Marvel	SR .35 SRI 38	✓		✓

Random Bundle				Single Units		
	LARGE RECTANGLE 350 X 546 X 60MM 13 7/8 X 21 1/2 X 2 3/8" 18 Units/Bundle XX Sq.Ft./Stone	SQUARE 360 X 360 X 60MM 14 1/4 X 14 1/4 X 2 3/8" 27 Units/Bundle XX Sq.Ft./Stone	SMALL RECTANGLE 180 X 360 X 60MM 7 X 14 1/4 X 2 3/8" 27 Units/Bundle XX Sq.Ft./Stone		4X8 100 X 200 X 60MM 3 7/8 X 7 7/8 X 2 3/8" 486 Units/Bundle .22 Sq.Ft./Stone	SLAB 540 X 900 X 60MM 21 1/4 X 35 1/2 X 2 3/4" 12 Units/Bundle 5.23 Sq.Ft./Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Umbriano Mottled
Joint Spacing - 7mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance


COLORFUSION™

Subtly mottled colored finish


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Umbriano 24x24
RB_AG



Umbriano 12x24
HB_O

	24 x 24	12 x 24	8 x 24	8 x 16	16 x 16
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	GEORGETOWN	GEORGETOWN	GEORGETOWN	GEORGETOWN	GEORGETOWN
Thickness (mm)	70 MM	70 MM	70 MM	70 MM	70 MM

SQFT PER	Bundle	62.00	93.00	82.67	82.67	82.67
	Layer	7.75	11.63	10.33	10.33	10.33
	Section	-	-	-	-	-
	Stone	3.88	1.94	1.29	0.86	1.72

PER BUNDLE	Layers	8.00	8.00	8.00	8.00	8.00
	Sections	-	-	-	-	-

SOILDER LNFT PER	SqFt	0.51	0.51	0.51	0.76	0.76
	Section	-	-	-	-	-
	Layer	3.94	5.91	5.25	7.87	7.87
	Bundle	31.50	47.24	41.99	62.99	62.99

SAILOR LNFT PER	SqFt	0.51	1.02	1.02	1.52	0.76
	Section	-	-	-	-	-
	Layer	3.94	11.81	10.50	15.75	7.87
	Bundle	31.50	94.49	83.99	125.98	62.99

UNITS PER	SqFt	0.26	0.52	0.77	1.16	0.58
	Section	-	-	-	-	-
	Bundle	16.00	48.00	64.00	96.00	48.00

LBS PER	Layer	258	393	331	343	350
	Section	-	-	-	-	-
	Bundle	2,062	3,142	2,647	2,746	2,797

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
French Grey	SR .18 SRI 17	✓	✓	✓	✓	✓
Midnight Sky	SR .17 SRI 15			✓	✓	
Summer Wheat	SR .42 SRI 48	✓	✓	✓	✓	✓
Winter Marvel	SR .35 SRI 38	✓	✓	✓	✓	✓

Single Units	24 X 24	12 X 24	8 X 24	8 X 16	16 X 16
	600 X 600 X 70MM 23 5/8 X 23 5/8 X 2 3/4" 16 Units/Bundle 3.88 Sq.Ft./Stone	300 X 600 X 70MM 11 1/8 X 23 5/8 X 2 3/4" 48 Units/Bundle 1.94 Sq.Ft./Stone	200 X 600 X 70MM 7 1/8 X 23 5/8 X 2 3/4" 64 Units/Bundle 1.29 Sq.Ft./Stone	200 X 400 X 70MM 7 7/8 X 15 3/4 X 2 3/4" 96 Units/Bundle .86 Sq.Ft./Stone	400 X 400 X 70MM 15 3/4 X 15 3/4 X 2 3/4" 48 Units/Bundle 1.72 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. 24x24" paver is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Umbriano Mottled
Joint Spacing - 7mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



Umbriano Fixed
Random A



Umbriano Fixed
Random B



Umbriano Multi-Unit
Random G

Random Bundle			
	LARGE RECTANGLE 350 X 546 X 80MM 13 7/8 X 21 1/2 X 3 1/8" 14 Units/Bundle 2.09 Sq.Ft./Stone	SQUARE 360 X 360 X 80MM 14 1/4 X 14 1/4 X 3 1/8" 21 Units/Bundle 1.40 Sq.Ft./Stone	SMALL RECTANGLE 180 X 360 X 80MM 7 X 14 1/4 X 3 1/8" 21 Units/Bundle 0.70 Sq.Ft./Stone

	Bundle Type	RANDOM
	Plant Produced	GEORGETOWN
	Thickness (mm)	80 MM

SQFT PER	Bundle	73.22
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	7.00
	Sections	-

SOILDR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.85
	Section	-
	Layer	8.86
	Bundle	62.01

UNITS PER	SqFt	0.76
	Section	-
	Bundle	56.00

LBS PER	Layer	383
	Section	-
	Bundle	2,680

COLORS	Reflectance	Stock
French Grey	SR .18 SRI 17	✓
Summer Wheat	SR .42 SRI 48	✓
Winter Marvel	SR .35 SRI 38	✓

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Textured
 Joint Spacing - 3-7mm
 Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

Bundle Type	RANDOM
Plant Produced	OHIO
Thickness (mm)	70 MM

SQFT PER	Bundle	94.19
	Layer	11.77
	Section	-
	Stone	0.59

PER BUNDLE	Layers	8.00
	Sections	-

SOILDER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	1.24
	Section	-
	Layer	14.57
	Bundle	116.56

UNITS PER	SqFt	1.70
	Section	-
	Bundle	160.00


LBS PER	Layer	361
	Section	-
	Bundle	2,884

COLORS	Reflectance	Stock
Granite	SR n/a SRI n/a	✓
River	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

LAYING PATTERNS



Westport Fixed
Random_A



Westport Fixed
Random_B

Random Bundle



LARGE RECTANGLE
 254 X 380 X 70MM
 10 X 15 X 2 3/4"
 32 Units/Bundle
 XX Sq.Ft./Stone



SQUARE
 254 X 254 X 70MM
 10 X 10 X 2 3/4"
 56 Units/Bundle
 XX Sq.Ft./Stone



SMALL RECTANGLE
 127 X 254 X 60MM
 5 X 10 X 2 3/4"
 72 Units/Bundle
 XX Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	SMALL TAPERED ANTIQUED	STANDARD CLASSIC ANTIQUED
Bundle Type	SINGLE	SINGLE
Plant Produced	OHIO	OHIO
Thickness (mm)	100 MM	100 MM

FCFT PER	Bundle	36.00	36.00
	Layer	6.00	6.00
	Stone	0.25	0.33

PER BUNDLE	Layers	6.00	6.00
	Sections	-	6.00

LNFT PER	Bundle	108.00	108.00
	Unit	0.75	1.00

UNITS PER	SqFt	4.00	3.00
	Section	-	18.00
	Bundle	144.00	108.00

LBS PER	Layer	480	530
	Section	-	530
	Bundle	2,880	3,182

COLORS	Reflectance	Stock	Stock
Dark Charcoal	SR n/a SRI n/a	-	✓
Limestone	SR n/a SRI n/a	✓	✓
River	SR n/a SRI n/a	✓	✓
Sandstone	SR n/a SRI n/a	✓	✓
Sierra	SR n/a SRI n/a	✓	✓

SUNSET FIREPIT KITS

Available in the following colors

- see Page 75:

- River
- Limestone
- Sierra
- Sandstone



ROUND



SQUARE

Single Units



SMALL TAPERED
229 X 100 X 200MM
9 X 3 7/8 X 7 7/8"
144 Units/Bundle
.25 Fc.Ft./Stone



STANDARD
300 X 100 X 200MM
11 1/8 X 3 7/8 X 7 7/8"
108 Units/Bundle
.33 Fc.Ft./Stone

Notes: Small tapered units are sold in full bundles only. Maximum height is 24" (under optimum conditions). *Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. Ledge stone, Brussels XL or 6" x 12" Fullnose complement as a possible coping unit. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	DIMENSIONAL SMOOTH STANDARD
Bundle Type	MULTI COMPONENT
Plant Produced	OHIO
Thickness (mm)	100 MM

FCFT PER	Bundle	27.00
	Layer	9.00
	Stone	0.33

PER BUNDLE	Layers	3.00
	Sections	3.00

LNFT PER	Bundle	54.00
	Unit	0.67

UNITS PER	SqFt	3.00
	Section	27.00
	Bundle	81.00

LBS PER	Layer	784
	Section	784
	Bundle	2,353

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓
Limestone	SR n/a SRI n/a	✓
Sandstone	SR n/a SRI n/a	✓

Single Uni



CORNER

300 X 100 X 200MM

11 7/8 X 3 7/8 X 7 7/8"

81 Units/Bundle

.33 Fc.Ft./Stone

Notes: Small tapered units are sold in full bundles only. Maximum height is 24" (under optimum conditions). *Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. Ledgerstone, Brussels XL or 6" x 12" Fullnose complement as a possible coping unit. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Standard

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	TIE-BACK	STANDARD 1/2	CORNER 45°	CORNER 90°
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	600 MM	600 MM	600 MM	600 MM

FCFT PER	Bundle	2.00	3.00	7.04	7.04
	Layer	2.00	3.00	7.04	7.04
	Stone	2.00	3.00	7.04	7.04

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	-	3.00	-	-
	Unit	-	3.00	-	-

UNITS PER	SqFt	0.50	0.33	0.14	0.14
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,660	800	1,480	1,320
	Section	-	-	-	-
	Bundle	1,660	800	1,480	1,320

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO

Single Units



TIE-BACK
1830 X 300 X 600MM
72 X 12 X 24"
1 Unit/Bundle
2.00 Fc.Ft./Stone



1/2 STANDARD
915 X 300 X 600MM
36 X 12 X 24"
1 Unit/Bundle
3.00 Fc.Ft./Stone



CORNER 45°
1520 X 300 X 600MM
60 X 12 X 24"
1 Unit/Bundle
7.04 Fc.Ft./Stone



CORNER 90°
1520 X 300 X 600MM
72 X 12 X 24"
1 Unit/Bundle
7.04 Fc.Ft./Stone

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
 Surface Texture - Standard

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
 Eligible for LEED v4.1 credits

	STANDARD	COPING 1/2	COPING STANDARD	COPING CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	600 MM	600 MM	600 MM	600 MM

FCFT PER	Bundle	6.02	2.95	6.02	6.02
	Layer	6.02	2.95	6.02	6.02
	Stone	6.02	2.95	6.02	6.02

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	6.02	-	-	-
	Unit	6.02	-	-	-

UNITS PER	SqFt	0.17	0.34	0.17	0.17
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,680	780	1,560	1,560
	Section	-	-	-	-
	Bundle	1,680	780	1,560	1,560

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	S0	S0	S0	S0

Single Units



STANDARD
 1830 X 300 X 600MM
 72 X 11 7/8 X 23 5/8"
 1 Unit/Bundle
 6.02 Fc.Ft./Stone



1/2 COPING
 915 X 300 X 600MM
 36 X 11 7/8 X 23 5/8"
 1 Unit/Bundle
 2.95 Fc.Ft./Stone



COPING
 1830 X 300 X 600MM
 60 X 11 7/8 X 23 5/8"
 1 Unit/Bundle
 6.02 Fc.Ft./Stone



CLOSED-END COPING
 1830 X 300 X 600MM
 72 X 11 7/8 X 23 5/8"
 1 Unit/Bundle
 6.02 Fc.Ft./Stone

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
 Surface Texture - Standard

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C1372
 Eligible for LEED v4.1 credits

	TIE-BACK	STANDARD	COPING	COPING CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	600 MM	600 MM	600 MM	600 MM

FCFT PER	Bundle	1.17	6.02	24.08	24.08
	Layer	1.17	6.02	6.02	6.02
	Stone	1.17	6.02	6.02	6.02





PER BUNDLE	Layers	1.00	1.00	4.00	4.00
	Sections	-	-	-	-

LNFT PER	Bundle	-	6.02	-	-
	Unit	-	6.02	-	-

UNITS PER	SqFt	0.85	0.17	0.17	0.17
	Section	-	-	-	-
	Bundle	1.00	1.00	4.00	4.00

LBS PER	Layer	938	938	884	884
	Section	-	-	-	-
	Bundle	938	938	3,536	3,536

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	S0	S0	S0	S0

Single Units				
	TIE-BACK	STANDARD	COPING	CLOSED-END COPING
	1830 X 360 X 300MM	1830 X 360 X 300MM	1830 X 360 X 300MM	1830 X 360 X 300MM
	72 X 14 1/4 X 11 7/8"	72 X 14 1/4 X 11 7/8"	72 X 14 1/4 X 11 7/8"	72 X 14 1/4 X 11 7/8"
	1 Unit/Bundle	1 Unit/Bundle	4 Units/Bundle	4 Units/Bundle
	1.17 Fc.Ft./Stone	6.02 Fc.Ft./Stone	6.02 Fc.Ft./Stone	6.02 Fc.Ft./Stone

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Split

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	TAPERED SPLIT CLASSIC ANTIQUED	CORNER SPLIT CLASSIC ANTIQUED
Bundle Type	RANDOM	SINGLE
Plant Produced	OHIO	OHIO
Thickness (mm)	150 MM	150 MM

FCFT PER	Bundle	24.00	16.66
	Layer	6.00	4.17
	Stone	0.50	0.52





PER BUNDLE	Layers	4.00	4.00
	Sections	4.00	4.00

LNFT PER	Bundle	42.56	33.28
	Unit	0.89	1.04

UNITS PER	SqFt	2.00	1.92
	Section	12.00	8.00
	Bundle	48.00	32.00

LBS PER	Layer	574	444
	Section	574	444
	Bundle	2,297	1,776

COLORS	Reflectance	Stock	Stock
Granite	SR n/a SRI n/a	✓	✓
River	SR n/a SRI n/a	✓	✓
Sierra	SR n/a SRI n/a	✓	✓

Random Bundle				Single Units	
	LARGE TAPERED 375 X 150 X 230MM 14 7/8 X 5 7/8 X 9" 16 Units/Bundle	MEDIUM TAPERED 300 X 150 X 230MM 11 7/8 X 5 7/8 X 9" 16 Units/Bundle	SMALL TAPERED 228 X 150 X 230MM 9 X 5 7/8 X 9" 16 Units/Bundle		CORNER SPLIT 320 X 150 X 230MM 12 5/8 X 5 7/8 X 9" 32 Units/Bundle .52 Sq.Ft./Stone

Notes: 6" random wall bundles have convertible large units that can be used for corners or ending seat walls. End caps not sold separately. LedgeStone™, Brussels Block® XL, or Brussels Fullnose™ complement as a possible coping. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Standard
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	RANDOM CLASSIC	PILLAR CLASSIC
Bundle Type	RANDOM	SINGLE
Plant Produced	OHIO	OHIO
Thickness (mm)	100 MM	100 MM

FCFT PER	Bundle	29.92	48.24
	Layer	9.97	16.08
	Stone	0.50	0.67

PER BUNDLE	Layers	3.00	3.00
	Sections	-	-

LNFT PER	Bundle	89.06	96.00
	Unit	1.48	1.33

UNITS PER	SqFt	2.01	1.49
	Section	-	-
	Bundle	60.00	72.00

LBS PER	Layer	881	936
	Section	-	-
	Bundle	2,642	2,808

COLORS	Reflectance	Stock	Stock
Buff	SR n/a SRI n/a	-	-
Granite	SR n/a SRI n/a	✓	✓
Fieldstone NEW	SR n/a SRI n/a	✓	✓
Grey	SR n/a SRI n/a	-	-
Sierra	SR n/a SRI n/a	✓	✓

Random Bundle					Single Unit	
	LARGE RECTANGLE 500 X 100 X 200MM 19 3/4 X 3 7/8 X 7 7/8 15 Units/Bundle 55 Fc.Ft./Stone	RECTANGLE 400 X 100 X 200MM 15 3/4 X 3 7/8 X 7 7/8 15 Units/Bundle 44 Fc.Ft./Stone	SMALL RECTANGLE 300 X 100 X 200MM 11 7/8 X 3 7/8 X 7 7/8 15 Units/Bundle 33 Fc.Ft./Stone	XL RECTANGLE 600 X 100 X 200MM 23 5/8 X 3 7/8 X 7 7/8 15 Units/Bundle 66 Fc.Ft./Stone		CORNER/PILLAR 400 X 100 X 200MM 15 3/4 X 3 7/8 X 7 7/8 72 Units/Bundle .67 Sq.Ft./StoneE

Notes: Sold in full bundles only and is produced and sold on a required, refundable skid. Spacing strips are shipped with random wall bundles to create even spacing between units. LedgeStone™, Unilock Natural Stone or 6"x12" Fullnose complement as possible coping options. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Split
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	CORNER SPLIT	STANDARD SPLIT	TAPERED SPLIT	12" COPING SPLIT	XL WALL SPLIT
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	OHIO	OHIO	OHIO	OHIO
Thickness (mm)	150 MM	150 MM	150 MM	150 MM	150 MM

FCFT PER	Bundle	15.00	20.00	20.00	21.00	21.33
	Layer	5.00	6.67	6.67	3.00	5.33
	Stone	0.83	0.33	0.33	0.25	0.67

PER BUNDLE	Layers	15.00	20.00	20.00	7.00	4.00
	Sections	5.00	6.67	6.67	2.00	4.00

LNFT PER	Bundle	-	40.00	40.00	-	42.67
	Unit	-	0.67	0.67	-	1.33

UNITS PER	SqFt	1.20	3.00	3.00	4.00	1.50
	Section	6.00	30.00	30.00	42.00	8.00
	Bundle	18.00	60.00	60.00	84.00	32.00

LBS PER	Layer	314	857	768	388	617
	Section	314	1,285	1,153	1,357	617
	Bundle	943	2,570	2,305	2,714	2,467

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
Granite	SR n/a SRI n/a	✓	✓	✓	✓	✓
River	SR n/a SRI n/a	✓	✓	✓	✓	✓
Sierra	SR n/a SRI n/a	✓	✓	✓	✓	✓

Single Unit	CORNER 200 X 150 X 300MM 7 7/8 X 5 7/8 X 11 7/8" 18 Units/Bundle .83 Fc.Ft./Stone	STANDARD 200 X 75 X 300MM 7 7/8 X 5 7/8 X 11 7/8" 60 Units/Bundle .33 Fc.Ft./Stone	TAPERED 300 X 75 X 300MM 7 7/8 X 5 7/8 X 11 7/8" 60 Units/Bundle .33 Fc.Ft./Stone	XL WALL 400 X 150 X 300MM 15 3/4 X 5 7/8 X 11 7/8" 32 Units/Bundle .67 Fc.Ft./Stone	COPING 400 X 150 X 300MM 11 7/8 X 3 X 11 7/8" 84 Units/Bundle .25 Fc.Ft./Stone
-------------	---	--	---	---	--

Notes: XL Wall units are single units and are sold in full bundles only. When purchased by the full bundle, 12" Coping bundle has 14 units of closed-end coping (7 left and 7 right). Closed-end 12" coping not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. The set back on Pisa2 wall is 3/4" every course or 1 1/2" every 2 courses. Retaining wall engineering software is also available free of charge at www.unilock.com. Walls greater than 4' in height require professional engineering. Tapered Units allow for a minimum 5' Radius. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS

APPEARANCE

Edge Detail - n/a
Surface Texture - Split

CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	CORNER	XL TAPERED	COPING & CLOSED-END COPING
Bundle Type	SINGLE	SINGLE	MULTI COMPONENT
Plant Produced	OHIO	OHIO	OHIO
Thickness (mm)	150 MM	150 MM	75 MM

FCFT PER	Bundle	46.52	20.67	15.50
	Layer	11.63	5.17	1.94
	Stone	0.97	0.65	0.32





PER BUNDLE	Layers	4.00	4.00	8.00
	Sections	3.00	4.00	-

LNFT PER	Bundle	-	-	62.99
	Unit	-	-	1.31

UNITS PER	SqFt	1.03	1.55	3.10
	Section	16.00	8.00	-
	Bundle	48.00	32.00	48.00

LBS PER	Layer	629	617	388
	Section	839	617	-
	Bundle	2,516	2,467	3,101

COLORS	Reflectance	Stock	Stock	Stock
Fieldstone	SR n/a SRI n/a	✓	✓	✓
Granite	SR n/a SRI n/a	✓	✓	✓

Single Units			Multi Component Units		
	CORNER 400 X 150 X 200MM 15 3/4 X 5 7/8 X 7 7/8" 48 Units/Bundle 0.97 Fc.Ft./Stone	XL TAPERED 400 X 150 X 300MM 15 3/4 X 5 7/8 X 11 7/8" 32 Units/Bundle 0.65 Fc.Ft./Stone		COPING 400 X 75 X 300MM 15 3/4 X 3 X 11 7/8" 24 Units/Bundle 0.32 Fc.Ft./Stone	COPING - CLOSED-END 400 X 75 X 300MM 15 3/4 X 3 X 11 7/8" 24 Units/Bundle 0.32 Fc.Ft./Stone

Notes: * Special Order - Lead time is required, minimum quantities apply. All Special Order items are sold in full bundles only. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Split

Joint Spacing - n/a

Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	CORNER SPLIT	STANDARD SPLIT	TAPERED SPLIT
Bundle Type	RANDOM	RANDOM	SINGLE
Plant Produced	OHIO	OHIO	OHIO
Thickness (mm)	100 MM	100 MM	100 MM

FCFT PER	Bundle	20.00	19.98	19.98
	Layer	6.67	6.66	6.66
	Stone	0.83	0.33	0.33




PER BUNDLE	Layers	3.00	3.00	3.00
	Sections	2.00	2.00	2.00

LNFT PER	Bundle	-	40.00	39.99
	Unit	-	0.67	0.67

UNITS PER	SqFt	1.20	3.00	3.00
	Section	12.00	30.00	30.00
	Bundle	24.00	60.00	60.00

LBS PER	Layer	343	857	750
	Section	514	1,285	1,126
	Bundle	1,028	2,570	2,251

COLORS	Reflectance	Stock	Stock	Stock
Granite	SR n/a SRI n/a	✓	✓	✓
River	SR n/a SRI n/a	✓	✓	✓
Sierra	SR n/a SRI n/a	✓	✓	✓

Single Units		CORNER SPLIT 200 X 150 X 300MM 7 7/8 X 5 7/8 X 11 7/8 24 Units/Bundle .83 Fc.Ft./Stone		STANDARD SPLIT 200 X 150 X 300MM 7 7/8 X 5 7/8 X 11 7/8 60 Units/Bundle .33 Fc.Ft./Stone		TAPERED SPLIT 200 X 150 X 300MM 7 7/8 X 5 7/8 X 11 7/8 60 Units/Bundle .33 Fc.Ft./Stone

Notes: Maximum height - 48" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. All measurements are nominal. Corners are sold as double units (one left and one right). Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. Contact your local Unilock representative for details. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: **contractor.unilock.com**

APPEARANCE

Edge Detail - n/a
Surface Texture - Split
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	CORNER SPLIT
Bundle Type	RANDOM
Plant Produced	OHIO
Thickness (mm)	100 MM

FCFT PER	Bundle	31.00
	Layer	5.17
	Stone	0.22

PER BUNDLE	Layers	6.00
	Sections	-

LNFT PER	Bundle	-
	Unit	-

UNITS PER	SqFt	4.65
	Section	-
	Bundle	144.00

LBS PER	Layer	393
	Section	-
	Bundle	2,357

COLORS	Reflectance	Stock
Granite	SR n/a SRI n/a	✓
River	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

Single Unit



COPING TAPERED SPLIT
200 X 100 X 200MM
7 7/8 X 3 3/8 X 7 7/8
144 Units/Bundle
.22 Fc.Ft./Stone

Notes: Maximum height - 20" (under optimum conditions) including materials below grade. Radius - minimum outside radius 29.5". All measurements are nominal.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Smooth
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	STANDARD SMOOTH	COPING SMOOTH
Bundle Type	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO
Thickness (mm)	180 MM	180 MM

FCFT PER	Bundle	23.25	23.25
	Layer	7.75	7.75
	Stone	1.94	1.94

PER BUNDLE	Layers	3.00	3.00
	Sections	3.00	-

LNFT PER	Bundle	39.37	-
	Unit	3.28	-

UNITS PER	SqFt	0.52	0.52
	Section	4.00	-
	Bundle	12.00	12.00

LBS PER	Layer	1,029	1,029
	Section	1,029	-
	Bundle	3,086	3,086

COLORS	Reflectance	Stock	Stock
Granite	SR n/a SRI n/a	✓	✓

Single Unit



STANDARD CORNER
1000 X 180 X 290MM
39 3/8 X 7 X 11 1/2"
12 Units/Bundle
1.94 Fc.Ft./Stone



COPING
1000 X 180 X 290MM
39 3/8 X 7 X 11 1/2"
12 Units/Bundle
1.94 Fc.Ft./Stone

Notes: All Special Order items are sold in full bundles only. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Split

CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	CORNER SPLIT	STANDARD 333 SPLIT	STANDARD 500 SPLIT	STANDARD 925 SPLIT	COPING SPLIT	COPING C-E SPLIT 48"
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	OHIO	OHIO	OHIO	OHIO	GORMLEY
Thickness (mm)	185 MM	185 MM	185 MM	185 MM	185 MM	185 MM

FCFT PER	Bundle	17.19	18.00	12.00	6.00	12.00	14.43
	Layer	5.73	6.00	4.00	2.00	4.00	4.81
	Stone	2.87	2.00	2.00	2.00	2.00	2.41







PER BUNDLE	Layers	3.00	3.00	3.00	3.00	3.00	3.00
	Sections	3.00	-	3.00	3.00	3.00	3.00

LNFT PER	Bundle	-	-	19.50	9.75	-	-
	Unit	-	-	3.25	3.25	-	-

UNITS PER	SqFt	0.35	0.50	0.50	0.50	0.50	0.42
	Section	2.00	-	2.00	1.00	2.00	2.00
	Bundle	6.00	9.00	6.00	3.00	6.00	6.00

LBS PER	Layer	834	864	878	942	954	1,140
	Section	834	-	878	942	954	1,140
	Bundle	2,502	2,592	2,635	2,827	2,863	3,420

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Granite	SR n/a SRI n/a	SO	SO	SO	SO	SO	✓
Natural	SR n/a SRI n/a	SO	SO	✓	SO	✓	✓

Single Units						
	CORNER SPLIT 90° 925 X 185 X 500MM 36 1/2 X 7 3/8 X 19 3/4" 6 UNITS/BUNDLE 2.87 FC.FT./STONE	STANDARD 333 SPLIT 1000 X 185 X 500MM 39 3/8 X 7 3/8 X 13" 6 UNITS/BUNDLE 2.00 FC.FT./STONE	STANDARD 500 SPLIT 1000 X 185 X 500MM 39 3/8 X 7 3/8 X 19 3/4" 6 UNITS/BUNDLE 2.00 FC.FT./STONE	STANDARD 925 SPLIT 1000 X 185 X 925MM 39 3/8 X 7 3/8 X 36 1/2" 3 UNITS/BUNDLE 2.00 FC.FT./STONE	COPING SPLIT 1000 X 185 X 500MM 39 3/8 X 7 3/8 X 19 3/4" 6 UNITS/BUNDLE 2.00 FC.FT./STONE	COPING C-E SPLIT 48" 1200 X 185 X 500MM 47 1/4 X 7 3/8 X 19 3/4" 6 UNITS/BUNDLE 2.41 FC.FT./STONE

Notes: * Special Order - Lead time is required, minimum quantities apply. All Special Order items are sold in full bundles only. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Split

Joint Spacing - n/a

Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	TAPERED COPING SPLIT
Bundle Type	RANDOM
Plant Produced	OHIO
Thickness (mm)	100 MM

FCFT PER	Bundle	32.30
	Layer	6.46
	Stone	0.22

PER BUNDLE	Layers	5.00
	Sections	25.00

LNFT PER	Bundle	87.50
	Unit	0.58

UNITS PER	SqFt	4.64
	Section	6.00
	Bundle	150.00

LBS PER	Layer	522
	Section	104
	Bundle	2,611

COLORS	Reflectance	Stock
Granite	SR n/a SRI n/a	✓
River	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

Single Units



TAPERED COPING SPLIT

200 X 100 X 200MM

7 7/8 X 3 7/8 X 7 7/8"

150 UNITS/BUNDLE


.22 FC.FT./STONE

Notes: Maximum height - 20" (under optimum conditions) including material below grade. Radius - minimum outside radius 29". All measurements are nominal.

U-Cara® Multi-Face Wall System



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth, Standard, Series
Exposed, Umbriano® Mottled & Pitched

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color


COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits



U-Cara® Multi-Face Wall System

	Standard Fascia Smooth	Standard Closed-End Smooth	Standard Closed-End Umbriano	Standard Fascia Umbriano	3" Fascia Panel Series	Standard Fascia Pitched	Standard Closed-End Pitched
Bundle Type	SINGLE	SINGLE	SINGLE	SINGE	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	OHIO	ONTARIO	ONTARIO	CHICAGO	OHIO	OHIO
Thickness (mm)	150 MM	150 MM	150 MM	150 MM	71MM	150 MM	150 MM

FCFT PER	Bundle	61.52	54.18	54.18	61.52	59.32	61.52	54.18
	Layer	10.25	9.03	9.03	10.25	9.89	10.25	9.03
	Section	-	-	-	-	-	-	-
	Stone	0.73	1.29	1.29	0.73	0.18	0.73	1.29

PER BUNDLE	Layers	6.00	-	6.00	6.00	6.00	-	-
	Sections	-	-	-	-	-	-	-

LNFT PER	Bundle	129.50	104.86	107.94	-	-	129.50	104.86
	Unit	1.54	2.50	2.57	-	-	1.54	2.50

UNITS PER	SqFt	1.37	0.78	0.78	1.37	5.66	1.37	0.78
	Section	-	-	-	-	-	-	-
	Bundle	84.00	42.00	42.00	84.00	336.00	84.00	42.00

LBS PER	Layer	275	207	207	252	250	302	236
	Section	-	-	-	-	-	-	-
	Bundle	1,648	1,242	1,240	1,513	1,501	1,809	1,416

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock	Stock
Granite Fusion	SR n/a SRI n/a	✓	✓	-	-	-	✓	✓
Dark Charcoal	SR n/a SRI n/a	✓	✓	-	-	-		
Fossil	SR n/a SRI n/a	✓	✓	-	-	-	✓	✓
Onyx Black	SR n/a SRI n/a	-	-	-	-	✓	-	-
French Grey	SR n/a SRI n/a	-	-	✓	✓	-	-	-
Midnight Sky	SR n/a SRI n/a	-	-	✓	✓	-	-	-
Summer Wheat	SR n/a SRI n/a	-	-	✓	✓	-	-	-
Winter Marvel	SR n/a SRI n/a	-	-	✓	✓	-	-	-


Fascia Panels		6" STANDARD FASCIA PANEL 5 7/8 x 18 3/8 x 2 3/8" 150 x 466 x 60mm 84 Units/Bundle .73 Sq.Ft./Stone		3" FASCIA PANEL 2 7/8 x 9 x 2 3/8" 71 x 231 x 60mm 336 Units/Bundle .18 Sq.Ft./Stone
2 Unit Corner		STANDARD FASCIA HALF PANEL 5 7/8 x 9 1/4 x 2 3/8" 150 x 233 x 60mm 42 Units/Bundle .37 Sq.Ft./Stone		CLOSED-END FASCIA PANEL 5 7/8 x 20 7/8 x 2 3/8" 150 x 530 x 60mm 42 Units/Bundle 1.29 Sq.Ft./Stone

Notes: Sold in full bundles. Produced and sold on a required refundable skids. Sure Track Large Backer Units when used as corners in a pillar application, can achieve 42 FFT/bundle or .757 FFT/unit.

U-Cara® Multi-Face Wall System



APPLICATIONS



CROSS SECTIONS

All Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth,
Standard, Series Exposed,
Umbriano® Mottled & Pitched

TECHNOLOGIES

ENDURACOLOR™

Refined surface
and long-lasting color

COLORFUSION™


Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1
credits

U-CARA RETAINING WALL GEOGRID SECTION




Download the U-Cara Multi-Face
Wall Installation Guide.

U-CARA® CROSS SECTION

REF: Detail_U-Cara_Garden_Wall

Garden Wall - Max Height 15"




Notes:
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

U-CARA® CROSS SECTION

REF: Detail_U-Cara_Seal_Wall

Seal Wall - Max Height 21"



Notes:
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

U-Cara® Multi-Face Wall System

Components



**SURE TRACK
CORNER BACKER**
5 7/8" X 6 7/8" X 11 5/8"
150 X 175 X 294MM



**SURE TRACK
STANDARD BACKER**
5 7/8" X 7 7/8" X 5 7/8"
150 X 200 X 150MM

		LARGE/CORNER/ PILLAR BACKER	STANDARD BACKER	UNIVERSAL BASE CLASSIC
Bundle Type		SINGLE	SINGLE	SINGLE
Plant Produced		OHIO	OHIO	OHIO
Thickness (mm)		150 MM	150 MM	55MM
FCFT PER	Bundle	15.82	33.91	-
	Layer	3.96	11.30	-
	Stone	0.28	0.32	-
PER BUNDLE	Layers	4.00	3.00	10.00
	Sections	-	-	-
LNFT PER	Bundle	-	69.99	70.00
	Unit	-	0.67	1.17
UNITS PER	SqFt	3.54	3.10	-
	Section	-	-	-
	Bundle	56.00	105.00	60.00
LBS PER	Layer	498	773	282
	Section	-	-	-
	Bundle	1,992	2,320	2,816

Recommended Base Unit



UNIVERSAL BASE UNIT
14 X 19 X 2 1/4"
355 X 482 X 55MM

Extra Components




**SURE TRACK
CORNER INSERT**
L = 2"
50MM

Notes: Sold in full bundles. Produced and sold on a required refundable skids. Sure Track Large Backer Units when used as corners in a pillar application, can achieve 42 FFT/bundle or .757 FFT/unit.

U-Cara® Modular System

The U-Cara Modular System offers a variety of aluminum frames that can be mixed and matched to construct vertical features like grill islands. Speak to your contractor to select a design and a U-Cara fascia panel finish to suit your project.

With the U-Cara Modular System you can build Grill Islands, Bars, Back splashes, Fire Places and Pillars.




Download the U-Cara Modular Fireplace Installation Guide.



NO.	MODEL	DESCRIPTION
RS-UCARA000001	URS	UCARA 8" RAIL (10/PACK)
RS-UCARA000002	URS	ALIGNMENT BARS 39" (10/PACK)
RS-UCARA000005	UL-HCK	U-CARA HEIGHT CONVERSION
RS-UCARA000006	UL-HCK-OS	U-CARA HEIGHT CONVERSION KIT-OS
RS-UCARA000009	UL-FIR	U-CARA FIREPLACE
RS-UCARA000010	UL-FIR-M	U-CARA FIREPLACE MANTLE
RS-UCARA000014	UL-HCK-CC-OS	U-CARA HEIGHT CONV CORNER CAB
RS-UCARA000015	UL-HCK-CC	U-CARA HEIGHT CONVERSION CORNER CAB
RS-UCARA000016	UL-FIR-MW	U-CARA FIREPLACE MANTLE WIDE UNIT
RS-UCARA000017	UL-FIR-CH	U-CARA U-CARA FIREPLACE CHIMNEY UNIT
RS-UCARA000018	UL-FIR-CH-MW	U-CARA FIREPLACE CHIMNEY WIDE UNIT
RS-UCARA000019	UL-FIR-RTN	U-CARA FIREPLACE RETURN
RS-UCARA000020	UL-FIR-RTN-OS	U-CARA FIREPLACE RETURN OVERSIZED

NO.	MODEL	DESCRIPTION
RS-UCARA001000	UL-GC	UNIVERSAL GRILL CABINET
RS-UCARA002000	UL-BC	BASE CABINET
RS-UCARA003000	UL-CC	CORNER CABINET 27.5" X 27.5"
RS-UCARA003001	UL-CCOS	CORNER CABINET 27.5" X 36.5"
RS-UCARA003002	UL-CCBP	CORNER CABINET PANEL
RS-UCARA004000	UL-ECK	END CLAD KIT 27.5"
RS-UCARA004001	UL-ECKOS	END CLAD KIT 36.5"
RS-UCARA005000	UL-BS	BACKSPLASH GRILL/BASE UNIT 64.5"
RS-UCARA005001	UL-BSCC	BACKSPLASH CORNER CABINET
RS-UCARA005002	UL-BSCCOS	BACKSPLASH CORNER CABINET OS
RS-UCARA006000	UL-DD	UCS STNLS DBL ACCESS DOORS 27"
RS-UCARA007000	UL-PU	PILLAR UNIT

U-Cara® Wall Mount System



The U-Cara Wall Mount System allows you to put the finishing touches on your project by cladding existing structures like unsightly exposed foundation areas or concrete steps with U-Cara fascia panels.



U-CARA ALIGNMENT BAR:
39" LENGTH - SOLD IN PACKS OF 10 PIECES

U-CARA RAILS:
8' LENGTH - SOLD IN PACKS OF 10 PIECES



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Exposed
Joint Spacing - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

	COPING ENDURACOLOR	PILLAR CAP 28" ENDURACOLOR
Bundle Type	SINGLE	SINGLE
Plant Produced		
Thickness (mm)	60 MM	76MM

SQFT PER	Bundle	-	-
	Unit	-	-

FCFT PER	Bundle	-	-
	Layer	-	-
	Unit	-	-

LNFT PER	Bundle	42.00	-
	Unit	2.00	-

UNITS PER	Bundle	21.00	6.00
	SqFt	-	-

LBS PER	Unit	68	183
	Bundle	1,428	1,098

COLORS	Reflectance	Stock	Stock
Buff	SR n/a SRI n/a	✓	✓
Charcoal	SR n/a SRI n/a	✓	✓

Single Units



COPING
609 X 60 X 355MM
24 X 2 3/8 X 14"



PILLAR CAP
711 X 76 X 711MM
28 X 3 X 28"

Notes: Shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 2mm

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

	FULLNOSE SMOOTH	DOUBLE FULLNOSE SMOOTH
Bundle Type	SINGLE	SINGLE
Plant Produced	OHIO	OHIO
Thickness (mm)	70 MM	70 MM

FCFT PER	Bundle	-	-
	Layer	-	-
	Stone	-	-

PER BUNDLE	Layers	8.00	8.00
	Sections	4.00	4.00

LNFT PER	Bundle	80.00	80.00
	Unit	0.50	0.50

UNITS PER	SqFt	-	-
	Section	40.00	40.00
	Bundle	160.00	160.00

LBS PER	Layer	297	297
	Section	594	594
	Bundle	2,376	2,376

COLORS	Reflectance	Stock	Stock
Dark Charcoal	SR .12 SRI 9	✓	✓
Limestone	SR .41 SRI 46	✓	✓
Sandstone	SR .41 SRI 46	✓	✓
Sierra	SR n/a SRI n/a	✓	✓

Single Units



**BRUSSELS FULLNOSE
CLASSIC / TUMBLED**
150 X 300 X 70MM
5 7/8 X 11 7/8 X 2 3/4"
160 Units/Bundle



**BRUSSELS DOUBLE FULLNOSE
CLASSIC / TUMBLED**
150 X 300 X 70MM
5 7/8 X 11 7/8 X 2 3/4"
160 Units/Bundle



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured

TECHNOLOGIES

REALA™
Cast from natural stone

TECHNICAL INFORMATION

Conforms to ASTM C 1776
Eligible for LEED v4.1 credits

	24" COPING	24" CLOSED-END COPING	24" FULLNOSE COPING	30" COPING	30" CLOSED-END COPING
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	70 MM	70 MM	70 MM	70 MM	70 MM

FCFT PER	Bundle	5.52	5.52	5.12	6.87	6.87
	Layer	1.38	1.38	0.39	1.72	1.72
	Stone	0.46	0.46	0.39	0.57	0.57

PER BUNDLE	Layers	-	-	-	-	-
	Sections	-	-	-	-	-

LNFT PER	Bundle	24.00	24.00	26.00	30.00	30.00
	Unit	-	-	-	-	-

UNITS PER	SqFt	2.18	2.18	2.54	1.75	1.75
	Section	-	-	-	-	-
	Bundle	12.00	12.00	13.00	12.00	12.00

LBS PER	Layer	-	-	-	-	-
	Section	-	-	-	-	-
	Bundle	722	796	723	1,128	1,116

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
Buff	SR n/a SRI n/a	✓	✓	✓	✓	✓
Grey	SR n/a SRI n/a	✓	✓	✓	✓	✓

Single Units					
	24" COPING 610 X 305 X 60MM 24 X 12 X 2 3/8" 12 Units/Bundle .46 Fc.Ft./Stone	24" CLOSED-END COPING 610 X 305 X 70MM 24 X 12 X 2 3/4" 12 Units/Bundle .46 Fc.Ft./Stone	24" FULLNOSE COPING 610 X 305 X 60MM 24 X 12 X 2 3/8" 13 Units/Bundle .46 Fc.Ft./Stone	LARGE (30") COPING 762 X 343 X 70MM 30 X 13 1/2 X 2 3/4" 12 Units/Bundle .57 Fc.Ft./Stone	LARGE (30") CLOSED-END COPING 762 X 343 X 70MM 30 X 13 1/2 X 2 3/4" 12 Units/Bundle .57 Fc.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Coping is rock faced on the front and the back. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Textured

TECHNOLOGIES

REALA™

Cast from historic street pavers

TECHNICAL INFORMATION

Conforms to ASTM C 1776

Eligible for LEED v4.1 credits

	48" STEP	24" PILLAR CAP	29" PILLAR CAP
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	CHICAGO	CHICAGO
Thickness (mm)	150 MM	100 MM	100 MM

FCFT PER	Bundle	5.91	3.28	-
	Layer	1.97	0.66	-
	Stone	1.97	0.66	-

PER BUNDLE	Layers	3.00	5.00	5.00
	Sections	-	-	-

LNFT PER	Bundle	12.00	10.04	-
	Unit	4.00	2.01	-

UNITS PER	SqFt	0.51	1.52	-
	Section	-	-	-
	Bundle	3.00	5.00	5.00

LBS PER	Layer	574	159	206
	Section	-	-	-
	Bundle	1,721	795	1,030

COLORS	Reflectance	Stock	Stock	Stock
Buff	SR n/a SRI n/a	✓	✓	✓
Grey	SR n/a SRI n/a	✓	✓	✓

Single Units



48" STEP
1220 X 610 X 150MM
48 X 24 X 5 7/8"
3 Units/Bundle
1.97 Fc.Ft./Stone



24" PILLAR CAP
610 X 610 X 100MM
24 X 24 X 3 7/8"
5 Units/Bundle
.66 Fc.Ft./Stone



29" PILLAR CAP NEW
740 x 740 x 100mm
29 1/8 x 29 1/8 x 3 7/8"
5 units/Bundle
.66 Fc.Ft./Stone

Notes: Produced and sold on a required, refundable skid. Coping is rock faced on the front and the back. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Split

CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	COPING SPLIT	COPING C-E SPLIT
Bundle Type	SINGLE	SINGLE
Plant Produced	OHIO	ONTARIO
Thickness (mm)	185 MM	185 MM

FCFT PER	Bundle	12.00	14.43
	Layer	4.00	4.81
	Stone	2.00	2.41

PER BUNDLE	Layers	3.00	3.00
	Sections	3.00	3.00

LNFT PER	Bundle	-	-
	Unit	-	-

UNITS PER	SqFt	0.50	0.42
	Section	2.00	2.00
	Bundle	6.00	6.00

LBS PER	Layer	954	1,140
	Section	954	1,140
	Bundle	2,863	3,420

COLORS	Reflectance	Stock	Stock
Granite	SR n/a SRI n/a		✓
Natural	SR n/a SRI n/a	✓	✓

Single Units



COPING SPLIT
1000 X 185 X 500MM
39 3/8 X 7 3/8 X 19 3/4"
6 Units/Bundle
2.00 Fc.Ft./Stone




COPING SPLIT
1200 X 185 X 500MM
47 1/4 X 7 3/8 X 19 3/4"
6 Units/Bundle
2.41 Fc.Ft./Stone

Notes: Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Umbriano Mottled
 Joint Spacing - 7mm
 Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	COPING MOTTLED	BULLNOSE COPING MOTTLED
Bundle Type	SINGLE	SINGLE
Plant Produced	PICKERING	PICKERING
Thickness (mm)	60 MM	60 MM

FCFT PER	Bundle	-	-
	Layer	-	-
	Stone	-	-

PER BUNDLE	Layers	6.00	6.00
	Sections	2.00	2.00

LNFT PER	Bundle	47.24	47.24
	Unit	1.97	1.97

UNITS PER	SqFt	12.00	12.00
	Section	-	-
	Bundle	24.00	24.00

LBS PER	Layer	252	252
	Section	755	755
	Bundle	1,510	1,510

COLORS	Reflectance	Stock	Stock
French Grey	SR n/a SRI n/a	✓	✓
Grenada White	SR n/a SRI n/a	✓	✓
Midnight Sky	SR n/a SRI n/a	✓	✓
Summer Wheat	SR n/a SRI n/a	✓	✓
Winter Marvel	SR n/a SRI n/a	✓	✓

Single Units



**UMBRIANO MOTTLED
COPING**
 600 X 60 X 355MM
 23 5/8 X 2 3/8 X 14"



**UMBRIANO MOTTLED
BULLNOSE COPING**
 600 X 60 X 355MM
 23 5/8 X 2 3/8 X 14"



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Standard / Smooth

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	UNIVERSAL COPING SMOOTH ENDURACOLOR
Bundle Type	SINGLE
Plant Produced	OHIO
Thickness (mm)	70 MM

FCFT PER	Bundle	13.08
	Layer	2.18
	Stone	0.36

PER BUNDLE	Layers	6.00
	Sections	-

LNFT PER	Bundle	-
	Unit	-

UNITS PER	SqFt	2.75
	Section	-
	Bundle	36.00

LBS PER	Layer	353
	Section	-
	Bundle	2,118

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓

Single Units



**UNIVERSAL COPING
ENDURACOLOR**
482 X 355 X 70MM
19 X 14 X 2 ¾"
36 Units/Bundle
.36 Fc.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.

Sunset Fire Pit Kit

CLASSIC



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Standard
Joint Spacing - n/a
Void % - n/a

TECHNOLOGIES

CLASSIC™
Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	SQUARE W / INSERT	ROUND W / INSERT
Bundle Type	SINGLE	SINGLE
Plant Produced		
Thickness (mm)	300 MM	300 MM

DIAMETER (inch)	Outside	44.00	52.00
	Inside	28.00	34.00
	Insert	36.00	34.00

LAYER PER UNIT	3.00	3.00
UNIT PER LAYER	12.00	18.00
UNIT PER PALLET	36.00	54.00

LBS PER PALLET	1,545	1,145
----------------	-------	-------

COLORS	Reflectance	Stock	Stock
Limestone	SR n/a SRI n/a	✓	✓
River	SR n/a SRI n/a	✓	✓
Sandstone	SR n/a SRI n/a	✓	✓
Sierra	SR n/a SRI n/a	✓	✓

Single Unit



SUNSET SQUARE W/INSERT
1100 X 1100 X 300MM
43 3/8 X 43 3/8 X 11 7/8"



SUNSET ROUND W/INSERT
1300 X 1300 X 300MM
51 1/4 X 51 1/4 X 11 7/8"

Notes: All measurements are nominal. Contact Unilock for more information.

Unilock Elements

TUSCANY

Large decorative accents adorn the top of the Tuscany fireplace. Brussels Fullnose™ is used to construct the ledges and mantle of the fireplace.



Tuscany Sierra with Copthorne® **



MODA SPECIAL ORDER

The Moda pre-built fireplace is constructed from Lineo™ Dimensional Stone and Series™ accent.



Moda (Lineo Dimensional Stone & Series)
SPECIAL ORDER

TUSCANY FIREPLACE



CUSTOM ACCENTS



Copthorne®

Courtstone®



Richcliff®

Umbriano®

UNILOCK ELEMENTS ARE AVAILABLE IN TUSCANY AND BARCELONA SERIES



FIREPLACE

Two piece set (base and chimney), and it comes with stainless fire box. 5,620 lbs



HEARTH

Hearth with gentle curved front. 1,025 lbs



WOOD BOXES

Sold as a set of two and flank either side of the gas or standard fireplace. 3,750 lbs per set



GRILL ISLAND

Available with OCS Grill, protective cover, and stainless double door insert. 3,800 lbs

Guarantee: The standard Unilock guarantee applies to the units used to construct Unilock Elements. (See Unilock literature for details.) Third party grills and fireboxes carry their respective manufacturer's warranty and may change without notice.

Note: Unilock reserves the right to change model designs, accessories and colors without notice. Unilock will not be responsible for improper use or handling that results in property damage. Some models may not be exactly as shown. Fireplaces come complete with UL- approved stainless steel fireboxes. Check local building codes and regulations prior to ordering and installing Unilock Elements.

Paver Cleaners



ALLIANCE GATOR OIL & GREASE CLEANER

- Effective in removing oil and grease from the surface of concrete pavers and natural stones
- Easy to use - dissolves, dislodges and removes oil and grease



ALLIANCE GATOR EFFLORESCENCE CLEANER & SLURRY REMOVER

- Removes any efflorescence stains trapped in the concrete paver and natural stone pores
- Makes the pavers look more clean and vibrant



ALLIANCE GATOR RUST CLEANER

- Effective in removing rust from the surface of concrete pavers
- Contains no muriatic acid



ALLIANCE GATOR RUBBER, PAINT & TAR REMOVER

- Effective in removing rubber, paint and tar from the surface of concrete pavers and natural stone
- Easily washes off with water and is easy to use

Natural Stone Cleaners



UNICARE NATURAL STONE ACID CLEAN

1L and 5L

Removal of:

- Cement Staining
- Efflorescence
- Iron Oxide (Rust) Cement mortar
- Grout



UNICARE NATURAL POWER CLEAN

1L and 5L

Removal of:

- Oil & Grease
- Food Stains
- General Dirt & Mud
- Sap & certain plant stains
- Light cement contamination (on acid sensitive surfaces)



UNICARE BIOCLEAN

1L and 5L

Removal of:

- Black spot algae
- Green algae
- Plant stains from leaves, wood, trees, berries & flowers
- Organic staining from bark & compost
- Colored stains from food spillages, tea, coffee and wine

Natural Stone Sealers



UNICARE NATURAL STONE NATMATTE SEALER

1L and 5L

For Porous Stones

- No change of color
- No surface coating, sheen or shine at all
- Riven Sandstone & Smooth Sandstone



UNICARE NATURAL STONE NATCOLORENHANCE SEALER

1L and 5L

Color Enhancement For Porous Stones

- No surface coating, sheen or shine
- Breathable
- Lasts several years
- Easy to apply

Sealers



ALLIANCE GATOR WET LOOK SEALER

- Made from acrylic-based polymers
- Penetrates deep into concrete paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion



ALLIANCE GATOR SATIN LOOK SEALER

- Made from acrylic-based polymers
- Penetrates deep into concrete paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion
- Low-gloss matte finish, solvent-based



ALLIANCE GATOR ECO SEAL HIGH GLOSS

- 100% pure, high-grade acrylic used to seal concrete pavers, clay pavers and natural stone
- Penetrates deep into paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion



ALLIANCE GATOR ECO SEAL LOW GLOSS

- 100% pure, high-grade acrylic used to seal concrete pavers, clay pavers and natural stone
- Penetrates deep into paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion



SUREBOND 1300 JOINT SAND STABILIZING SEALER - MATTE FINISH

- Seals surface & hardens joint sand, while protecting the sealer film from mold, moss & algae
- Reduces sand washout, weeds & insect infestation
- Locks in a clean, natural look & matte finish.
- Product is breathable, designed for immediate application and is water-based; moisture or efflorescence will not get trapped
- Approximate Coverage: 80-120 sq.ft

Sealers continued



SUREBOND 7700 JOINT STABILIZING SEALER - GLOSS FINISH WITH ANTIFUNGAL PROTECTION

- Seals the surface and bonds joint sand between interlocking concrete pavers
- Protects colored, stained and exposed aggregate concrete from staining
- Resists acid, salt, other corrosives and weathering
- Stabilizing sealer, water-based, single component and epoxy-modified; exceeds all VOC and EPA standards
- Non-hazardous with the consistency of water; milky white in appearance when applied, dries crystal clear creating a semi-gloss finish



SUREBOND 8700 WET LOOK JOINT SAND STABILIZER WITH FUNGICIDE

- An advanced premium acrylic sealer that will not yellow under exposure to sunlight
- A 2 in 1 product; protects the substrate surface and stabilizes jointing sand at the same time
- Specially formulated with antifungal agents designed to help inhibit the growth of mold, fungi and moss on horizontal pavement surfaces
- Forms a tenacious bond to the concrete or masonry surface.
- Wet look, rain safe in 90 minutes, water-repellant, breathable, solvent-based.

Adhesives



UNILOCK SB-10 ADHESIVE

- 10 oz - ADH009-1 / 28 oz RS-ADH015-1
- 10 oz. Tube: 20' at 1/4" bead (12/Case)(140 cs/skid)
- 28 oz. Tube: 52' at 1/4" bead (12/Case)(60 cs/skid)
- SPECIFICATIONS - (Conforms to UN-STD. 1804, ASTM 2339-70& FHA UM-60)



ALLIANCE XP GATOR BLOCK ADHESIVE

RS-ADH039 10 oz; 12/case; 90 cases/skid (1080 ea)
RS-ADH040 28 oz; 12/case; 60 cases/skid (720 ea)

- Bonds permanently in 24 hours
- Material may be repositioned for up to 30 minutes
- Works in temperatures above 32°F
- 850 psi in 24 hrs (1000 psi in 7 days)

Sands



POLYBIND™ HP SAND

- Designed for paver joints up to a maximum of 1 inch
- Unique mixture of polymer binders and calibrated sand available in Nevada Tan & Oxford Grey
- Installation almost identical to using regular paver joint sand, except for the application of water; once set, it becomes very firm and locks between the paver joints, maintaining pavers securely in place
- Equally effective on both horizontal & sloped surfaces.
- **Packaging:** 50 lb bag 56 bags/skid
- **Coverage:** 65-85 sq.ft. per bag for narrow joints/larger joints require more sand



POLYBIND™ COMPLETE SAND

- Specifically designed for drainage and non-drainage base systems.
- Can be used with concrete pavers, wetcast and natural stones for a variety of uses including pool sides, patios, paths, driveways, parking spaces, etc.
- Available in three colors: Nevada, Tan & Oxford Grey
- Sets above the freezing temperature 32°F and can be used for joints up to a maximum of 1.5 in.
- **Packaging:** 50 lb bag 56 bags/skid
- **Coverage:** 65-85 sq.ft. per bag for narrow joints/larger joints require more sand



POLYBIND G2 SAND - NO DUST • HAZE FREE • NO BLOWER • ONE WATERING

- Made with calibrated sand that is mixed with sophisticated intelligent polymers, which neutralize haze and dust; application is now dust free and haze free.
- No blower needed and the intelligent polymeric sand requires only one watering
- Recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc.
- Available in Nevada and Oxford Grey and it sets above the freezing temperature 32°F and can be used for joints up to a maximum of 2 in.
- **Packaging:** 50 lb bag 56 bags/skid
- **Coverage:** 65-85 sq.ft. per bag for narrow joints/larger joints require more sand



POLYBIND G2 COMPLETE SAND - NO DUST • HAZE FREE • NO BLOWER • ONE WATERING

- Designed for paver joints up to maximum of 4"
- Drainage & non-drainage applications (overlays).
- No Dust - No Haze - No Blower - One Watering
- The cleanest, fastest and easiest polymeric sand installed in the industry
- Can be used with concrete pavers, wetcast & natural stones, and is recommended for use in patios, pool decks, walkways, driveways, etc.
- **Packaging:** 50 lb bag 56 bags/skid
- **Coverage:** 65-85 sq.ft./ bag for narrow joints/larger joints require more sand; 58-76 sq.ft./ bag for narrow joints/larger joints need more sand (Jet Black)



POLYBIND DUST

- Designed for natural stone joints 1/2" to 4"
- A unique mixture of polymer binders and calibrated crushed stone available in two colors - Tan & Grey
- Once set, becomes very firm and locks between the stone joints, maintaining a bond that holds the stones securely in place
- Equally effective on both horizontal and sloped surfaces
- **Packaging:** 50 lb bag 56 bags/skid
- **Coverage:** 20-30 sq.ft. per bag for joints 1"-2" wide and stones approximately 2" thick



ALLIANCE EUROSTONE BOND

- The first polymeric sand specifically designed for drainage and non-drainage base systems
- Can be used with natural stones and cobblestone
- Sets above the freezing temperature (0°C / 32°F) and can be used for joints up to a maximum of 35mm/ 1"
- **Packaging:** 50 lb bag 56 bags/skid
- Available in Slate Grey

Sands continued



ALLIANCE GATOR NITRO SAND

- Ready-to-use mixture of calibrated sand and resins which cure when exposed to air, harden from top to bottom of the joint
- Can be installed in wet or dry weather, in joints ranging from a minimum 3/16" (5mm) to a maximum 2" (50mm) joint width; minimum jointing depth is 1" (25mm).
- Packaging: 40 lb bucket • 48 buckets/skid
Available in Beige, Grey, Black & Silver
- **Coverage:** 10-56sf = 1 bucket depending on joint size



SEK POLYSWEEP POLYMERIC SAND

- Designed to keep sand in the joints by creating a semi-solid joint & available in Grey and Tan
- A blend of native sands conforming to ASTM C-144 and binders specially formulated to allow the joints to expand and contract with the elements (ie. heat, cold & freeze/thaw cycles)
- Prevents sand erosion from the pavement joints caused by rain and other water run-off, proven to produce less hazing
- Also deters weed growth and reduces overall pavement maintenance.
- Max width: 2.5cm (1"); a larger joint width is acceptable where pavers intersect. Min depth: 3cm (1.25")
- **Packaging:** 50 lb bag 56 bags / skid (2,860 lbs / skid)
- **Coverage:** Courtstone - 1 bag covers approx. 25sq.ft.

Note: Extra care must be exercised when using with Courtstone®, Copthorne®, Richcliff® & Town Hall®. This product is not recommended for use with Il Campo®, Series™ & Umbriano®.



SUREBOND JOINTING SAND

- Will properly complete the interlocking of segmental pavers because it is clean, angular and meets ASTM-C144 specifications
- More stable in the paver joints and has optimal gradation to ensure long term performance of the pavement system.
- Recommended for joints up to 3/4" • Washed, screened & dried • Available in Tan & Grey
- **Packaging:** 50 lb bag

SAND RECOMMENDATIONS BY PRODUCT

Sands	Polybind HP G2	Polybind Complete Sand G2	Polysweep Polymeric Sand	Unicare® Easy Pro®
PAVERS	For joints up to 1/8" May be sealed. Tan color Non-binding sand	For joints up to 1" May be sealed. Available in Tan or Grey Binding sand	For joints up to 4" May be sealed. Available in Tan or Grey Binding sand	For joints up to 1" May be sealed. Available in Tan or Black Binding sand
Copthorne®	✓	✓	✓*	✓
Courtstone®	✓	✓	✓	✓
Il Campo®	N/R	N/R	N/R	N/R
Richcliff®	✓	✓	✓*	✓
Senzo™	✓	✓	N/R	N/R
Series™	N/R	N/R	N/R	N/R
Town Hall®	✓	✓	✓	✓
Umbriano®	✓	✓	N/R	N/R
Tumbled Pavers	✓	✓	✓	N/R
Standard Pavers	✓	✓	✓	✓

N/R - Not Recommended

✓ Recommended

✓* These pavers have a very narrow or slightly angled edge (chamfer), limiting sand penetration in the joint and causing possible weak bonding areas. The life cycle performance could be affected.

IMPORTANT NOTICE

1. DO NOT USE Polymeric Jointing Sand on the following products: Series™ Il Campo®

If joint stabilization is required, use ordinary jointing sand and apply a stabilizing sealer. Contact your local Unilock office for recommended sealants and application specifics.

2. EXTRA CARE must be exercised when using Polymeric Sand on the following products:

Courtstone®

Copthorne®

Richcliff®

Town Hall®

Umbriano®

Polymeric Jointing Sand can be used on these products but the fine polymers and binders in Polymeric Jointing Sand have a natural tendency to adhere to the surface and therefore extra diligence must be taken to pre-clean the surface prior to "wetting the sand in" and squeegee off the surface post application. Failure to do so will result in a "whitish haze" on the surface that is difficult to remove.

3. IMPORTANT COMPACTION NOTICE: Always pre-compact the pavers WITHOUT SAND IN THE JOINTS. This will facilitate proper leveling. Polymeric sand can then be swept into the joints. Always use a compactor with a protective membrane attached to the bottom of the plate.

Polymeric Jointing Sand, cleaners and sealers, must always be applied by a trained and experienced professional. Contact your local Unilock office for training and the most up-to-date best practices.

NOTICE: Unilock does not accept any responsibility for damage to the surface caused by the improper application and use of polymeric sand, sealers or cleaners. Unilock will not accept responsibility for alternate suppliers of polymeric sand, jointing sand, cleaners and sealers.

Edging



PERMA EDGE PAVER EDGING

- Designed to float & flex with the sub base and not work independently like standard edging & spikes
- Quick & easy to install, typically cutting edging install time down by 80%
- Stays under the soil/mulch grade invisible edging
- Combats the freeze/thaw cycles in cold weather; won't deteriorate in moist/humid conditions
- **Coverage per container;** yields approx. 25-30 linear feet of edging per bucket
- **Packaging:** 75 lb container / 34 kg bucket 35 / skid



ALLIANCE GATOR XTREME EDGE

- The ultimate fiber-reinforced structural edging solution for any hardscape project.
- Can be used for any traditional, open-graded, permeable, Gator Base or overlay application using concrete pavers or slabs, natural and wet cast stones
- Offers permanent continuous lateral support
- **Packaging:** 50 lb bag / 56 bags per skid
- **Coverage:** 20-25 sqft coverage per bag for a 60mm paver

Edge Restraints continued

PERMEDGE PERMEABLE PAVER EDGING

RS-EDGE033

- Designed specifically for permeable pavement with open-graded base material
- Holds pavement edges securely in place
- Does straight and curved edges

Product Information:

8' (96") length pcs.
Weight per Unit: 2.5 lbs.
Pieces per Pallet: 64 (72 ln. ft.)
Freight Class: 300
Pallet Weight: 210 lbs.
Pallet Size: 98" l x 48"w x 50" h




Spikes

- 10" Round Spikes
- About 150 spikes per case
- **Sold in full cases only**

Edge Restraints

SNAPEDGE - ONE-PIECE EDGING THAT DOES IT ALL!

- Only one part required for straight runs or curved installations
- Built-in connector fastens one piece to the next - convenient 96" size, easy to transport
- Unique 'Snip and Flex' feature speeds installations of curves and corners without pre-planning
- The open design allows a root system to grow through SnapEdge, further reinforcing the installation
- Engineered to provide a strong, easy-to-install edge restraint for concrete/clay pavers
- Nail hole bosses are full-length cylinders. Hammer blows will not fracture or force nail heads through edging



Product Information:

8' (96") length pcs.
Sidewall: 1 7/8"
Pieces per Pallet: 672 (5,376 ln. ft.)
Pieces per Bundle: 24 (192 ln. ft.)
Bundles per Pallet: 28
Pallet Weight: 1395 lbs.
Pallet Size: 98" l x 48"w x 50" h




Product Information:

6'8" (80") length pcs.
Sidewall: 1 3/8"
Pieces per Pallet: 672 (5,376 ln. ft.)
Pieces per Bundle: 24 (192 ln. ft.)
Bundles per Pallet: 28
Pallet Weight: 1395 lbs.
Pallet Size: 98" l x 48"w x 50" h

X & T Slab Spacers


X & T SLAB SPACERS

- 250 per bag
- X & T bagged separately
- X spacers 2" x 2" (RS-ACC237)
- T spacers 2" x 1" (RS-ACC236)



Unilock recommends using slab spacers when installing Arcana on an open grade surface. "T" spacers are needed for running bond patterns, "X" spacers are needed for stack bond patterns. Please contact your sales manager for more information.

Drainage, Separation & Reinforcement



UNILOCK DRIVEGRID™ SYSTEM

- 120' x 13' Roll,
1,572 Sq.Ft./Roll
56 lbs/Roll



GATOR GRID 30-30

Gator Grid 30-30, a biaxial geogrid, provides strength, longevity, excellent stress transfer and prevents failure to the internal structure of landing areas, retaining walls and steep slopes. It has a high molecular weight as well as high-tenacity polyester yards which are woven in tension and finished with a PVC coating.

Packaging: • 4' x 50' / 16 rolls per box
• 6' x 50' / 20 rolls per pallet



GATOR FABRIC NON-WOVEN 3.5

Gator Fabric Non-Woven 3.5 geotextile is ideal for drainage, filtration and will allow water flow in a paver or retaining wall application. It is designed for soil separation for added stability, has high strength and is dimensionally stable.

Packaging: • 3' x 100' / 4 roll package
• 6' x 100' / 12 roll package



GATOR FABRIC WOVEN 5

Gator Fabric Woven 5 is a woven geotextile made from polypropylene yarns and can achieve higher tensile strength at low elongation. It is an excellent heavy-loading geotextile, ideal for driveways, alleyways, pathways and retaining walls.

Packaging: • 4' x 100' / 4 roll package
• 6.25' x 300' / 12 roll package



GATOR FABRIC POLYSPUN 20 **SPECIAL ORDER**

Gator Fabric Polyspun 20 geotextile is specially formulated to resist deterioration in garden and landscape applications. It creates a barrier to reduce weed growth and allows water, fertilizer and air to pass through.

Packaging: • 3' x 50' / 16 rolls per case / 64 rolls per skid
• 3' x 100' / 9 rolls per case / 36 rolls per skid
• 4' x 100' / 9 rolls per case / 36 rolls per skid
• 6' x 100' / 30 rolls per case / 36 rolls per skid

Base/Drainage Systems

GATOR TILE SYSTEM

Contact Unilock for more information.



RS-ACC074-1



RS-ACC087



10oz - RS-ADH039
28oz - RS-ADH040



RS-EDGE061




RS-ACC088

Base/Drainage Systems continued

GATOR TILE SYSTEM

Contact Unilock for more information.



STEP 1 • EXCAVATION FOR THE GATOR BASE INSTALLATION

The total depth required will be determined by adding the thickness of the sand or chip setting bed (3/4" [19 mm]), GATOR BASE (3/4" [19 mm]), and thickness of the paver, slab, stone, or porcelain tile. Excavation depth is approximately 4" for a 2 3/8" [60 mm] concrete paver. Excavate 6" (15 cm) wider than the perimeter of the paved surface or 12" wider (30 cm) when building a seating wall or fire pit.

STEP 2 • LEVELING AND COMPACTING OF THE SOIL

The bottom of the excavated area should be uniform and smooth (+/- 3/8" [10 mm] in 10') and slope in the same direction as the finished paver surface. Compact the soil using a vibrating plate or hand tamper in confined areas.

STEP 3 • ADD GATOR FABRIC GF4.4 AND INSTALL SETTING BED

Cover the bottom and sides of the excavated area with Gator Fabric GF4.4. Spread an even layer of sand (ASTM C33 Concrete Sand) or chip (ASTM No. 9 Stone) in a 3/4" [19 mm] thick layer over the Gator Fabric GF4.4. No compaction is needed for the chip stone. However, the sand-setting bed should be compacted using a hand tamper or vibrating plate. It will help to moisten the sand before compaction. The surface should be smooth, the finished paver surface will mirror the grade set in this step.

STEP 4 • INSTALL THE GATOR BASE

Cover the area with the GATOR BASE panels, 6" (15 cm) wider than the finished paver edge or 12" (30 cm) for a seating wall or fire pit. Lay the GATOR BASE units in an alternating (staggered) pattern - if the Gator Faces line up, the interlocking edges will align perfectly. Gator Base can easily be cut to size using a utility knife.

STEP 5 • INSTALL PAVERS, BLOCKS, AND GATOR EDGE

Place the pavers or blocks directly on the GATOR BASE. Adding a 1/2" (13 mm) of bedding sand onto the surface of the GATOR BASE is also an accepted method for non-uniform thickness stone. Install the Gator Edge on the GATOR BASE, firmly against the pavers or blocks. Use a Gator Base Screw every second edging hole to maximize the lateral support provided by the Gator Edge.

STEP 6 • APPLY GATOR MAXX G2 TO PAVER JOINTS

Visit alliancegator.com/gator-base/ for more details and videos.

Tools & Accessories



Install up to 700 sq. ft. per hour!

- Access tight or narrow areas
- Eliminate the need for a forklift on site
- Reduce labor costs
- Reduce shoulder, hand & knee pain and injury
- Improve your bottom line

Contact your local rep for details



MODEL
MINI P



MODEL P



MODEL L



NEW
ALL TERRAIN
PALLET MOVER



U-LEVEL™

- Easy to use
- Accurate readings
- Low maintenance
- Works in difficult locations
- Large working area

A PRECISION TOOL NO HARDSCAPER SHOULD BE WITHOUT



PISA XL LIFTING TONG

- The Pisa XL tong makes it easier to lift and place units, especially on the base course
- The action of lifting the handle secures the lifter and makes for easy, balanced lifting and placement.



VPR 450 PAVER ROLLER

- Centrifugal Force: 1,798 lbs
- Machine Weight: 238 lbs
- Base Plate Width: 16.5"
- Engine: Honda GX160 Four-Stroke

Calculations

AREA OF A CIRCLE

Radius (in.)	18	21	24	27	30	33	36	39	42	45	48	51	54	57
Radius (ft.)	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.235	4.50	4.75
Square Feet	7.07	9.62	12.56	15.90	19.63	23.75	28.26	33.17	38.47	44.16	50.24	56.72	63.59	70.85
Circumference (in.)	113.04	131.88	150.72	169.56	188.40	207.24	226.08	244.92	263.76	282.60	301.44	320.28	339.12	357.96
Circumference (Ft.)	9.42	10.99	12.56	14.13	15.70	17.27	18.84	20.41	21.98	23.55	25.12	26.69	28.26	29.83
Area of a circle = 3.14 x Radius x Radius														
Circumference = 6.28 x Radius														

AREA CONVERSION CHART

Square Feet	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Square Meter	0.09	0.19	0.28	0.39	0.46	0.56	0.65	0.74	0.84	0.93	1.02	1.11	1.21	1.30
Square Meter	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Square Feet	10.76	21.53	32.29	43.06	53.82	64.58	75.35	86.11	96.88	107.64	118.40	129.17	139.93	150.69
Cubic Yard	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Cubic Feet	27	54	81	108	135	162	189	216	243	270	297	324	351	378
Area Square = Length x Width														
Area Triangle = 1/2 Base x Height														

LINEAR DISTANCE CONVERSION CHART

Inches	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Centimeters	2.54	5.08	7.62	10.16	12.70	15.24	17.78	20.32	22.86	25.40	27.94	30.48	33.02	35.53
Centimeters	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Inches	0.39	0.79	1.18	1.57	1.97	2.36	2.76	3.5	3.54	3.94	4.33	4.72	5.12	5.51
Feet	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Meters	0.30	0.61	0.91	1.22	1.52	1.83	2.13	2.44	2.74	3.05	3.35	3.66	3.96	4.25
Meters	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Inches	39.37	78.74	118.11	157.48	196.85	236.22	275.59	314.96	354.33	393.70	433.07	472.44	511.81	551.18
Feet	3.28	6.56	9.84	13.12	16.40	19.69	22.97	26.25	29.53	32.81	36.09	39.37	42.65	45.93

WEIGHT CONVERSION CHART

Pounds	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Kilograms	0.45	0.91	1.36	1.81	2.27	2.72	3.18	3.63	4.08	4.54	4.99	5.44	5.90	6.35
Kilograms	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Pounds	2.20	4.41	6.61	8.82	11.02	13.23	15.43	17.64	19.84	22.05	24.25	26.46	28.66	30.86

Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.

BEDDING MATERIALS CHART (APPROXIMATE IMPERIAL TONS)

Bedding Course												
Square Feet	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.3	0.5	0.8	1.0	1.3	1.5	1.8	2.0	2.3	2.5	2.8	3.0
100	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0
150	0.8	1.5	2.3	3.0	3.8	4.5	5.3	6.0	6.8	7.5	8.3	9.0
200	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0
250	1.3	2.5	3.8	5.0	6.3	7.5	8.8	10.0	11.36	12.5	13.8	15.0
300	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	13.5	15.0	16.5	18.0
350	1.8	3.5	5.3	7.0	8.8	10.5	12.3	14.0	15.8	17.5	19.3	21.0
400	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.2	22.0	24.0
450	2.3	4.5	6.8	9.8	11.3	13.5	15.8	18.0	20.3	22.5	24.8	27.0
500	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	22.5	25.0	27.5	30.0
550	2.8	5.5	8.3	11.0	13.8	16.5	19.3	22.0	24.8	27.5	30.3	33.0
600	3.0	6.0	9.0	12.0	15.0	18.0	21.0	24.0	27.0	30.0	33.0	36.0
650	3.3	6.5	9.8	13.0	16.3	19.5	22.8	26.0	29.3	32.5	35.8	39.0
700	3.5	7.0	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
750	3.8	7.5	11.36	15.0	18.8	22.5	26.3	30.0	33.8	37.5	41.3	45.0
800	4.0	8.0	12.0	16.0	20.0	24.0	28.0	32.0	36.0	40.0	44.0	48.0
850	4.3	8.5	12.8	17.0	21.3	25.5	29.8	34.0	38.3	42.5	46.8	51.0
900	4.5	9.0	13.5	18.0	22.5	27.0	31.5	36.0	40.5	45.0	49.5	54.0
950	4.8	9.5	14.3	19.0	23.8	28.5	33.3	38.0	42.8	47.5	52.3	57.0
1000	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0

BASE DEPTH CHARTS (CUBIC YARDS)

Bedding Course												
Square Feet	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.2	0.3	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.5	1.7	1.9
100	0.3	0.6	0.9	1.2	1.5	1.9	2.2	2.5	2.8	3.1	3.4	3.7
150	0.5	0.9	1.4	1.9	2.3	2.8	3.2	3.7	4.2	4.6	5.1	5.6
200	0.6	1.2	1.9	2.5	3.1	3.7	4.3	4.9	5.6	6.2	6.8	7.4
250	0.8	1.5	2.3	3.1	3.9	4.6	5.4	6.2	6.9	7.7	8.5	9.3
300	0.9	1.9	2.8	3.7	4.6	5.6	6.5	7.4	8.3	9.3	10.2	11.1
350	1.1	2.2	3.2	4.3	5.4	6.5	7.6	8.6	9.7	10.8	11.9	13.0
400	1.2	2.5	3.7	4.9	6.2	7.4	8.6	9.9	11.1	12.3	13.6	14.8
450	1.4	2.8	4.2	5.6	6.9	8.3	9.7	11.1	12.5	13.9	15.3	16.7
500	1.5	3.1	4.6	6.2	7.7	9.3	10.8	12.3	13.9	15.4	17.0	18.5
550	1.7	3.4	5.1	6.8	8.5	10.2	11.9	13.6	15.3	17.0	18.7	20.4
600	1.9	3.7	5.6	7.4	9.3	11.1	13.0	14.8	16.7	18.5	20.4	22.2
650	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.1	20.1	22.1	24.1
700	2.2	4.3	6.5	8.6	10.8	13.0	15.1	17.3	19.4	21.6	23.8	25.9
750	2.3	4.6	6.9	9.3	11.6	13.9	16.2	18.5	20.8	23.1	25.5	27.8
800	2.5	4.9	7.4	9.9	12.3	14.8	17.3	19.8	22.2	24.7	27.2	29.6
850	2.6	5.2	7.9	10.5	13.1	15.7	18.4	21.0	23.6	26.2	28.9	31.5
900	2.8	5.6	8.3	11.1	13.9	16.7	19.4	22.2	25.0	27.8	30.6	33.3
950	2.9	5.9	8.8	11.7	14.7	17.6	20.5	23.5	26.4	29.3	32.3	35.2
1000	3.1	6.2	9.3	12.3	15.4	18.5	21.6	24.7	27.8	30.9	34.0	37.0

Actual volume may vary due to type of materials, moisture content, and compaction. Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.

IMPORTANT NOTES

UNILOCK PAVER PATTERNS

This Product Data Guide contains an extensive reference to patterns and designs. The purpose of these pattern swatches is to help the designer plan unique and exceptional designs. The percentages of products shown are based on the pattern and not on bundle configurations. In fact, there may be situations in which a pattern has been created with one particular size of stone, but that stone only comes packaged with two other sizes. This means that the designer will have to plan how the other components are used in the overall plan. This is usually accomplished by adding a border or an accent. As a result, overages or shortages may occur in certain patterns. The designer and/or installer of Unilock products accepts all responsibility for design and all associated costs incurred as a result of applying any of Unilock's suggested design patterns in a project. Please plan your project and review your order carefully prior to ordering.

TRANSFERABLE LIFETIME GUARANTEE

Unilock provides a Transferable Lifetime Guarantee* on the structural integrity of our paving stones, slabs and retaining wall units to the original purchaser of the product for residential use. Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Color matching cannot be guaranteed and replacement labor is not included. Proof of purchase is required.

Excessive defective material (over the industry accepted normal of 2% for non-tumbled unit pavers) delivered to the purchaser will be replaced free of charge if a written claim is made within 5 days of delivery from the manufacturer. Such claims will not constitute reason for delaying payment. All goods shall be deemed accepted if completely installed. Inspect concrete products prior to opening bundle packaging to ensure that shape and color are as ordered. Unsatisfactory material must be available for inspection by Unilock to entitle the purchaser to any adjustment or credit. Inspect all concrete units during installation and set aside any which are chipped or cracked to use for any cut pieces required. The color of concrete products may vary significantly between production lots. Always install concrete units from several bundles simultaneously to ensure proper distribution of color. Prior to final compaction, inspect installed pavers for good color distribution. Relocate certain pavers, if necessary, to achieve desired color blend.

*Transferable Lifetime Guarantee: Register your project within 60 days of your dated proof of purchase to ensure your Unilock Guarantee is fully transferable! Simply go online at unilock.com and follow instructions. Once processed, you will receive an original Transferable Warranty Certificate for your records.

PRODUCT HANDLING WARNING

Bundle Straps Under Tension - Use extreme caution when removing or handling straps. Always wear gloves, goggles, safety footwear, and protective clothing when removing or handling straps. Failure to do so may result in serious bodily injury or loss of sight.

Cut all concrete products only in well ventilated areas. Inhalation of dust is a serious health risk. A "NIOSH" (US) or a "CSA" (CDN) approved respirator, safety goggles, hearing protectors, and gloves must be worn at all times. Always "wet-cut" or "wet grind" concrete products to minimize dust.

Do not stack bundled concrete products higher than 2 bundles high. Contents of the bundle may be unstable and subject to topple when stacked. Always use extreme caution and appropriate equipment when transporting or storing bundled concrete products. Failure to do so may result in serious bodily injury or death. Always obey gross vehicle weight (GVW) loading limitations and regulations.

Hazard Rating: Fire 0, Health 1, Reactivity 0. See MSDS Concrete Masonry (Pavers). Contact Unilock for complete sheet or view safety information at Unilock.com.

Unilock assumes no liability or responsibility for loss or damage, resulting from the improper use or handling of our products, or from failure to follow instructions, warnings, and/or advisories on the product label, and on the MSDS sheet.

TRADEMARK & LEGAL INFORMATION

Umbriano® is a trademark of Metten Stein + Design GmbH & Co KG used under license by Unilock. Unilock Ltd. and Hengestone Holdings, Inc. are the owners or authorized users of all trademarks used in this publication unless otherwise specified.

Colors shown in this brochure should be used only as a guide. Colors should always be chosen from actual samples. Contact your local Unilock representative for color availability in your area. Not all products shown are available at all Unilock locations. Log on to www.unilock.com for availability. Measurements throughout this portfolio are nominal.

©2023 Hengestone Holdings, Inc.



QUALITY COMMITMENT

Unilock was the first concrete paver manufacturer in North America to offer a Lifetime Guarantee, and since then we have continued to stand behind it to ensure customers are completely satisfied with our products. With almost 2 billion stones in the ground, that's quite the commitment!

Our products are better and stronger than other brands. In fact, our internal standards of manufacturing in the USA and Canada far exceed industry standards set by ASTM (American Society for Testing and Materials) and CSA (Canadian Standards Association) and other European organizations.



LIFETIME GUARANTEE - RESIDENTIAL

Our Transferable Lifetime Guarantee warranties the structural integrity of Unilock concrete paving stones and retaining wall units when used in residential applications. It covers any structural failure or deterioration of the concrete unit resulting from normal use or from the reasonable application of sodium chloride (common rock salt used for de-icing). StoneMark™ products have the same warranties as Unilock paving stones and retaining walls, but cannot be warranted against damage resulting from de-icing products.

Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Proof of purchase is required. Customers are encouraged to submit receipts to us as soon as their project is complete, using the Unilock Warranty Registration Form on our website (Unilock.com).

Purchasers need to ensure that the product they purchase is appropriate for their intended application; for example, only certain thicknesses of products are appropriate for driveways. Color matching of the replacement product and/or lost time cannot be guaranteed and labor costs related to installing replacement product is not included. Unilock reserves the right to seek a professional diagnosis and opinion to determine the exact cause of the product failure. If the failure falls within our warranty parameters, Unilock will replace the defective product.

EXCLUSIONS – Unfortunately, some things are beyond the control of Unilock, and are therefore not covered by this warranty. These include: naturally occurring efflorescence, hazing from polymeric jointing sand, scratching and chipping resulting from snow removal or construction equipment, damage caused by natural or un-natural disasters, or negligence by anyone other than Unilock. While EasyClean helps to increase a paver's resistance to staining from various substances, it does not make our products stain-proof nor does it resist every kind of stain. The Unilock warranty also does

not cover deterioration or damage as a result of poor design or poor installation practices that are contrary to specifications as laid out by ICPI (Interlocking Concrete Pavement Institute) and the NCMA (National Concrete Masonry Association). For more information please visit www.icpi.org and www.ncma.org. Additionally, please refer to the Maintenance, Color and Installation Advisories.

MAINTENANCE ADVISORY

1. Cleaning and Sealing

As with anything that is outdoors, Unilock products are subject to harsh weather, dust, acid rain, leaf stains, water stains and general wear from foot or vehicular traffic. Therefore, periodic cleaning using environmentally safe detergents designed for cleaning concrete is recommended to maintain a bright, fresh appearance.

To make subsequent cleaning easier and more effective, a concrete sealer can be applied to new or cleaned products to help prevent the penetration of substances that can cause stains.

There are many types of concrete cleaners and sealers on the market. Always read the instructions carefully before using the product to make sure that it will function as expected. Testing first, in a small unobtrusive area, is always a good idea to ensure the results are acceptable. Consult your local hardscape dealer to find the products best suited for your paver or wall installation.



Visit Unilock.com to register for your Transferable Lifetime Guarantee.

2. Winter Maintenance

Snow removal by way of metal blades on plows or shovels will scratch and chip the surface of pavers, causing permanent damage. To mitigate this risk, metal snow clearing blades must always have a polyurethane or rubber cutting edge attached when plowing pavers.

De-icing Salts – The use of de-icing products on paver surfaces is important for safety and to help mitigate snow accumulation. Most de-icing products will have some effect on concrete, even if the product label indicates that it is safe on concrete. If you must use a de-icing product, we recommend that you use Sodium Chloride (ordinary rock salt) or Calcium Chloride (for colder climates). Always apply sparingly. The use of de-icing products on StoneMark, wet-cast pavers, slabs or coping may damage the product and therefore is not recommended. Whenever possible use a coarse sand as an anti-slip measure instead of de-icing chemicals.

COLOR ADVISORY

1. Selection

Due to the inherently variable nature of printed materials and digital monitors, Unilock cannot guarantee that products will match the color of printed or online images. Therefore, when making final product selections, decisions should be made based on actual stones which are readily available from Unilock, Authorized Contractors or Authorized Dealers. Most Unilock products are not comprised of a single color, but rather contain blended colors for a more natural appearance. This means that there will be significant color variance from stone to stone, so purchasers should view multiple units together to get a more accurate impression of the overall color.

Note: Unilock Natural Stone variations are outside the control of Unilock.

Purchasers of natural stone must be willing to accept this inherent variability.

2. Pre-installation checking

Always check the label to ensure that the Unilock product delivered to your project is the product and color ordered. If there is a discrepancy, or if the product inside the packaging doesn't appear to be correct, contact your hardscape dealer before installing any pavers or wall units. If the product is installed, it indicates your acceptance of the products as delivered.

3. Blending

If the project requires more than one bundle of product it's always a good idea to draw product from several bundles when installing, as this ensures that any variation between bundles will be seamlessly integrated in the project. When bundles are from different production runs, random selection from multiple bundles is even more important.

4. Efflorescence

Efflorescence is a naturally occurring process that may appear as a white or light grey powder on the surface of concrete, clay or natural stone. It is temporary, and will disappear over time. However, if it is bothersome, an efflorescence cleaner can be used to remove it. There is no way to predict or prevent efflorescence. Because it does not compromise the structural integrity of the product, it is not covered by Unilock product warranties.

INSTALLATION ADVISORY

1. Construction Residue

While a certain amount of dirt on pavers and walls is inevitable during the construction phase, installers are strongly encouraged to clean as they go as construction residue can embed in the surface and become difficult to remove. The slurry produced

during wet-saw cutting is particularly stubborn to clean if allowed to dry on the surface of pavers. Unilock warranties do not cover stains caused by a failure to remove construction residue.

2. Polymeric Haze

Surface hazing caused by polymeric jointing sand is not the responsibility of Unilock. Polymeric jointing sand should only be installed by an experienced and knowledgeable contractor. Any sand that is left on the surface prior to activation will result in a haze that is very difficult and time-consuming to remove. Only the highest quality, brand name polymeric sand that is guaranteed by the manufacturer should be used.

3. Compaction Damage

Both smooth and textured paver surfaces can be scratched by compaction equipment used to 'flatten' a new paver installation. Therefore, metal plate compactors must be fitted with a polyethylene mat to protect the paver surface from becoming scratched, or a superior option is to use a rubber-roller compactor instead. Damage to product surfaces caused by failure to follow these instructions is not covered by Unilock product warranties.

FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.


FINISHES



Umbriano®
Mottled Finish with
ColorFusion™ and EasyClean



Series™
Exposed Granite Finish



Il Campo®
Brushed Finish




Smooth
Premier Finish



Flagstone
Premier Finish



Antiqued
Timeworn Finish



Classic
Thrumix Finish

COLOR BLEND DESCRIPTIONS

COLOR NAME	DESCRIPTION
Avorio	Solid Beige/Tan
Basalt	Blueish-Black
Bavarian	Brown, Cream and Charcoal
Birch	Dark Brown, Light Brown and Cream
Black Granite	Black Granite and Charcoal
Burgundy Red	Plum with Red
Burnt Clay	Brown with Red
Cocoa Brown	Solid Dark Brown
Corvara	Light Grey/Beige
Dark Charcoal	Dark Charcoal
Dawn Mist	Grey and Tan
Desert Sand	Salmon, Buff and Charcoal
Fieldstone	Buff and Grey
Fossil	Light & Dark Grey, Chamois and White Accents
French Grey	Light Grey with White Flake
Granite	Natural and Charcoal
Limestone	Light Gray and Charcoal

COLOR NAME	DESCRIPTION
Midnight Sky	Charcoal and Black Flake
Modena	White Concrete with Black Flecks
Natural Blend	Light Grey and Medium Grey
Nevada	Chamois and Natural
Old Oak	Rust with Red
Opal Blend	Light Grey and White
Pebble Taupe	Tan with Light Brown
Rustic Red	Red and Charcoal
Sable Blend	Cream Tan Brown
Sandstone	Buff and Tan
Sierra	Charcoal, Russet and Buff
Steel Grey Blend	Dark Charcoal & Grey
Steel Mountain	Natural and Charcoal
Summer Wheat	Cream White with Pale Yellow & Beige Particles
Terra Cotta	Salmon and Charcoal
Vivanto	Dark Grey and Charcoal
Winter Marvel	White and Black Flake

OHIO PRODUCT DIRECTORY

UNIT PAVERS

Product	Page	Finish	Pedestrian	Residential Vehicular	Commercial Vehicular	Environmental	For Borders & Accents
Arcana™	4	S	✓				
Artline™	5	S	✓				✓
Beacon Hill™ Flagstone	6	F	✓				
Beacon Hill™ Smooth	7	SM	✓				
Boulevard™	8	F	✓	✓			✓
Bristol Valley®	9	S	✓				
Brussels Block®	10	W		✓			✓
Camelot™	11	S	✓	✓	✓		✓
Copthorne®	12	T	✓	✓			✓
Courtstone®	13	C	✓	✓			✓
Eco-Line™	14	S	✓	✓	✓	✓	
Eco-Optiloc™	15	S	✓	✓	✓	✓	
Eco-Priora™	16	B	✓	✓	✓	✓	
Eco-Promenade™	17	S	✓	✓	✓	✓	
Hex Paver	18	S	✓	✓			
Hollandstone™	19	S	✓	✓	✓		✓
Holland Premier®	20	S	✓	✓	✓		✓
Il Campo®	21	B	✓	✓	✓		✓
Mattoni™	22	T	✓	✓			✓
Natural Stone	23		✓				
Optiloc™	27	S	✓	✓	✓		
Porcelain	28		✓				
Promenade™ Paver	31	S	✓	✓	✓		
Promenade™ Premier	32	S	✓	✓	✓		
Richcliff®	34	F	✓	✓			✓
Series™	35	WS	✓	✓	✓		✓
Skyline™	36	S	✓				
Soreno™	37	S	✓				
Thornbury™	38	F	✓	✓	✓		
Town Hall®	39	T	✓	✓	✓	✓	✓
Treo® Premier	40	F	✓	✓			✓
Treo® Smooth NEW	41	SM	✓	✓			✓
Tribeca Cobble	42	C	✓	✓			✓
Turfstone™	43	S		✓		✓	
Umbriano®	44	SZ	✓	✓	✓		✓
Westport™	47	F	✓	✓			✓

RETAINING WALLS

Product	Page	Finish	Gardens	Retaining Walls	Steps	Seatwalls	Pillars
Brussels Dimensional System™	48	W	✓	✓	✓	✓	✓
Dimensional Smooth™ NEW	49	SM	✓	✓	✓	✓	✓
DuraHold®	50	S		✓			
DuraHold2®	52	S		✓			
Estate Wall™	53	SP/W	✓	✓	✓	✓	✓
Lineo™ Dimensional Stone	54	SZ	✓	✓	✓	✓	✓
Pisa2® & Pisa2 XL	55	SP	✓	✓	✓	✓	✓
Pisa Smooth™ NEW	56	SP	✓	✓	✓	✓	✓
RomanPisa™	57	SP/W	✓	✓	✓	✓	✓
RomanStack™	58	SP/W	✓				
SienaEdge®	59			✓	✓		
SienaStone®	60	SP		✓	✓		
Split'nStack™	61	SP	✓				
U-Cara®	62	Various	✓	✓	✓	✓	✓


Finishes: B=Brushed; C=Cobblestone; D=Dimpled; DW=Dimpled and Weathered; F=Flagstone; S=Standard; SM=Smooth; SZ=Smooth Zero Bevel; SP=Split; SP/W=Split and Weathered; T=Timeworn; W=Weathered; WS=Washed

This application chart should only be used as a guide. Site conditions, base materials, pattern and frequency of use may vary the performance of various types and styles of products.



THE MOST COMPLETE HARDSCAPE WALL SYSTEM





Let's **BUILD YOUR BUSINESS** **together.**

**CONTACT 1-800-UNILOCK OR VISIT UNILOCK.COM TO
CONNECT WITH YOUR LOCAL TERRITORY MANAGER**

BOSTON
(508) 278-4536

CHICAGO
(630) 892-9191

MILWAUKEE
(262) 742-3890

KANSAS
(913) 417-7985

MICHIGAN
(248) 437-7037

NEW YORK
(845) 278-6700

MID-ATLANTIC
(202) 798-2060

ONTARIO
(416) 646-9000

CINCINNATI/KY/TN
(513) 202-0219

**OHIO/WESTERN PA/
WNY&CNY**
(330) 927-4000

UNILOCK.COM | 1-800-UNILOCK

©2023 Hengestone Holdings, Inc.