



Beacon Hill™ Smooth 80mm

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS

BEACON HILL™ SMOOTH 80mm

ENDURACOLOR™



ALMOND GROVE FUSION



GRANITE FUSION



OPAL BLEND

34
SRI



TUSCANY

39
SRI



DARK BROWN

SMALL RECTANGLE BUNDLE ONLY



MIDNIGHT CHARCOAL

SMALL RECTANGLE BUNDLE ONLY



OPAL BLEND

SMALL RECTANGLE BUNDLE ONLY

34
SRI



SMALL RECTANGLE BUNDLE

7 x 14 x 3 1/8"

190 x 380 x 80mm

RECOMMENDED SAND



Gator G2 MAXX Sand

- | Setting time - 15 mins
- | Sets above 32° F/ 0° C
- | Can be applied if rain is expected (min. 1 hr)
- | Dust free and haze free
- | Requires only one watering
- | Four colours: Beige, Grey, Black and Ivory

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Grey, Ivory <i>50lb. bag</i>	65-85 sqft	22-42 sqft
Black <i>50lb. bag</i>	58-76 sqft	20-38 sqft

RECOMMENDED SEALER



Gator Natural Look Sealer

- | Water-based
- | Zero gloss finish
- | Multi purpose
- | Rain safe after 24 hours

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L. / 5.28 U.S. gal.	875 sqft

PRODUCT ATTRIBUTES

Visual Appearance	Beacon Hill Smooth offers a smooth surface texture for a sleek, modern look with a contemporary colour palette.
Finish	Smooth with Enduracolor finish.

PRODUCT SPECIFICATIONS



LARGE RECTANGLE
15 x 22 7/16 x 3 1/8"
380 x 570 x 80mm




SQUARE
15 x 15 x 3 1/8"
380 x 380 x 80mm




SMALL RECTANGLE
7 x 14 x 3 1/8"
190 x 380 x 80mm

3 UNIT RANDOM BUNDLE

LAYING PATTERNS



BHS A
14% Small Rectangle, 28%
Square, 28% Large Rectangle,
28% XL Rectangle




BHS B
14% Small Rectangle, 28%
Square, 28% Large Rectangle,
28% XL Rectangle

EDGE DETAILS



ROUNDED EDGE

BUNDLE CONFIGURATION



TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy +/- 3mm

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

TECHNICAL ADVANTAGES

ENDURACOLOR™

Refined surface and long-lasting colour

DRIVE FRIENDLY

80mm pavers can handle vehicular loads
Ask about our base stabilization system

PRODUCT DATA (CURRENT)

Stones & Bundling	Unit Thickness	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per		Lbs Per		
		Bundle	Layer	Section	Stone	Layers	Section	SqFt	Section	Bundle	SqFt	Layer	Bundle	SqFt	Bundle	Layer	Section	Bundle
Pickering Manufacturing / Beacon Hill Flagstone 6cm Almond Grove Fusion stocked in Ayr																		
Random Bundle		73.22	10.46			7	-	-	-	-	0.99		74.4	0.77	56	383	-	2,680
Large Rectangle	3 1/8" (80mm)	-	-	-	2.09	-	-	-	-	-	1.18		24.8	0.48	14		-	-
Small Rectangle	3 1/8" (80mm)	-	-	-	0.70	-	-	-	-	-	0.59		24.8	1.43	21		-	-
Square	3 1/8" (80mm)	-	-	-	1.40	-	-	-	-	-	1.18		24.8	0.72	21		-	-
Small Rectangle (Smooth only)	3 1/8" (80mm)	73.24	10.46		0.70	7	-	1.17	-	78.75	0.58	-	157.5	1.43	105	383	-	2,680

Notes: Sold in full bundles only on a refundable skid. **Beacon Hill 80mm is approved for vehicular applications.** All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information. *For custom options, please contact your Unilock Territory Manager.

* Addendum to Bundle Configurations coming soon!

APPLICATIONS



Pedestrian



Commercial Vehicular



Residential Vehicular



*Wall pairing suggestion- U-CARA® - matching colour and finish